Surface Evolver Manual

Version 1.95
June 24, 1994

Kenneth A. Brakke

The Geometry Center
1300 South Second Street
Minneapolis, MN 55454

and

Susquehanna University
Selinsgrove, PA 17870

brakke@geom.umn.edu

Table of Contents

1. Introduction. 1
2. Installation. 2
    2.1. Acquisition. 2
    2.2. Environment. 3
    2.3. Files. 3
    2.4. Unix Compilation. 4
        2.4.1. X-Windows graphics. 4
    2.5. Customizing graphics. 4
        2.5.1. Random-order interface. 4
        2.5.2. Painter interface. 5
3. Tutorial. 6
    3.1. Basic Concepts. 6
    3.2. Example 1. Cube evolving into a sphere. 6
    3.3. Example 2. Mound with gravity. 9
    3.4. Example 3. Catenoid. 11
    3.5. Example 4. Torus partitioned into two cells. 13
    3.6. Example 5. Ring around rotating rod. 15
    3.7. Example 6. Column of liquid solder. 18
    3.8. Example 7. Rocket fuel tank. 21
        3.8.1. Surface energy. 21
        3.8.2. Volume. 22
        3.8.3. Gravity. 23
        3.8.4. Running. 24
    3.9. Example 8. Spherical tank. 26
        3.9.1. Surface energy. 27
        3.9.2. Volume. 27
        3.9.3. Gravity. 28
        3.9.4. Running. 29
    3.10. Example 9. Crystalline integrand. 31
4. The Model. 33
    4.1. Geometric elements. 33
        4.1.1. Vertices. 33
        4.1.2. Edges. 33
        4.1.3. Facets. 33
        4.1.4. Bodies. 34
    4.2. Quadratic represention. 34
    4.3. Dimension of surface. 34
    4.4. Simplex model. 34
    4.5. Dimension of ambient space. 35
    4.6. Riemannian metric. 35
    4.7. Torus domain. 35

4.8. Quotient spaces. 36
4.9. Symmetric surfaces. 36
4.10. Constraints. 36
4.11. Boundaries. 37
4.12. Energy. 37
4.13. Named quantities and methods. 39
4.14. Numbered surface integrals (obsolete). 40
4.15. Pressure. 41
4.16. Volume or content. 41
4.17. Diffusion. 42
4.18. Motion. 42
4.19. Hessian. 42
4.20. Mobility. 43
4.20.1. Vertex mobility. 43
4.20.2. Area normalization. 44
4.20.3. Area normalization with effective area. 44
4.20.4. Approximate polyhedral curvature. 44
4.20.5. Approximate polyhedral curvature with effective area. 44
4.20.6. User-defined mobility. 44
4.21. Stability. 44
4.21.1. Zigzag string. 44
4.21.2. Perturbed sheet with equilateral triangulation. 45
4.22. Topology changes. 45
4.23. Refinement. 45
4.24. Adjustable constants and parameters. 45
4.25. The String Model. 46
5. The Datafile. 47
5.1. Lexical format. 47
5.1.1. Comments. 47
5.1.2. Lines and line splicing. 47
5.1.3. Including files. 47
5.1.4. Macros. 47
5.1.5. Case. 47
5.1.6. Whitespace. 47
5.1.7. Identifiers. 47
5.1.8. Real numbers. 47
5.1.9. Keywords. 47
5.1.10. Colors. 49
5.1.11. Expressions. 49
5.2. Datafile organization. 50
5.2.1. Definitions and options. 50
5.2.2. Element lists. 61
5.2.3. Vertex list. 61

5.2.4. Edge list. 61
5.2.5. Face list. 62
5.2.6. Bodies. 62
5.2.7. Commands. 63
6. Operation. 64
6.1. System command line. 64
6.2. Initialization. 64
6.3. Error handling. 64
6.4. Commands. 65
6.4.1. General language syntax. 65
6.4.2. Single-letter command summary. 66
6.5. Alphabetical single-letter command reference. 67
6.6. Command and query language. 72
6.7. Graphics. 83
6.8. Script examples. 85
6.9. Interrupts. 87
6.10. Graphics output file formats. 87
6.10.1. Pixar 87
6.10.2. Geomview. 88
6.10.3. PostScript. 88
6.10.4. Triangle file. 88
6.10.5. SoftImage file. 88
7. Technical Reference. 91
7.1. Notation. 91
7.2. Surface representation. 91
7.3. Energies and forces. 91
7.3.1. Surface tension. 91
7.3.2. Crystalline integrand. 92
7.3.3. Gravity. 92
7.3.4. Constraint integrals. 92
7.3.5. Surface integrands. 93
7.3.6. Gap areas. 93
7.3.7. Ideal gas compressibility. 93
7.3.8. Prescribed pressure. 94
7.3.9. Squared mean curvature. 94
7.3.10. Squared Gaussian curvature. 95
7.4. Named quantities and methods. 95
7.4.1. Vertex value. 96
7.4.2. Edge length. 96
7.4.3. Facet area. 96
7.4.4. Path integrals. 96
7.4.5. Line integrals. 96
7.4.6. Scalar surface integral. 96

7.4.7. Vector surface integral. 97
7.4.8. 2-form surface integral. 97
7.4.9. General edge integral. 97
7.4.10. General facet integral. 97
7.4.11. String area integral. 97
7.4.12. Volume integral. 97
7.4.13. Gravity. 98
7.4.14. Hooke energy. 98
7.4.15. Local Hooke energy. 99
7.4.16. Integral of mean curvature. 99
7.4.17. Integral of squared mean curvature. 99
7.4.18. Integral of Gaussian curvature. 99
7.4.19. Average crossing number. 99
7.4.20. Knot energies. 99
7.5. Volumes. 102
7.5.1. Default facet integral. 102
7.5.2. Symmetric content facet integral. 103
7.5.3. Edge content integrals. 103
7.5.4. Volume in torus domain. 103
7.6. Quantity integrands. 104
7.6.1. Quantity of a facet. 105
7.6.2. Quantity of an edge. 105
7.7. Constraint projection. 105
7.7.1. Projection of vertex to constraints. 105
7.7.2. Projection of vector onto constraint tangent space. 105
7.8. Volume and quantity constraints. 105
7.8.1. Volume restoring motion. 106
7.8.2. Motion projection in gradient mode. 106
7.8.3. Force projection in mean curvature mode. 106
7.9. Iteration. 106
7.9.1. Fixed scale motion. 106
7.9.2. Optimizing scale motion. 107
7.9.3. Conjugate gradient mode. 107
7.10. Hessian iteration. 108
7.11. Equiangulation. 109
7.12. Dihedral angle. 110
7.13. Area normalization. 110
7.14. Hidden surfaces. 110
7.15. Extrapolation. 111
7.16. Curvature test. 111
7.17. Annealing (jiggling). 111
7.18. Long wavelength perturbations (long jiggling). 111
7.19. Homothety. 111

7.20. Popping non-minimal edges. 111
7.21. Popping non-minimal vertex cones. 112
7.22. Refining. 112
7.23. Refining in the simplex model. 112
7.24. Removing tiny edges. 112
7.25. Weeding small triangles. 113
7.26. Vertex averaging. 113
7.27. Zooming in on vertex. 113
7.28. Mobility and approximate curvature. 113
8. Helpful hints and notes. 116
9. Bugs. 117
10. Version history. 118
11. Bibliography. 126
12. Index. 128
Figures.
Figure 1. Cube for example 1
Figure 2. Mound for example 2
Figure 3. Tank for example 4
Figure 4. Sphere for example 5

Chapter 1. Introduction.

The Surface Evolver is an interactive program for the study of surfaces shaped by surface tension and other energies. A surface is implemented as a simplicial complex, that is, a union of triangles. The user defines an initial surface in a datafile. The Evolver evolves the surface toward minimal energy by a gradient descent method. The evolution is meant to be a computer model of the process of evolution by mean curvature, which was studied in [B1] for surface tension energy in the context of varifolds and geometric measure theory. The energy in the Evolver can be a combination of surface tension, gravitational energy, squared mean curvature, user-defined surface integrals, or knot energies. The Evolver can handle arbitrary topology (as seen in real soap bubble clusters), volume constraints, boundary constraints, boundary contact angles, prescribed mean curvature, crystalline integrands, gravity, and constraints expressed as surface integrals. The surface can be in an ambient space of arbitrary dimension, which can have a Riemannian metric, and the ambient space can be a quotient space under a group action. The user can interactively modify the surface to change its properties or to keep the evolution well-behaved. The Evolver was written for one and two dimensional surfaces, but it can do higher dimensional surfaces with some restrictions on the features available. Graphical output is available as screen graphics and in several file formats, including PostScript.

The Surface Evolver program is freely available (see chapter 2) and is in use by a number of researchers. Some of the applications of the Evolver so far include modelling the shape of fuel in rocket tanks in low gravity [Te], calculating areas for the Opaque Cube Problem [B4], computing capillary surfaces in cubes [MH] and in exotic containers [C], simulating grain growth, studying grain boundaries pinned by inclusions, finding partitions of space more efficient than Kelvin's tetrakaidecahedra [WP], modelling the shape of molten solder on microcircuits [RSB], studying polymer chain packing, and classifying minimal surface singularities.

The strength of the Surface Evolver program is in the breadth of problems it handles, rather than optimal treatment of some specific problem. It is under continuing development, and users are invited to suggest new features.

This manual contains full operational details and mathematical descriptions. A journal article description of the Evolver appeared in [B2].

The Evolver is written in portable C and has been run on several systems: Sun, Iris, NeXT, Xenix, Dec, MS-DOS, Macintosh, and HP 98731. It is meant to be easily portable to any system that has C.

The Evolver was written as part of the Geometry Supercomputing Project (now The Geometry Center), sponsored by the National Science Foundation, the Department of Energy, Minnesota Technology, Inc., and the University of Minnesota. The program is in the public domain.

Bug reports should be submitted by email to `brakke@geom.umn.edu`. Please include the Evolver version number, a description of the problem, the initial data file, and the sequence of commands necessary to reproduce the problem.

Previous users of the Evolver should consult the History chapter for the new features.

Newsletter. The group of Surface Evolver users has grown large enough that I have started a newsletter. Contents include:

- Latest features added to Evolver.
- Future plans for new features.
- Suggestions for new features, with the likelihood of their being added proportional to demand.
- Bibliography of papers using Evolver, hopefully with brief abstracts.
- Workshops, talks, etc. to be given.
- Descriptions of projects underway using Evolver.
- List of systems users have ported Evolver to.
- Anything else anybody would wish to contribute.

If you would like to be on the mailing list, send your email address to `brakke@geom.umn.edu`.

Chapter 2. Installation.

This chapter explains how to get and install the Evolver. Evolver is written to be portable between systems. The only requirement is a C compiler. Graphics on different systems may need customizing; see the section on graphics porting below.

§2.1. Acquisition.

The Evolver program is public domain, and there is no charge for it.

If you can connect to Internet and can use ftp, do a ftp login to `geom.umn.edu` (128.101.25.35) as "anonymous" with your email address as password. From the `pub/software/evolver` directory, get `evolver.tar.Z` (970Kbytes). This archive contains source code, datafiles, and this manual. See below for special versions for NeXTs, Macs, and PCs.

The program is distributed in a compressed tar file `evolver.tar.Z`. Get this file into a working directory. Uncompress it with

```
uncompress evolver.tar
```

(yes, leave off the `.Z`). Extract the files with

```
tar xvf evolver.tar
```

This will unpack into three subdirectories: src (source code), doc (the manual), and fe (sample datafiles).

If you cannot use ftp, you can get Evolver on a floppy disk. Send email to `brakke@geom.umn.edu` or write to

> Kenneth A. Brakke
> Mathematics Department
> Susquehanna University
> Selinsgrove, PA 17870
> USA

Indicate what format you can handle: 5 1/4" or 3 1/2" floppy, tar, compressed, MS-DOS, etc.

This complete manual is in TeX DVI format in `manual.dvi`. Print it out however you print DVI files. If you can't handle it, you can ask for a hardcopy from `brakke@geom.umn.edu`. The figures to accompany the tutorial examples in the manual are in PostScript files `*.ps`, which can be sent direct to any PostScript printer.

For those with NeXTs, there is also a separate ftp archive `pub/software/evolver/evolver.next.tar.Z` which contains a NeXT executable Evolver and Interface Builder files. This version will only run from a NeXT console. Even though there is a command line option (-u) to not display graphics, it still insists on access to the screen. If you want a version you can run remotely, get the source code and compile vanilla version with no graphics or X windows graphics.

For those with Macintoshes, there is a Mac version available for anonymous ftp from geom.umn.edu as `pub/software/evolver/evolver.sit.hqx`. This is a binhexed Stuffit 1.5.1 archive. It includes a README file with Mac specific information and datafiles in Mac format.

For those with PC compatibles, there is a 32-bit DOS version in `pub/software/evolver/evolver.zip`. This PKZIP archive contains evolver.exe and the DOS extender program needed to run it, and a few datafiles. It was made with the Free Software Foundation's DJGPP compiler. For further instructions, see evolver.doc in evolver.zip.

Screen graphics generally uses an external graphics program. There is an X-Windows graphics interface, and the NeXT version uses NeXT graphics. The best graphics, however, are done on Silicon Graphics systems with the `geomview` graphics program. `geomview` is available by anonymous ftp from `geom.umn.edu`. There is also a version of `geomview` for the NeXT, and one is under development for X-Windows. Beware, though,

that X-geomview has to emulate all 3D graphics in software, as X-windows is a 2D system. Hence X-geomview is slower, and does not use any built-in 3D graphics hardware a machine may have. It is also still under development, and may have a few bugs and porting problems. X-geomview is available by anonymous ftp from geom.umn.edu in /pub/software/geomview. There are precompiled binaries in geomview-next.tar and geomview-sun.x11-beta.tar.Z, and source in geomview-src.x11-beta.tar.Z for other systems.

§2.2. Environment.

Evolver needs to find the initial data file and sometimes other files (e.g. command files for the "read" command). If the named file is not in the current directory, then an environment variable called `EVOLVERPATH` will be consulted for a directory search list. The format is the same as the usual `PATH` variable. Set it up as usual in your system:

Unix C shell:

```
setenv EVOLVERPATH /usr/you/fe:/usr/you
```

Bourne shell:

```
EVOLVERPATH=/usr/you/fe:/usr/you
export EVOLVERPATH
```

MS-DOS:

```
set EVOLVERPATH=c:\evolver\fe;d:\misc
```

For the MS-DOS version, see the file `evolver.doc` included in `evolver.zip` for some optional environment variables.

Output files are written to the filename given by the user in response to a prompt, so include the path you want.

§2.3. Files.

Documentation in subdirectory `doc`:

```
manual.dvi
*.ps
```

In subdirectory `src`:

For datafile and command parsing (user should not remake these):

`datafile.lex`	lex source for lexyy.c
`command.yac`	yacc source for ytab.c

For compilation:

```
Makefile
*.c
*.h
```

Screen graphics interfaces:

`xgraph.c`	X-Windows graphics interface
`geomgraph.c`	`geomview` interface for Silicon graphics
`iriszgraph.c`	Silicon Graphics GL graphics
`irisstereo.c`	does stereo displays on Irises so equipped

`hpzgraph.c`	HP 98731 graphics
`gnugraph.c`	graphics for DOS DJGPP version
`nulgraph.c`	no screen graphics

Evolver data files in subdirectory `fe`:

`*.fe`	(initial data files)
`*.wlf`	(Wulff vector files)
`jcmap`	(sample color map file)

You may put the data and colormap files in various directories. Evolver checks the environment variable `EVOLVERPATH` for data file paths.

§2.4. Unix Compilation.

First, you need to modify `Makefile` for your system. `Makefile` begins with sets of macro definitions for various systems. If your system is listed, remove the comment symbols '`#`' from start of your definitions. If your system is not there, use the `GENERIC` defines, or set up your own, and leave the graphics file as `nulgraph`. If you do define your own, be sure to put a corresponding section in `include.h`. After you get a working program you can write a screen graphics interface if you wish. Edit `CFLAGS` to have the proper options (optimization, floating point option, etc.). `GRAPH` should be the name of a screen graphics interface file (see list under **Files** above, or write your own as discussed below). `GRAPHLIB` should be the appropriate graphics library plus any other libraries needed. Check all paths and change if necessary for your system.

If you want Evolver to be able to use geomview, incldue `-DOOGL` in CFLAGS.

If you want Evolver to operate in a different space dimension than the default of 4, include `-DMAXCOORD=6` in CFLAGS. This sets the upper limit of dimensionality, and is used for allocating space in data structures.

Silicon Graphics systems with multiple processors may compile a version that will use all processors for some calculations by including `-DSGI_MULTI` in CFLAGS. This version will run fine with one processor, also. Currently, the only calculations done in parallel are the "named quantities".

The file `include.h` lists the include files for various systems. If your system isn't listed, you will have to put in a list of your own. Try copying the generic list (or one of the others) and compiling. Your compiler will no doubt be very friendly and helpful in pointing out unfound header files.

`include.h` also has various other system-specific defines. See the `GENERIC` section of it for comments on these, and include the appropriate ones for your system.

Now try compiling. Hopefully, you will only have to change the system-specific parts of `Makefile` and `include.h` to get things to work. If significant changes to other files are needed, let me know. For example, the return value of `sprintf()` varies among systems, and that caused problems once upon a time.

Test by running on the cube sample file as described in the **Tutorial** chapter.

§2.4.1. X-Windows graphics.

To have Evolver use X-Windows graphics for its native graphics, edit `Makefile` to have `xgraph` as the graphics module and have all the proper libraries linked in. The X window will appear when you do the "`s`" command. Evolver does not continually poll for window redraw events, so if you move or resize the window you will have to do "`s`" again to redraw the surface. You may also be interested in the X version of geomview mentioned above.

§2.5. Customizing graphics.

This section is provided for those people who need to write their own graphics interface module. All device-specific graphics output has been collected into a few basic routines. There are two styles of interface. One provides facets in random order for routines that can do their own hidden surface removal. The other provides facets in back to front order (painter algorithm).

§2.5.1. Random-order interface.

The random-order interface has several global pointers to functions which should be set to the user's functions. This permits several sets of graphics routines in one program. The facets are generated by `graphgen()`, which call the user functions. The function `display()` is called as the overall display function; it should set the function pointers and call `graphgen()`. Example: `iriszgraph.c`

The function pointers are:

`void (*graph_start)(void)`

This is called at the start of each display. It should do whatever device initialization and screen clearing is needed.

`void (*graph_facet)(struct graphdata *,facet_id)`

This is called to graph one triangular facet. See `extern.h` for the definition of `graphdata`. The second argument is a facet identifier for routines that are not happy with just the information in `graphdata`; it is for Evolver gurus only. Facets are presented in random order. The coordinates are not transformed; the current transformation matrix is in `view[][]`, which is in homogeneous coordinates.

`void (*graph_edge)(struct graphdata *)`

This function is called to graph one edge in the string model.

`void (*graph_end)(void)`

This function is called after all data has been given.

§2.5.2. Painter interface.

The painter model is similar, except there is an extra layer of functions. Example: `xgraph.c`, `psgraph.c`, `gnugraph.c`. In `display()`, the user should set

```
graph_start = painter_start;
graph_facet = painter_facet;
graph_end   = painter_end;
```

The user should also set these function pointers:

`void (*init_graphics)(void)`

Called by `painter_start()` to do device initialization.

`void (*display_facet)(struct tsort *)`

Called by `painter_end()` to graph sorted facets one at a time. See `extern.h` for `struct tsort`.

`void (*finish_graphics)(void)`

Called at the end of all facets.

The user should set `graph_edge` as in the random interface.

Chapter 3. Tutorial.

This chapter introduces some basic concepts and then guides the user through a series of examples. Not all the sample datafiles that come with Evolver are discussed; users may browse them at their liesure. This chapter can be read before the following chapters. The following chapters assume you have read the Basic Concepts section of this chapter.

§3.1. Basic Concepts.

The basic geometric elements used to represent a surface are vertices, edges, facets, and bodies. Vertices are points in Euclidean 3-space. Edges are straight line segments joining pairs of vertices. Facets are flat triangles bounded by three edges. A surface is a union of facets. (Actually, there is no separate surface entity in the program; all facets essentially belong to one logical surface.) A body is defined by giving its bounding facets.

The term "surface", when used to refer to the entity upon which the Evolver operates, refers to all the geometric elements plus auxiliary data such as constraints, boundaries, and forces.

There are no limitations on how many edges may share a vertex nor on how many facets may share an edge. Thus arbitrary topologies are possible, including the triple junctions of surfaces characteristic of soap films.

Edges and facets are oriented for bookkeeping purposes, but there are no restrictions on the orientation of neighboring facets. Unoriented surfaces are thus possible.

A surface is deemed to have a total energy, arising from surface tension, gravitational energy, and possibly other sources. It is this energy which the Evolver minimizes.

No particular units of measurement are used. The program only deals with numerical values. If you wish to relate the program values to the real world, then all values should be within one consistent system, such as cgs or mks.

The initial surface is specified in a text file (hereafter referred to as the datafile) that may be created with any standard text editor. (The `.fe` extension I always use for datafiles stands for facet-edge, which refers to the internal data structure used to represent the surface. You may use any name you wish for a datafile.)

The basic operation of the Evolver is to read in a datafile and take commands from the user. The main command prompt is

```
Enter command:
```

Basic commands are one letter (case is significant), sometimes with a numerical parameter. The most frequently used commands are:

`g` n	do n iterations
`s`	show surface on screen (or `P` option 8 for geomview)
`r`	refine triangulation of surface
`P`	graphics output (option 3 for PostScript)
`q`	quit

There is also a more elaborate command language (in which case is not significant). Commands must be followed with the `ENTER` key; Evolver only reads complete lines.

An iteration is one evolution step. The motion for the step is calculated as follows: First, the force on each vertex is calculated from the gradient of the total energy of the surface as a function of the position of that vertex. The force gives the direction of motion. Second, the force is made to conform to whatever constraints are applicable. Third, the actual motion is found by multiplying the force by a global scale factor.

§3.2. Example 1. Cube evolving into a sphere.

A sample datafile `cube.fe` comes with Evolver. The initial surface is a unit cube. The surface bounds one body, and the body is constrained to have volume 1. There is no gravity or any other force besides surface tension. Hence the minimal energy surface will turn out to be a sphere. This example illustrates the basic datafile format and some basic commands.

Let's look at the datafile that specifies the initial unit cube (see Figure 1 for a sketch):

```
// cube.fe
// Evolver data for cube of prescribed volume.

vertices  /* given by coordinates */
1  0.0 0.0 0.0
2  1.0 0.0 0.0
3  1.0 1.0 0.0
4  0.0 1.0 0.0
5  0.0 0.0 1.0
6  1.0 0.0 1.0
7  1.0 1.0 1.0
8  0.0 1.0 1.0

edges  /* given by endpoints */
1   1 2
2   2 3
3   3 4
4   4 1
5   5 6
6   6 7
7   7 8
8   8 5
9   1 5
10  2 6
11  3 7
12  4 8

faces  /* given by oriented edge loop */
1   1 10 -5  -9
2   2 11 -6 -10
3   3 12 -7 -11
4   4  9 -8 -12
5   5  6  7   8
6  -4 -3 -2  -1

bodies  /* one body, defined by its oriented faces */
1   1 2 3 4 5 6  volume 1
```

The datafile is organized in lines, with one geometric element defined per line. Vertices must be defined first, then edges, then faces, then bodies. Each element is numbered for later reference in the datafile.

Comments are delimited by `/* */` as in C, or follow `//` until the end of the line as in C++. Case is not significant, and all input is lower-cased immediately. Hence error messages about your datafiles will refer to items in lower case, even when you typed them in upper case.

The datafile syntax is based on keywords. The keywords `VERTICES`, `EDGES`, `FACES`, and `BODIES` signal the start of the respective sections. Note that the faces are not necessarily triangles (which is why they are called `FACES` and not `FACETS`). Any non-triangular face will be automatically triangulated by

putting a vertex at its center and putting in edges to each of the original vertices. Faces don't have to be planar. Note that a minus sign on an edge means that the edge is traversed in the opposite direction from that defined for it in the `EDGES` section. The face oriented normal is defined by the usual right hand rule. The cube faces all have outward normals, so they all are positive in the body list. In defining a body, the boundary faces must have outward normals. If a face as defined has an inward normal, it must be listed with a minus sign.

That the body is constrained to have a volume of 1 is indicated by the keyword `VOLUME` after the body definition, with the value of the volume following. In general, any attributes or properties an element has are given on the same line after its definition.

Start Evolver and load the datafile with the command line

```
evolver cube.fe
```

You should get a prompt

```
Enter command:
```

If you have `geomview`, do command `P` option 8 to get a display. It takes a couple of seconds to initialize. You can manipulate the `geomview` display as usual independently of the Evolver. Evolver will automatically update the image whenever the surface changes.

If you do not have `geomview` and if you have screen graphics linked in, give the command `s` to show the surface. You should see a square divided into four triangles by diagonals. This is the front side of the cube; hidden surfaces are removed by default. The graphics command prompt is

```
Graphics command:
```

It takes strings of letters, each letter making a viewing transformation on the surface: The most used ones are

`r`	rotate right by 6 degrees
`l`	rotate left by 6 degrees
`u`	rotate up by 6 degrees
`d`	rotate down by 6 degrees
`R`	reset to original position
`q`	quit back to main command prompt

Try `rrdd` to get an oblique view of the cube. Any transformations you make will remain in effect the next time you show the surface. Now do `q` to get back to the main prompt.

Now do some iterations. Give the command `g 10` to do 10 iterations. You should get this:

```
10.  area:  4.786234596177497 energy:  4.786234596177497  scale:  0.295137
9.  area:  4.987767806940851 energy:  4.987767806940851  scale:  0.380324
8.  area:  5.101912421796101 energy:  5.101912421796101  scale:  0.293334
7.  area:  5.108866386444287 energy:  5.108866386444287  scale:  0.283689
6.  area:  5.112087629027262 energy:  5.112087629027262  scale:  0.280605
5.  area:  5.112431292155377 energy:  5.112431292155377  scale:  0.280773
4.  area:  5.112484710716689 energy:  5.112484710716689  scale:  0.280554
3.  area:  5.112491934865932 energy:  5.112491934865932  scale:  0.280616
2.  area:  5.112492961234981 energy:  5.112492961234981  scale:  0.28059
1.  area:  5.112493104356962 energy:  5.112493104356962  scale:  0.280599
```

Note that after each iteration a line is printed with the iterations left, area, energy, and current scale factor. By default, the Evolver seeks the optimal scale factor to minimize energy. At first, there are large motions, and the volume constraint may not be exactly satisfied. The energy increase is due to the volume constraint

taking hold. Volume constraints are not exactly enforced, but each iteration tries to bring the volume closer to the target. Here that results in increases in area. You can find the current volumes with the `v` command:

```
Body       target volume          actual volume        pressure
  1     1.000000000000000     0.999999779366360   3.408026016427987
```

The pressure in the last column is actually the Lagrange multiplier for the volume constraint. Now let's refine the triangulation with the `r` command. This subdivides each facet into four smaller similar facets. The printout here gives the counts of the geometric elements and the memory they take:

```
Vertices:  50 Edges:  144 Facets:  96  Facetedges:  288 Memory:  27554
```

Iterate another 10 times:

```
10.  area:  4.908899804670224 energy:  4.908899804670224  scale:  0.268161
9.  area:  4.909526310166165 energy:  4.909526310166165  scale:  0.204016
8.  area:  4.909119925577212 energy:  4.909119925577212  scale:  0.286541
7.  area:  4.908360229118204 energy:  4.908360229118204  scale:  0.304668
6.  area:  4.907421919968726 energy:  4.907421919968726  scale:  0.373881
5.  area:  4.906763705259419 energy:  4.906763705259419  scale:  0.261395
4.  area:  4.906032256943935 energy:  4.906032256943935  scale:  0.46086
3.  area:  4.905484754688263 energy:  4.905484754688263  scale:  0.238871
2.  area:  4.904915540917190 energy:  4.904915540917190  scale:  0.545873
1.  area:  4.904475138593070 energy:  4.904475138593070  scale:  0.227156
```

You can continue iterating and refining as long as you have time and memory.

Eventually, you will want to quit. So give the `q` command. You get

```
Enter new datafile name (none to continue, q to quit):
```

You can start a new surface by entering a datafile name (it can be the same one you just did, to start over), or continue with the present surface by hitting `ENTER` with no name (in case you pressed `q` by accident, or suddenly you remember something you didn't do), or you can really quit with another `q`.

§3.3. Example 2. Mound with gravity.

This example is a mound of liquid sitting on a tabletop with gravity acting on it. The contact angle between the drop surface and the tabletop is adjustable, to simulate the different degrees to which the liquid wets the table. This example illustrates macros, adjustable constants, constraints with energy, and omitting faces from body surfaces.

The drop starts as a cube with one face (face 6 of example 1) on the tabletop (the $z = 0$ plane). The most straightforward way to specify a contact angle is to declare face 6 to be constrained to stay on the tabletop and give it a surface tension different than the default of 1. But this leads to problems described below. The way the contact angle is handled instead is to omit face 6 and give the edges around face 6 an energy integrand that results in the same energy we would get if we did include face 6. If we let the interface energy density for face 6 be T, then we want a vectorfield $\vec{w}$ such that

$$\int\int_{face\ 6} T\vec{k}\cdot d\vec{S} = \int_{\partial(face\ 6)} \vec{w}\cdot d\vec{l}.$$

So all we need is $curl\ \vec{w} = T\vec{k}$, and I have used $\vec{w} = -Ty\vec{i}$.

I have chosen to parameterize the contact angle as the angle in degrees between the table and the surface on the interior of the drop. This angle can be adjusted with the `A` command at run time. I could have made T the parameter directly, but then I wouldn't have had an excuse to show a macro.

Here is the datafile `mound.fe` (see figure 2 for a sketch):

```
// mound.fe
// Evolver data for drop of prescribed volume sitting on plane with gravity.
// Contact angle with plane can be varied interactively with A command.

PARAMETER angle = 90    // interior angle between plane and surface, degrees

#define T  (-cos(angle*pi/180))  // virtual tension of facet on plane

constraint 1   /* the table top */
formula:  z = 0
energy:    // for contact angle
e1:  -T*y
e2:  0
e3:  0

vertices
1   0.0  0.0 0.0  constraint 1  /* 4 vertices on plane */
2   1.0  0.0 0.0  constraint 1
3   1.0  1.0 0.0  constraint 1
4   0.0  1.0 0.0  constraint 1
5   0.0  0.0 1.0
6   1.0  0.0 1.0
7   1.0  1.0 1.0
8   0.0  1.0 1.0
9   2.0  2.0 0.0  fixed   /* for table top, display purposes only */
10  2.0 -1.0 0.0  fixed
11 -1.0 -1.0 0.0  fixed
12 -1.0  2.0 0.0  fixed

edges  /* given by endpoints and attribute */
1   1 2    constraint 1 /* 4 edges on plane */
2   2 3    constraint 1
3   3 4    constraint 1
4   4 1    constraint 1
5   5 6
6   6 7
7   7 8
8   8 5
9   1 5
10  2 6
11  3 7
12  4 8
13  9 10   fixed  /* for table top */
14 10 11   fixed
15 11 12   fixed
16 12  9   fixed

faces  /* given by oriented edge loop */
1   1 10 -5  -9
2   2 11 -6 -10
3   3 12 -7 -11
```

```
4   4  9 -8 -12
5   5  6  7   8
7  13 14 15  16  density 0 fixed /* table top for display */

bodies  /* one body, defined by its oriented faces */
1   1 2 3 4 5   volume 1  density 1
```

The mound itself was basically copied from `cube.fe`, but with face 6 deleted. The reason for this is that face 6 is not needed, and would actually get in the way. It is not needed for the volume calculation since it would always be at $z = 0$ and thus not contribute to the surface integral for volume. The bottom edges of the side faces are constrained to lie in the plane $z = 0$, so face 6 is not needed to keep them from catastrophically shrivelling up. We could have handled the contact angle by including face 6 with a surface tension equal to the interface energy density between the liquid and surface, but that can cause problems if the edges around face 6 try to migrate inward. After refinement a couple of times, interior vertices of face 6 have no forces acting on them, so they don't move. Hence it would be tough for face 6 to shrink when its outer vertices ran up against its inner vertices. The tabletop face, face 7, is entirely extraneous to the calculations. Its only purpose is to make a nice display. You could remove it and all its vertices and edges without affecting the shape of the mound. It's constraint 1 that is the tabletop as far as the mound is concerned.

Now run Evolver on mound.fe. Refine and iterate a while. You should get a nice mound. It's not a hemisphere, since gravity is on by default with $G = 1$. If you use the `G` command to set $G = 0$ and iterate a while, you get a hemisphere. Try using the `A` command to change the contact angle, to 45 degrees or 135 degrees for example. You can also play with gravity. Set $G = 10$ to get a flattened drop, or $G = -5$ to get a drop hanging from the ceiling. $G = -10$ will cause the drop to break loose.

§3.4. Example 3. Catenoid.

The catenoid is the surface formed between two rings not too far apart. In cylindrical coordinates, its equation is $r = (1/a)\cosh(az)$. In `cat.fe`, both the upper and lower rings are given as one-parameter boundary wires. The separation and radius are adjustable constants, so you can change them during a run with the `A` command. The initial radius given is the minimum for which a catenoid can exist for the given separation of the rings. To get a stable catenoid, you will have to increase this value. However, if you do run with the original value, you can watch the neck pinch out. The initial surface consists of six rectangles forming a cylinder between the two circles. The vertices on the boundaries are fixed, elsewise they would slide along the boundary to short-cut the curvature; two diameters is shorter than one circumference. The boundary edges are fixed so that vertices arising from subdividing the edges are likewise fixed.

Here is the catenoid datafile:

```
// cat.fe
// Evolver data for catenoid.

PARAMETER  RMAX = 1.5088795   // ring radius; here critical value
PARAMETER  ZMAX = 1.0         // ring distance from midplane

boundary 1 parameters 1     //  upper ring
x1:    RMAX * cos(P1)
x2:    RMAX * sin(P1)
x3:    ZMAX

boundary 2 parameters 1    //   lower ring
x1:    RMAX * cos(P1)
```

```
x2:    RMAX * sin(P1)
x3:    -ZMAX

vertices   // given in terms of boundary parameter
1    0.00  boundary 1   fixed
2    pi/3  boundary 1   fixed
3  2*pi/3  boundary 1   fixed
4    pi    boundary 1   fixed
5  4*pi/3  boundary 1   fixed
6  5*pi/3  boundary 1   fixed
7    0.00  boundary 2   fixed
8    pi/3  boundary 2   fixed
9  2*pi/3  boundary 2   fixed
10   pi    boundary 2   fixed
11 4*pi/3  boundary 2   fixed
12 5*pi/3  boundary 2   fixed

edges  /* given by endpoints */
1    1  2  boundary 1   fixed
2    2  3  boundary 1   fixed
3    3  4  boundary 1   fixed
4    4  5  boundary 1   fixed
5    5  6  boundary 1   fixed
6    6  1  boundary 1   fixed
7    7  8  boundary 2   fixed
8    8  9  boundary 2   fixed
9    9  10 boundary 2   fixed
10   10 11 boundary 2   fixed
11   11 12 boundary 2   fixed
12   12 7  boundary 2   fixed
13   1  7
14   2  8
15   3  9
16   4  10
17   5  11
18   6  12

faces  /* given by oriented edge loops */
1   1 14 -7 -13
2   2 15 -8 -14
3   3 16 -9 -15
4   4 17 -10 -16
5   5 18 -11 -17
6   6 13 -12 -18
```

The parameter in a boundary definition is always `P1` (and `P2` in a two-parameter boundary). The Evolver can handle periodic parameterizations, as is done in this example.

Try this sequence of commands (displaying at your convenience):

```
r        (refine to get a crude, but workable, triangulation)
u        (equiangulation makes much better triangulation)
g 120    (takes this many iterations for neck to collapse)
```

```
t       (collapse neck to single vertex by eliminating all edges shorter than 0.05)
0.05
o       (split neck vertex to separate top and bottom surfaces)
g       (spikes collapse)
```

The catenoid shows some of the subtleties of evolution. Suppose the initial radius is set to `RMAX` = 1.0 and the initial height to `ZMAX` = 0.55. Fifty iterations with optimizing scale factor result in an area of 6.458483. At this point, each iteration is reducing the area by only .0000001, the triangles are all nearly equilateral, everything looks nice, and the innocent user might conclude the surface is very near its minimum. But this is really a saddle point of energy. Further iteration shows that the area change per iteration bottoms out about iteration 70, and by iteration 300 the area is down to 6.4336. The triangulation really wants to twist around so that there are edges following the lines of curvature, which are vertical meridians and horizontal circles. Hence the optimum triangulation appears to be rectangles with diagonals.

This saddle point also seems to confuse the conjugate gradient method (§7.9.3). With conjugate gradient in effect (use the `U` command to toggle on and off), the saddle point is reached at iteration 17 and area starts decreasing again until iteration 30, when it reaches 6.4486. But then iteration stalls out, and the conjugate gradient mode has to be turned off and on to erase the history vector. Once restarted, another 20 iterations will get the area down to 6.4334. This shows that conjugate gradient mode can work much better than ordinary mode, but it can also have problems. A version of conjugate gradient that works better here is the Polak-Ribiere version, which can be toggled with the `ribiere` command. Try again with `U; ribiere; g60` to see evolution all the way.

Exercise for the reader: Get the Surface Evolver to display an unstable catenoid by declaring the catenoid facets to be the boundary of a body, and adjusting the body volume with the `b` command to get zero pressure.

§3.5. Example 4. Torus partitioned into two cells.

This example has a flat 3-torus divided into two bodies. The unit cell is a unit cube, and the surface has the topology of Kelvin's partitioning of space into tetrakaidecahedra [TW], which was the least area partitioning of space into equal volumes known until recently [WP]. The datafile handles the wrapping of edges around the torus by specifying for each direction whether an edge wraps positively (+), negatively (-), or not at all (*).

The display of a surface in a torus can be done several ways. When displaying this one, try both the `connected bodies` and the `clipped cell` options. For a screen display, you can switch between the two with the `t` command. Interactive `geomview` users can use the `clipped`, `connected`, and `raw_cells` commands to set the option.

The Weaire-Phelan structure [WP] is in the datafile `phelan.fe`. It has area 0.3% less than Kelvin's.

```
// twointor.fe
// Two Kelvin tetrakaidecahedra in a torus.

TORUS_FILLED   // signals that domain is a torus and bodies fill it.

periods
1.000000 0.000000 0.000000
0.000000 1.000000 0.000000
0.000000 0.000000 1.000000

vertices // values from another program
1  0.499733 0.015302 0.792314
2  0.270081 0.015548 0.500199
3  0.026251 0.264043 0.500458
4  0.755123 0.015258 0.499302
```

```
5  0.026509 0.499036 0.794636
6  0.500631 0.015486 0.293622
7  0.025918 0.750639 0.499952
8  0.499627 0.251759 0.087858
9  0.256701 0.499113 0.087842
10 0.026281 0.500286 0.292918
11 0.500693 0.765009 0.086526
12 0.770240 0.499837 0.087382

edges // with wraps in axis directions
1    1 2  * * *
2    2 3  * * *
3    1 4  * * *
4    3 5  * * *
5    2 6  * * *
6    2 7  * - *
7    1 8  * * +
8    4 6  * * *
9    5 9  * * +
10   3 10 * * *
11   3 4  - * *
12   6 8  * * *
13   6 11 * - *
14   7 4  - + *
15   8 12 * * *
16   9 8  * * *
17   9 11 * * *
18   10 7 * * *
19   11 1 * + -
20   12 5 + * -
21   5 7  * * *
22  11 12 * * *
23  10 12 - * *
24   9 10 * * *

faces
1    1 2 4 9 16 -7
2    -2 5 12 -16 24 -10
3    -4 10 18 -21
4    7 15 20 -4 11 -3
5    -1 3 8 -5
6    6 14 -11 -2
7    5 13 -17 24 18 -6
8    -12 13 19 7
9    -16 17 22 -15
10   -10 11 8 12 15 -23
11   -21 9 17 19 1 6
12   -14 -18 23 -22 -13 -8
13   -24 -9 -20 -23
14   -19 22 20 21 14 -3

bodies
1    -1 -2 -3 -4 -5 9 7 11 -9 10 12 5 14 3 volume 0.500
```

```
2     2 -6 -7 8 -10 -12 -11 -13 1 13 -14 6 4 -8 volume 0.500
```

§3.6. Example 5. Ring around rotating rod.

This example consists of a ring of liquid forming a torus around a rod rotating along its long axis (z axis) in weightlessness. The liquid has controllable contact angle with the rod. The interesting question is the stability of the ring as the spin increases.

The effect of the rotation is incorporated in the energy through an integral using the divergence theorem:

$$E = -\int\int\int_B \frac{1}{2}\rho r^2\omega^2 dV = -\int\int_{\partial B} \frac{1}{2}\rho\omega^2(x^2+y^2)z\vec{k}\cdot d\vec{A}$$

where ρ is the fluid density and ω is the angular velocity. Note the energy is negative, because spin makes the liquid want to move outward. This has to be countered by surface tension forces holding the liquid on the rod. If ρ is negative, then one has a toroidal bubble in a rotating liquid, and high spin stabilizes the torus. The spin energy is put in the datafile using the named quantity syntax. "`centrip`" is a user-chosen name for the quantity, "`energy`" declares that this quantity is part of the total energy, "`global_method`" says that the following method is to be applied to the whole surface, "`facet_vector_integral`" is the pre-defined name of the method that integrates vector fields over facets, and "`vector_integrand`" introduces the components of the vectorfield.

The rod surface is defined to be constraint 1 with equation $x^2+y^2=R^2$, where R is the radius of the rod. The contact energy of the liquid with the rod is taken care of with an edge integral over the edges where the liquid surface meets the rod:

$$E = \int\int_S -T\cos(\theta)dA = -T\cos(\theta)\int_{\partial S} zds = T\cos(\theta)\int_{\partial S}\frac{z}{R}(y\vec{i}-x\vec{j})\cdot\vec{ds}$$

Here T is the surface tension of the free surface, and θ is the internal contact angle.

Constraint 2 is a horizontal symmetry plane. By assuming symmetry, we only have to do half the work.

Constraint 3 is a one-sided constraint that keeps the liquid outside the rod. Merely having boundary edges on the rod with constraint 1 is not enough in case the contact angle is near 180^o and the liquid volume is large. Constraint 3 may be put on any vertices, edges, or faces likely to try to invade the rod. However, it should be noted that if you put constraint 3 on only some vertices and edges, equiangulation will be prevented between facets having different constraints.

Constraint 4 is a device to keep the vertices on the rod surface evenly spaced. Edges on curved constraints often tend to become very uneven, since long edges short-cutting the curve can save energy. Hence the need for a way to keep the vertices evenly spread circumferentially, but free to move vertically. One way to do that is with another constraint with level sets $\theta = constant$. Constraint 4 uses the real modulus function with arctangent to create a periodic constraint. Each refinement, the parameters need to be halved to cut the period in half. This is done with the special "`rr`" refinement command at the end of the datafile. The regular "`r`" refinement command should never be used on this file. Note that autorecalc is temporarily turned off to prevent projecting vertices to the constraint when it is in an invalid state. Also note the $\pi/6$ offset to avoid the discontinuity in the modulus function. $\pi/6$ was cleverly chosen so that all refinements would also avoid the discontinuity.

For detecting stability, one can perturb the torus by defining a command

```
perturb := set vertex y y+.01 where not on_constraint 1
```

For convenience, this command is defined in the "`read`" section at the end of the datafile, where you can put whatever commands you want to execute immediately after the datafile is loaded. To detect small perturbations, and get numerical values for the size of perturbations, the y moment of the liquid is calculated

in the named quantity "ymoment". It is not part of the energy, as indicated by the "info_only" keyword. You can see the value with the "v" command.

```
// ringblob.fe

// Toroidal liquid ring on a rotating rod in weightlessness.
// Half of full torus
// Using second periodic constraint surface intersecting rod to
// confine vertices on rod to vertical motion.

// Important note to user:  Use only the 'rr' command defined at
// the end of this file to do refinement.    This is due to the
// nature of constraint 4 below.

// This permits drawing both halves of the ring
view_transforms 1
1 0 0 0
0 1 0 0
0 0 -1 0
0 0 0 1

// Basic parameters.    These may be adjusted at runtime with the
// 'A' command.    Only spin is being adjusted in these experiments.
parameter rodr = 1  // rod radius
parameter spin = 0.5 // angular velocity
parameter angle = 90 // internal contact angle with rod
parameter tens = 1   // surface tension of free surface
#define rode (tens*cos(angle*pi/180))  // liquid-rod contact energy
parameter dens = 1  // density of liquid, negative for bubble

// spin centripetal energy
quantity centrip energy global_method facet_vector_integral
vector_integrand:
q1:  0
q2:  0
q3:  -0.5*dens*spin*spin*(x^2+y^2)*z

// y moment, for detecting instability
quantity ymoment info_only global_method facet_vector_integral
vector_integrand:
q1:  0
q2:  0
q3:  y*z

// Constraint for vertices and edges confined to rod surface,
// with integral for blob area on rod
constraint 1
formula:  x^2 + y^2 = rodr^2
energy:
e1:  rode*z*y/rodr
e2:  -rode*z*x/rodr
e3:  0
```

```
// Horizontal symmetry plane
constraint 2
formula:  z = 0

// Rod surface as one-sided constraint, to keep stuff from caving in
// Can be added to vertices, edges, facets that try to cave in
constraint 3 nonnegative
formula:  x^2 + y^2 = rodr^2

// Constraint to force vertices on rod to move only vertically.
// Expressed in periodic form, so one constraint fits arbitrarily
// many vertices.  Note offset to pi/6 to avoid difficulties with
// modulus discontinuity at 0.
parameter pp = pi/2    /* to be halved each refinement */
parameter qq = pi/6    /* to be halved each refinement */
constraint 4
formula:    (atan2(y,x)+pi/6) % pp = qq

//initial dimensions
#define ht 2
#define wd 3

vertices
1  0   -wd 0  constraints 2    // equatorial vertices
2  wd    0 0  constraints 2
3  0    wd 0  constraints 2
4  -wd   0 0  constraint 2
5  0   -wd ht                 // upper outer corners
6  wd    0 ht
7  0    wd ht
8  -wd   0 ht
9  0 -rodr ht constraints 1,4   // vertices on rod
10 rodr  0 ht constraints 1,4
11 0  rodr ht constraints 1,4
12 -rodr  0 ht constraints 1,4

edges
1   1 2 constraint 2  // equatorial edges
2   2 3 constraint 2
3   3 4 constraint 2
4   4 1 constraint 2
5   5 6               // upper outer edges
6   6 7
7   7 8
8   8 5
9   9  10 constraint 1,4   // edges on rod
10  10 11 constraint 1,4
11  11 12 constraint 1,4
12  12  9 constraint 1,4
13   1  5        // vertical outer edges
14   2  6
15   3  7
16   4  8
```

```
17   5  9        // cutting up top face
18   6 10
19   7 11
20   8 12

faces  /* given by oriented edge loop */
1    1 14 -5 -13 tension tens // side faces
2    2 15 -6 -14 tension tens  // Remember you can't change facet tension
3    3 16 -7 -15 tension tens  // dynamically just by changing tens; you have
4    4 13 -8 -16 tension tens  // to do "tens := 2; set facet tension tens"
5    5 18 -9 -17 tension tens  // top faces
6    6 19 -10 -18 tension tens
7    7 20 -11 -19 tension tens
8    8 17 -12 -20 tension tens

bodies  /* one body, defined by its oriented faces */
1    1 2 3 4 5 6 7 8  volume 25.28

read  // some initializations
transforms off     // just show fundamental region to start with

// special refinement command
rr :=  autorecalc off;  pp := pp/2; qq := qq % pp;  r; autorecalc on;

// a slight perturbation, to check stability
perturb := set vertex y y+.01 where not on_constraint 1
```

§3.7. Example 6. Column of liquid solder.

Here we have a tiny drop of liquid solder that bridges between two parallel, horizontal planes. On each plane there is a circular pad that the solder perfectly wets, and the solder is perfectly nonwetting off the pads. This would be just a catenoid problem with fixed volume, except that the pads are offset, and it is desired to find out what aligning force the solder exerts. The surface is defined the same way as in the catenoid example, except the lower boundary ring has a shift variable "`shift`" in it to provide an offset in the y direction. This makes the shift adjustable at run time. Since the top and bottom facets of the body are not included, the constant volume they account for is provided as the "`volconst`" value in the body definition. (This value is valid only for the initial value of `ZH`, though.)

The interesting part of this example is the calculation of the restoring force. One could incrementally shift the pads, minimizing energy at each shift, and numerically differentiate the energy to get the force. Or one could set up integrals to calculate the force directly, which is what is done here. The energy has surface tension and gravitational components,

$$E = \int\int_S T dA + \int\int_S \rho G \frac{z^2}{2}\vec{k} \cdot d\vec{A}.$$

where T is the surface tension of the free surface S, ρ is the gravitational constant, and G is the acceleration of gravity. Given a variation vectorfield $\vec{g}$, the unconstrained variation of the energy is

$$\delta E = T \int\int_S (div \vec{g} - \vec{N} \cdot D\vec{g} \cdot \vec{N}) dA + \rho G \int\int_S (div(\frac{z^2}{2}\vec{k})\vec{g} - curl(\vec{g} \times \frac{z^2}{2}\vec{k}) \cdot d\vec{A}.$$

where $\vec{N}$ is the unit normal. Of course, we have to correct for any volume change, and since the pressure P is the Lagrange multiplier relating volume and energy changes at a minimum,

$$\delta E = P\delta V = P \int \int_S \vec{g} \cdot d\vec{A}.$$

Projecting volume back to the volume constraint subtracts this, so the net change is

$$\delta E = T \int \int_S (div\vec{g} - \vec{N} \cdot D\vec{g} \cdot \vec{N}) dA + \rho G \int \int_S ((div \frac{z^2}{2}\vec{k})\vec{g} - curl(\vec{g} \times \frac{z^2}{2}\vec{k}) \cdot d\vec{A} - P \int \int_S \vec{g} \cdot d\vec{A}.$$

We shall take the perturbation to be $\vec{g} = (z + ZH)\vec{j}/2ZH$, which leaves the bottom plane fixed and gives a unit shift to the top plane. It is important when working with piecewise linear surfaces that the perturbations be likewise piecewise linear. The force, then, is

$$\delta E = T \int \int_S -\frac{N_z N_y}{2ZH} dA + \rho G \int \int_S -\frac{z^2}{4ZH}\vec{k} \cdot d\vec{A} - P \int \int_S \frac{z + ZH}{2ZH}\vec{j} \cdot d\vec{A}.$$

The $N_z N_y$ term requires the use of the "`facet_general_integral`" method, which integrates an arbitrary scalar function of position and normal vector over facets. The three terms are defined as three method instances in the datafile below, and combined into one quantity "`forcey`".

To check the accuracy of the quantity calculation of the force, a command "`dodiff`" is defined at the end of the datafile. This calculates the force the two different ways. It should only be run when the surface is exactly at a minimum. Try this, and watch the triangulation dance around during the iteration:

```
u; r; U; ribiere; g 200; hessian 5; dodiff
```

The advantage of the quantity method over the differencing method is that the former gives accurate values even when the surface is not at its exact minimum.

```
// column.fe
// example of using facet_general_integral to measure restoring force
// of tiny column of liquid solder in shape of skewed catenoid.

// All units cgs
parameter RAD = 0.05     // ring radius
parameter ZH = 0.04      // height
parameter SHIFT = 0.025    // shift
#define SG 8      // specific gravity of solder
#define TENS 460  // surface tension of solder
#define GR  980   // acceleration of gravity

quantity grav_energy energy modulus GR*SG global_method gravity_method

// following method instances and quantity for aligning force

method_instance dareay method facet_general_integral
scalar_integrand:  -TENS*x6*x5/2/ZH/sqrt(x4^2+x5^2+x6^2)

method_instance dgrav method facet_vector_integral
vector_integrand:
q1:  0
q2:  -0.25*GR*SG*z^2/ZH
q3:  0
```

```
method_instance dvoly method facet_vector_integral
vector_integrand:
q1:  0
q2:  -(z+ZH)/2/ZH
q3:  0

// Now add the three energy change instances into one quantity, with
// overall modulus -1 since force is negative energy gradient.
quantity forcey info_only modulus -1 global_method dareay global_method dvoly
global_method dgrav

BOUNDARY 1  PARAMETERS 1
X1:  RAD*cos(P1)
X2:  RAD*sin(P1) + SHIFT
X3:  ZH

BOUNDARY 2  PARAMETERS 1
X1:  RAD*cos(P1)
X2:  RAD*sin(P1)
X3:  -ZH


vertices   // given in terms of boundary parameter
1    0.00  boundary 1   fixed
2    pi/3  boundary 1   fixed
3  2*pi/3  boundary 1   fixed
4    pi    boundary 1   fixed
5  4*pi/3  boundary 1   fixed
6  5*pi/3  boundary 1   fixed
7    0.00  boundary 2   fixed
8    pi/3  boundary 2   fixed
9  2*pi/3  boundary 2   fixed
10   pi    boundary 2   fixed
11 4*pi/3  boundary 2   fixed
12 5*pi/3  boundary 2   fixed

edges
1    1  2  boundary 1   fixed
2    2  3  boundary 1   fixed
3    3  4  boundary 1   fixed
4    4  5  boundary 1   fixed
5    5  6  boundary 1   fixed
6    6  1  boundary 1   fixed
7    7  8  boundary 2   fixed
8    8  9  boundary 2   fixed
9    9  10 boundary 2   fixed
10   10 11 boundary 2   fixed
11   11 12 boundary 2   fixed
12   12 7  boundary 2   fixed
13   1  7
14   2  8
15   3  9
16   4  10
```

```
17   5  11
18   6  12

faces
1    1 14 -7 -13   density TENS
2    2 15 -8 -14   density TENS
3    3 16 -9 -15   density TENS
4    4 17 -10 -16   density TENS
5    5 18 -11 -17   density TENS
6    6 13 -12 -18   density TENS

bodies
1     -1 -2 -3 -4 -5 -6 volume 0.00045 volconst 2*pi*RAD^2*ZH

read

dodiff := { olde := total_energy; shift := shift + .0001 ;
oldforce := total forcey;
conj_grad; ribiere; g 40;
printf "Difference force:  %2.15g\n", -(total_energy-olde)/.0001;
printf "Quantity  force:    %2.15g\n", (total forcey+oldforce)/2;
}
```

§3.8. Example 7. Rocket fuel tank.

This example discusses a cylindrical flat-ended tank in low gravity with some liquid inside. Complete understanding of this example qualifies you as an Evolver Power User.

The initial configuration is shown in figure 3. The axis is horizontal with the base at the left. We will assume the fuel is in a ring around the base of the tank. The fuel comprises one body, and the boundary of the body has four components:

1. The covered part of the flat circular base at $y = 0$, implemented as constraint 1..
2. The cylindrical wall at $x^2 + z^2 = R^2$, implemented as constraint 2..
3. The triangular facets (8 of them in figure 3).
4. The gaps between the edges on the wall (the "gap edges", edges 5,6,7,8 in figure 3) and the wall. We will assume that the gap surfaces are generated by lines radially outward from the central axis (the y axis) through the points of the gap edges.

To specify contact angles, let θ_B be the interior contact angle with the base, and let θ_W be the interior contact angle with the cylindrical wall.

§3.8.1. Surface energy.

Base.

The surface energy here comes from the contact angle. The angle is represented by pretending the uncovered base has surface tension $T_B = cos(\theta_B)$. That we handle with an energy integral on constraint 1. We want

$$E = \int\int_{base} T_B \vec{j} \cdot d\vec{A}. \tag{1}$$

By Stokes' theorem, this is the integral around the edges in the base (edges 1,2,3,4)

$$E = \int_{edges} T_B z \vec{i} \cdot \vec{ds}, \tag{2}$$

where the edges are oriented oppositely from figure 3. Hence the energy integrand for constraint 1 should be $-T_B z\vec{i}$.

Wall.

The contact angle is represented by pretending the uncovered wall has surface tension $T_W = cos(\theta_W)$. The uncovered wall in infinite, so we will assume equivalently that the covered wall has tension $-T_W$. The energy is

$$E = \int\int_{wall} -T_W dA = \int\int_{wall} -T_W \frac{1}{R}(x\vec{i} + z\vec{k}) \cdot d\vec{A}. \tag{3}$$

We want to turn this into an integral over the boundary of the wall, which is made of two paths, the base circumference and the "gap trace" where the gap surfaces meet the wall. This calls for a vector potential, but our integrand above does not have zero divergence. But we could choose a divergenceless integrand that is equal on the wall:

$$E = \int\int_{wall} \vec{F} \cdot d\vec{A}. \tag{4}$$

where

$$\vec{F} = -T_W \frac{R}{(x^2 + z^2)}(x\vec{i} + z\vec{k}). \tag{5}$$

Now we can get a vector potential $\vec{w}$

$$\vec{w} = -T_W \frac{Ry}{(x^2 + z^2)}(-z\vec{i} + x\vec{k}), \quad \nabla \times \vec{w} = \vec{F}. \tag{6}$$

Hence

$$E = \int_{basecircum} \vec{w} \cdot ds + \int_{gap\ trace} \vec{w} \cdot ds. \tag{7}$$

The first of these is zero since $y = 0$ there. The second is equal to the integral over the gap edges, since $\nabla \times \vec{w}$ is parallel to the gap surfaces! So

$$E = \int_{gap\ edges} \vec{w} \cdot ds, \tag{8}$$

where the gap edges are oppositely oriented from figure 3. Hence the constraint 2 energy integrand includes $-\vec{w}$.

The facets.

The surface tension energy here is automatically taken care of by the Evolver. We will leave the surface tension as the default value of 1.

The gaps.

We will declare constraint 2 to be `CONVEX` so that Evolver will include a gap surface energy for all the gap edges. We put the spring constant to be 1, as that value give the best approximation to the true area for small gaps.

§**3.8.2. Volume.**

The body volume $V = \int\int\int dV$ can be calculated as a surface integral $V = \int\int \vec{F} \cdot d\vec{A}$ where $\nabla \cdot F = 1$. The integral over the facets is handled automatically, but there are two choices for $\vec{F}$. We will take $\vec{F} = (x\vec{i} + y\vec{j} + z\vec{k})/3$ by putting `SYMMETRIC_CONTENT` in the datafile. (This choice works better for the tank on its side; for an upright tank, the default $\vec{F} = z\vec{k}$ is easier.) The surface integral has four components:

Base.

This part of the integral is zero, since $y = 0$ and the normal is $\vec{j}$.

The wall.

Here the $\vec{j}$ component of $\vec{F}$ can be dropped, and the rest put in the equivalent divergenceless form

$$\vec{F}_W = \frac{R^2}{3(x^2+z^2)}(x\vec{i} + z\vec{k}). \tag{9}$$

This has vector potential

$$\vec{w} = \frac{R^2 y}{3(x^2+z^2)}(-z\vec{i} + x\vec{k}), \qquad \nabla \times \vec{w} = \vec{F}_W. \tag{10}$$

By the same reasoning as for wall area, this reduces to the integral of $-\vec{w}$ over the gap edges. Thus we include $-\vec{w}$ in the content integrand of constraint 2.

Facets.

Evolver takes care of these automatically.

Gaps.

We subtract some radial component from $\vec{F}$ to get a divergenceless vector $\vec{F}_G$ with the same surface integral over the gap surfaces:

$$\vec{F}_G = -\frac{1}{6}x\vec{i} + \frac{1}{3}y\vec{j} - \frac{1}{6}z\vec{k}. \tag{11}$$

This has vector potential

$$\vec{w} = \frac{1}{6}zy\vec{i} - \frac{1}{6}xy\vec{k}. \tag{12}$$

Hence

$$\int\int_{gaps} \vec{F}\cdot d\vec{A} = \int_{gap\ trace} \vec{w}\cdot d\vec{s} + \int_{gap\ edges} \vec{w}\cdot d\vec{s}. \tag{13}$$

The second part we can put directly into the constraint 2 content integrand (with opposite orientation of the edges). The gap trace part we convert to an equivalent integrand $\vec{v}$:

$$\vec{v} = \frac{R^2 y}{6(x^2+z^2)}(z\vec{i} - x\vec{k}). \tag{14}$$

which has radial curl. Hence the gap trace integral is the same as $\int_{gap\ edges} \vec{v}\cdot d\vec{s}$, this time with the edges in the same orientation as figure 3.

§3.8.3. Gravity.

Just for fun, we're going to put in gravity in such a way that the user can make it act in any direction. Let the acceleration of gravity be $\vec{G} = g_y\vec{j} + g_z\vec{k}$. g_y and g_z will be adjustable constants. Let the fuel density be ρ. Then the gravitational potential energy is

$$E = -\int\int\int_{body} \vec{G}\cdot\vec{x}\rho dV = -\int\int\int_{body} (g_y y + g_z z)\rho dV. \tag{15}$$

First we change this to a surface integral

$$E = -\rho\int\int_{\partial body} \vec{F}\cdot d\vec{A}, \qquad \nabla\cdot\vec{F} = g_y y + g_z z. \tag{16}$$

It turns out convenient to take

$$\vec{F} = (g_y\frac{y^2}{2} + g_z yz)\vec{j}. \tag{17}$$

The surface integral has four components:

Base.

This part is zero since $y = 0$.

Wall.

This part is also zero since $\vec{F}$ is parallel to the wall.

Facets.

This part is taken care of by installing $-\rho\vec{F}$ as the integrand for surface energy 1 for the facets.

Gaps.

We get an equivalent divergence-free integrand $\vec{F}_G$ by adding a radial component to $\vec{F}$:

$$\vec{F}_G = g_y\left(\frac{y^2}{2}\vec{j} - \frac{y}{2}(x\vec{i} + z\vec{k})\right) + g_z\left(yz\vec{j} - \frac{z}{3}(x\vec{i} + z\vec{k})\right). \tag{18}$$

This has vector potential $\vec{w}$

$$\vec{w} = \left(g_y\frac{y^2}{4} + g_z\frac{yz}{3}\right)(z\vec{i} - x\vec{k}). \tag{19}$$

This is integrated over the gap edges with negative orientation, so $\rho\vec{w}$ goes into the energy integrand of constraint 2, and over the gap trace. For the gap trace part, we construct an equivalent $\vec{w}_G$ that has radial curl:

$$\vec{w}_G = \left(g_y\frac{y^2}{4}\frac{R^2}{(x^2+y^2)} + g_z\frac{yz}{3}\frac{R^3}{(x^2+z^2)^{(3/2)}}\right)(z\vec{i} - x\vec{k}), \tag{20}$$

so

$$\int_{gap\ trace}\vec{w}\cdot d\vec{s} = \int_{gap\ edges}\vec{w}_G\cdot d\vec{s}. \tag{21}$$

Here the integral is over the same orientation as in figure 3, so $-\rho w_G$ also goes into the energy integrand of constaint 2.

§3.8.4. Running.

Refine once before iterating. Iterate and refine to your heart's content. You might try command `u` once in a while to regularize the triangulation. Play around with command `A` to change gravity and wall contact angles. Keep an eye on the scale factor. If it gets towards zero, check out the `t` and `w` histograms.

```
// tankex.fe

// Equilibrium shape of liquid in flat-ended cylindrical tank.

// Tank has axis along y-axis and flat bottom in x-z plane.    This
// is so gravity acting vertically draws liquid toward wall.

// Straight edges cannot conform exactly to curved walls.
// We need to give them an area so that area cannot shrink by straght edges
// pulling away from the walls.  The gaps are also accounted for
// in volume and gravitational energy.

SYMMETRIC_CONTENT     // for volume calculations

// Contact angles, initially for 45 degrees.
PARAMETER ENDT  = 0.707   /* surface tension of uncovered base   */
```

```
PARAMETER WALLT = 0.707   /* surface tension of uncovered side wall */

// Gravity components
PARAMETER GY = 0
PARAMETER GZ = -1

SPRING_CONSTANT 1  // for most accurate gap areas for constraint 2

#define  TR  1.00       /* tank radius */
#define  RHO 1.00       /* fuel density */

constraint 1  // flat base
function:    y = 0
energy:                                // for contact energy line integral
e1:      -ENDT*z
e2:      0
e3:      0

#define wstuff (WALLT*TR*y/(x^2 + z^2))   // common wall area term
#define vstuff (TR^2/3*y/(x^2 + z^2))     // common wall volume term
#define gstuff (GY*TR^2*y^2/4/(x^2 + z^2) + GZ*TR^3*y*z/3/(x^2+z^2)**1.5)
// common gap gravity term

constraint 2  CONVEX         // cylindrical wall
function:    x^2 + z^2 = TR^2
energy:                                  // for contact energy and gravity
e1:    -wstuff*z  + RHO*GY*y^2*z/4 + RHO*GZ*y*z^2/3 - RHO*gstuff*z
e2:        0
e3:      wstuff*x  - RHO*GY*y^2*x/4 - RHO*GZ*y*z*x/3 + RHO*gstuff*x
content:                                 // so volumes calculated correctly
c1:      vstuff*z - z*y/6 + vstuff*z/2
c2:        0
c3:    -vstuff*x + x*y/6 - vstuff*x/2

surface_energy 1   // for arbitrary direction gravity on facets
e1:    0
e2:    -RHO*GY*y^2/2 - RHO*GZ*y*z
e3:    0


// Now the specification of the initial shape

vertices
1    0.5  0.0  0.5  constraint 1
2    0.5  0.0 -0.5  constraint 1
3   -0.5  0.0 -0.5  constraint 1
4   -0.5  0.0  0.5  constraint 1
5    1.0  0.5  0.0  constraint 2
6    0.0  0.5 -1.0  constraint 2
7   -1.0  0.5  0.0  constraint 2
8    0.0  0.5  1.0  constraint 2

edges
```

```
1     2   1   constraint 1
2     1   4   constraint 1
3     4   3   constraint 1
4     3   2   constraint 1
5     5   6   constraint 2
6     6   7   constraint 2
7     7   8   constraint 2
8     8   5   constraint 2
9     1   8
10    1   5
11    2   5
12    2   6
13    3   6
14    3   7
15    4   7
16    4   8

faces
1    13    6 -14 energy 1
2     3   14 -15 energy 1
3    15    7 -16 energy 1
4     2   16  -9 energy 1
5     9    8 -10 energy 1
6     1   10 -11 energy 1
7    11    5 -12 energy 1
8     4   12 -13 energy 1

bodies
1     1 2 3 4 5 6 7 8   volume 0.6  density 0  /* no default gravity */
```

§3.9. Example 8. Spherical tank.

This example discusses a sperical tank in low gravity with some liquid inside. Complete understanding of this example qualifies you as an Evolver Power User.

The initial configuration is shown in figure 4. The liquid comprises one body, and the boundary of the body has three components:

1. The sphere at $x^2 + y^2 + z^2 = R^2$, implemented as constraint 1.
2. The faceted surface (initially, the single face).
3. The gaps between the edges on the sphere (the "gap edges", edges 1,2,3,4 in figure 4) and the sphere. We will assume that the gap surfaces are generated by lines radially outward from the center of the sphere through the points of the gap edges.

We will often be looking for vectorfields that have radial curl, since their integral over the gap edges will be the same as over the gap trace. As a useful fact for all the curls below, note that if

$$\vec{w} = \frac{z^n}{(x^2+y^2)(x^2+y^2+z^2)^{n/2}}(y\vec{i} - x\vec{j}) \tag{1}$$

then

$$\nabla \times \vec{w} = \frac{nz^{n-1}}{(x^2+y^2+z^2)^{1+n/2}}(x\vec{i} + y\vec{j} + z\vec{k}). \tag{2}$$

To specify contact angles, let θ_W be the interior contact angle with the spherical wall.

§3.9.1. Surface energy.

Wall.

The contact angle is represented by pretending the uncovered wall has surface tension $T_W = cos(\theta_W)$. We will assume equivalently that the covered wall has tension $-T_W$. The energy is

$$E = \int\int_{wall} -T_W dA = \int\int_{wall} -T_W \frac{1}{R}(x\vec{i} + y\vec{j} + z\vec{k}) \cdot d\vec{A}. \tag{3}$$

We want to turn this into an integral over the boundary of the covered wall, the "gap trace" where the gap surfaces meet the wall. This calls for a vector potential, but our integrand above does not have zero divergence. But we could choose a divergenceless integrand that is equal on the wall:

$$E = \int\int_{wall} \vec{F} \cdot d\vec{A}, \tag{4}$$

where

$$\vec{F} = -T_W \frac{R^2}{(x^2+y^2+z^2)^{3/2}}(x\vec{i} + y\vec{j} + z\vec{k}). \tag{5}$$

Now we can get a vector potential $\vec{w}$ (see useful fact above with $n = 1$)

$$\vec{w} = -T_W \frac{R^2 z}{(x^2+y^2)(x^2+y^2+z^2)^{1/2}}(y\vec{i} - x\vec{j}), \quad \nabla \times \vec{w} = \vec{F}. \tag{6}$$

Hence

$$E = \int_{gap\ trace} \vec{w} \cdot ds. \tag{7}$$

This is equal to the integral over the gap edges, since $\nabla \times \vec{w}$ is parallel to the gap surfaces. So

$$E = \int_{gap\ edges} \vec{w} \cdot ds, \tag{8}$$

where the gap edges are oppositely oriented from figure 4. Hence the constraint energy integrand includes $-\vec{w}$.

The facets.

The surface tension energy here is automatically taken care of by the Evolver. We will leave the surface tension as the default value of 1.

The gaps.

We will declare constraint 1 to be `CONVEX` so that Evolver will include a gap surface energy for all the gap edges. We put the spring constant to be 1, as that value give the best approximation to the true area for small gaps.

§3.9.2. Volume.

The body volume $V = \int\int\int dV$ can be calculated as a surface integral $V = \int\int \vec{F} \cdot d\vec{A}$ where $\nabla \cdot F = 1$. The integral over the facets is handled automatically, but there are two choices for $\vec{F}$. We will take $\vec{F} = (x\vec{i} + y\vec{j} + z\vec{k})/3$ by putting `SYMMETRIC_CONTENT` in the datafile. Thus

$$V = \frac{1}{3}\int\int_{body\ surface} (x\vec{i} + y\vec{j} + z\vec{k}) \cdot dA. \tag{9}$$

The surface integral has three components:

The wall.

Like wall energy, this is first put in the equivalent divergenceless form

$$\vec{F} = \frac{1}{3}\frac{R^3}{(x^2+y^2+z^2)^{3/2}}(x\vec{i}+y\vec{j}+z\vec{k}). \tag{10}$$

This has vector potential (again useful fact above with $n = 1$)

$$\vec{w} = \frac{1}{3}\frac{R^3 z}{(x^2+y^2)(x^2+y^2+z^2)^{1/2}}(y\vec{i}-x\vec{j}), \quad \nabla \times \vec{w} = \vec{F}. \tag{11}$$

By the same reasoning as for wall area, this reduces to the integral of $-\vec{w}$ over the gap edges. Thus we include $-\vec{w}$ in the content integrand of constraint 1. However, we also note a potential problem at $z = -R$ where $x^2 + y^2 = 0$. We must be sure that this point always remains within the covered surface. As long as it does, it will have a constant effect. In fact, we see that at $z = 0$ the integrand $\vec{w}$ is zero, and the other volume contributions are zero at $z = 0$, so the singularity at $z = -R$ must have a contribution to the volume of half the volume of the sphere. We can account for this by using `VOLCONST 2*pi*R^3/3` with the body.

Facets.

Evolver takes care of these automatically.

Gaps.

The integrand is parallel to the gap surfaces, hence this contribution is zero.

§3.9.3. Gravity.

The sphere being very symmetric, all directions of gravity are the same. Therefore we will use Evolver's default gravity. Let the magnitude of gravity be G (downwards). Let the liquid density be ρ. Then the gravitational potential energy is

$$E = G\int\int\int_{body} z\rho dV. \tag{12}$$

First we change this to a surface integral

$$E = G\rho\int\int_{\partial body} \vec{F}\cdot d\vec{A}, \qquad \nabla\cdot\vec{F} = z. \tag{13}$$

The default gravity mechanism uses

$$\vec{F} = G\rho\frac{z^2}{2}\vec{k}. \tag{14}$$

The surface integral has three components:

Wall.

First, we convert to the equivalent divergence-free integrand

$$\vec{F} = G\rho\frac{R^4 z^3}{2(x^2+y^2+z^2)^3}(x\vec{i}+y\vec{j}+z\vec{k}). \tag{15}$$

Note this has the same dot product with $x\vec{i}+y\vec{j}+z\vec{k}$ on the surface of the sphere. The vector potential is

$$\vec{w} = G\rho\frac{R^4 z^4}{8(x^2+y^2)(x^2+y^2+z^2)^2}(y\vec{i}-x\vec{j}), \quad \nabla\times\vec{w} = \vec{F}. \tag{16}$$

So

$$E = \int_{gap\ trace} \vec{w} \cdot d\vec{s} - \frac{G\rho R^4}{4}. \tag{17}$$

The constant term here is the gravitaional energy of the lower hemisphere, since $\vec{w} = 0$ when $z = 0$. It will not show up in the Evolver energy; you must remember to adjust for it yourself. Due to the radial curl of $\vec{w}$, the integral is also the integral over the gap edges. The orientation is opposite that given for the gap edges, so $-\vec{w}$ goes in the energy for constraint 1.

Facets.

The integrals over facets are automatically taken care of by the Evolver.

Gaps.

We get an equivalent divergence-free integrand $\vec{F}_G$ by adding a radial component $-(z/4)(x\vec{i} + y\vec{j} + z\vec{k})$ to $\vec{F}$:

$$\vec{F}_G = \frac{G\rho}{4}(-xz\vec{i} + -yz\vec{j} + z^2\vec{k}). \tag{18}$$

This has vector potential $\vec{w}$

$$\vec{w} = -\frac{G\rho z^2}{8}(y\vec{i} - x\vec{j}). \tag{19}$$

This is integrated over the gap edges with opposite orientation, so $-\vec{w}$ goes into the energy integrand of constraint 1, and over the gap trace. For the gap trace part, we construct an equivalent $\vec{w}_G$ that has radial curl (using two versions of useful fact with $n = 2$ and $n = 4$ to show radial curl):

$$\begin{aligned} \vec{w}_G &= \frac{G\rho}{8}\frac{z^2(R^2 - z^2)}{(x^2 + y^2)}(y\vec{i} - x\vec{j}) \\ &= \frac{G\rho}{8}\left(\frac{z^2R^4}{(x^2 + y^2)(x^2 + y^2 + z^2)} - \frac{z^4R^4}{(x^2 + y^2)(x^2 + y^2 + z^2)^2}\right)(y\vec{i} - x\vec{j}) \\ &= \frac{G\rho}{8}\frac{z^2R^4}{(x^2 + y^2 + z^2)^2}(y\vec{i} - x\vec{j}) \end{aligned} \tag{20}$$

so

$$\int_{gap\ trace} \vec{w} \cdot d\vec{s} = \int_{gap\ edges} \vec{w}_G \cdot d\vec{s}. \tag{21}$$

Here the integral is over the same orientation as in figure 4, so w_G also goes into the energy integrand of constaint 1.

§3.9.4. Running.

Refine once before iterating. Iterate and refine to your heart's content. You might try command `u` once in a while to regularize the triangulation. Play around with command `A` to change gravity and wall contact angles. Keep an eye on the scale factor. If it gets towards zero, check out the `t` and `w` histograms.

```
// sphere.fe

// Spherical tank.

SYMMETRIC_CONTENT   // natural for a sphere

/* sphere radius */
#define R  1.00

/* cosine of contact angle */
```

```
PARAMETER WALLT = 0.707

/* density of body */
#define RHO   1.0

#define wstuff (R^2*z/(x^2 + y^2)/sqrt(x^2+y^2+z^2))
#define gstuff (G*RHO/8*R^4*z^4/(x^2 + y^2)/(x^2+y^2+z^2)^2)
#define gapstuff (G*RHO*R^4/8*z^2/(x^2+y^2+z^2)^2)

constraint 1    /* the sphere */
formula:        x^2 + y^2 + z^2 = R^2
energy:
e1:         WALLT*wstuff*y - gstuff*y + G*RHO/8*y*z^2 + gapstuff*y
e2:       -WALLT*wstuff*x + gstuff*x - G*RHO/8*x*z^2 - gapstuff*x
e3:0
content:
c1:    -wstuff*y/3
c2:      wstuff*x/3
c3:      0

vertices:
1    1  0  0  constraint 1
2    0  1  0  constraint 1
3   -1  0  0  constraint 1
4    0 -1  0  constraint 1
5    0  0  1  FIXED   // to show back hemisphere
6    0  0 -1  FIXED
7    0  1  0  FIXED
8   -1  0  0  FIXED
9    0 -1  0  FIXED

edges:
1    1  2     constraint 1
2    2  3     constraint 1
3    3  4     constraint 1
4    4  1     constraint 1
5    5  9     constraint 1  FIXED // to show back hemisphere
6    9  6     constraint 1  FIXED
7    6  7     constraint 1  FIXED
8    7  5     constraint 1  FIXED
9    5  8     constraint 1  FIXED
10   9  8     constraint 1  FIXED
11   6  8     constraint 1  FIXED
12   7  8     constraint 1  FIXED

faces:
1    1 2 3 4
2    5 10 -9  constraint 1 density 0 FIXED   // to show back hemisphere
3   -10 6 11  constraint 1 density 0 FIXED
4   -11 7 12  constraint 1 density 0 FIXED
5    8 9 -12  constraint 1 density 0 FIXED

bodies:    // start with sphere half full
```

```
1    1    volume 2*pi*R^3/3  volconst 2*pi*R^3/3
```

§3.10. Example 9. Crystalline integrand.

This example shows how to use Wulff vectors for a crystalline integrand. In general, the Wulff vector at a point on a surface is a vector that is dotted with the surface normal to give the energy density of the surface. For ordinary area, it is the unit normal itself. But if a finite set of Wulff vectors is given, and the one used at a point is the one with the maximum dot product, then the minimal surface has only flat faces, i.e. it is crystalline. The crystal shape in this example is an octahedron. The Wulff vectors are the vertices of the octahedron, and are in `octa.wlf`. The datafile `crystal.fe` describes a cube with extra edges around the equator. These edges provide places for octahedron edges to form. Things work a lot better if the facet edges are where the crystal edges want to be.

To see the cube turn into an octahedron, refine once, use the `m` command to set the scale to 0.05, and iterate about 50 times. Fixed scale works much better than optimizing scale for crystalline integrands, since crystalline energy is not a smooth function of the scale factor. Sometimes you have to put in jiggling also to get over local obstacles to minimizing energy.

Here is the Wulff vector file `octa.wlf`:

```
0      0      1
0      0     -1
0.707  0.707  0
-0.707  0.707  0
0.707 -0.707  0
-0.707 -0.707  0
```

Here is the datafile:

```
// crystal.fe
// Evolver data for cube of prescribed volume with
//   crystalline surface energy.    Evolves into an octahedron.

Wulff "octa.wlf"    // Wulff vectors for octahedral crystal

vertices
1  0.0 0.0 0.0
2  1.0 0.0 0.0
3  1.0 1.0 0.0
4  0.0 1.0 0.0
5  0.0 0.0 1.0
6  1.0 0.0 1.0
7  1.0 1.0 1.0
8  0.0 1.0 1.0
9  0.0 0.0 0.5
10 1.0 0.0 0.5
11 1.0 1.0 0.5
```

```
12 0.0 1.0 0.5

edges  /* given by endpoints and attribute */
1   1 2
2   2 3
3   3 4
4   4 1
5   5 6
6   6 7
7   7 8
8   8 5
9   1 9
10  2 10
11  3 11
12  4 12
13  9 5
14  10 6
15  11 7
16  12 8
17   9 10
18  10 11
19  11 12
20  12  9

faces  /* given by oriented edge loop */
1   1 10 -17  -9
2   2 11 -18 -10
3   3 12 -19 -11
4   4  9 -20 -12
5   5  6  7   8
6  -4 -3 -2  -1
7  17 14 -5 -13
8  18 15 -6 -14
9  19 16 -7 -15
10 20 13 -8 -16

bodies  /* one body, defined by its oriented faces */
1   1 2 3 4 5 6 7 8 9 10  volume 1
```

Chapter 4. The Model.

This chapter describes the mathematical model of a surface that the Surface Evolver incorporates. See the **Datafile** chapter for how to set up the initial surface and the **Operations** chapter for how to manipulate the surface. Keywords are often given in upper case in this manual, even though case is not significant.

§4.1. Geometric elements.

The surface is defined in terms of its geometric elements of each dimension. Each element has its own set of attributes. Some may be set by the user; others are set internally but may be queried by the user. It is also possible to dynamically define "extra attributes" for any type of element, which may be single values or vectors of values.

§4.1.1. Vertices.

A vertex is a point in space. The coordinates of the vertices are the parameters that determine the location of the surface. It is the coordinates that are changed when the surface evolves.

Attributes:

coordinates - either Euclidean coordinates or boundary parameters.

fixed - vertex cannot be moved or eliminated.

constraints - vertex may be subject to a set of constraints.

boundary - vertex position is defined parametrically on a boundary. A vertex can be on at most one boundary.

id - an identification number.

original - number of the vertex in the original datafile

§4.1.2. Edges.

An edge is an oriented line segment between a tail vertex and a head vertex.

Attributes:

vertices - numbers of the tail and head vertices of the edge.

midv - in the quadratic model, the midpoint of the edge.

length - actual length of the edge.

fixed - endpoints fixed, and all vertices generated from subdividing edge will be fixed.

constraints - set of constraints edge satisfies. Constraints may be used to specify volume and energy integrands.

boundary - edge may be in one boundary.

torus wrapping - whether edge crosses torus unit cell faces, and in which direction.

density - energy per unit length in string model.

color - for display.

id - an identification number.

original - number of the original datafile edge this edge is descended from.

§4.1.3. Facets.

A facet is an oriented triangle defined by its edges.

Attributes:

edges - loop of three edges connected head to tail.

area - actual area of the facet.

fixed - fixedness inherited by all elements descended from this facet.

constraints - set of constraints facet satisfies.

boundary - facet may be in one boundary.

density - energy per unit area; surface tension.

energy - whether facet has a surface energy integrand.

quantities - facet contribution to user-defined quantity integrals.

displayable - whether facet should be displayed in graphics.

tag - a user-defined number that can identify groups of facets.

id - an identification number.

original - number of the original datafile edge this edge is descended from.

color - for display.

frontcolor, backcolor - for coloring the two sides differently.

phase - for determining boundary tension in string model.

§4.1.4. Bodies.

A body is a three-dimensional region of space.

Attributes:

facets - a set of oriented facets defines the boundary of body. These facets are used for calculating body volume and gravitational energy. Only those facets needed for correct calculation need be given.

id - an identification number.

density - for gravitational potential energy.

volume - actual volume.

target volume - constrained volume value set by user.

volume constant - an adjustment used in the torus model to do correct volume calculations.

pressure - for prescribed pressure, or for pressure resulting from volume constraint.

phase - for determining boundary tension in soapfilm model.

§4.2. Quadratic represention.

By default, edges and facets are linear. It is possible to represent edges as quadratic curves and facets as quadratic patches by putting the `QUADRATIC` keyword in the datafile or by using the `M` command. If this is done, then each edge is endowed with a midpoint vertex. Some basic features are implemented for the quadratic representation, such as area, volume, constraints, and basic named quantity methods.

§4.3. Dimension of surface.

In the standard Evolver surface, the surface tension resides in the two-dimensional facets (this is referred to as the **soapfilm model**.). However, it is possible to have the tension reside in the edges. This is referred to as the **string model** and is declared by the keyword `STRING` in the datafile. See `slidestr.fe` for an example. It is possible in the soapfilm model to also have edges with tension in order to represent a situation where singular curves have energy. This chapter is written for the soapfilm model. For differences in the string model, see the **String Model** section below. For a surface of more than two dimensions, see **Simplex model**.

§4.4. Simplex model.

This model represents a surface solely with vertices and facets. It was put in to enable representation of arbitrary dimension surfaces, but many Evolver features are not available with it. Here each facet is

represented as an oriented list of $k+1$ vertices, where k is the dimension of the surface. Edges may be specified as $k-1$ dimensional simplices, but they are used only to compute constraint integrals; a complete list of edges is not needed. Bodies still exist for hypersurfaces.

The datafile must have the keyword `SIMPLEX_REPRESENTATION` in the first section, and the phrase `SURFACE_DIMENSION` k if $k \neq 2$. If the domain is not 3-dimensional, then `SPACE_DIMENSION` n must also be included. The `EDGES` section is optional. Each facet should list $k+1$ vertex numbers. Non-simplicial facets are not allowed. See the sample datafile `simplex3.fe`.

Most features are not implemented. Vertices may be `FIXED`. Constraints are allowed, but no integrands of any kind. No `TORUS` domain. No `QUADRATIC` representation. No surface changing except iteration and refining. Refining subdivides each simplex edge, with the edge midpoint inheriting the common attributes of the edge endpoints. Refining will increase the number of facets by a factor of 2^k.

§4.5. Dimension of ambient space.

By default, surfaces live in 3 dimensional space. However, the phrase `SPACE_DIMENSION` n in the datafile sets the dimension to n. This means that all coordinates and vectors have n components. The only restriction is that Evolver has to be compiled with the `MAXCOORD` macro defined to be at least n in Makefile or in `model.h`. Change `MAXCOORD` and recompile if you want more than four dimensions.

Graphics will display only the first three dimensions of spaces with more than three dimensions, except for geomview, which has a four-dimensional viewer built in (although its use is awkward now).

§4.6. Riemannian metric.

The ambient space can be endowed with a Riemannian metric by putting the keyword `METRIC` or `CONFORMAL_METRIC` in the datafile followed by the elements of the metric tensor. A conformal metric tensor is a multiple of the identity matrix, so only one element is needed. Only one coordinate patch is allowed, but the quotient space feature makes this quite flexible. Edges and facets are linear in coordinates, they are not geodesic. The metric is used solely to calculate lengths and areas. It is not used for volume. To get a volume constraint on a body, you will have to define your own "quantity" constraint. See `quadm.fe` for an example of a metric.

One special metric is available built-in. It is the Klein model of hyperbolic space in n dimensions. The domain is the unit disk or sphere in Euclidean coordinates. Including the keyword `KLEIN_METRIC` in the top section of the datafile will invoke this metric. Lengths and areas are calculated exactly, but as with other metrics you are on your own for volumes and quantities.

§4.7. Torus domain.

By default, the domain of a surface is Euclidean space R^3. However, there are many interesting problems dealing with periodic surfaces. The Evolver can take as its domain a flat torus with an arbitrary parallelpiped as its unit cell, i.e. the domain is a parallelpiped with its opposite faces identified. This is indicated by the `TORUS` keyword in the datafile. The defining basis vectors of the parallelpiped are given in the `TORUS_PERIODS` entry of the datafile. See `twointor.fe` for an example.

Certain features are not available with the torus domain, namely quadratic representation, constraints, boundaries, quantities, and gravity. (Actually, you could put them in, but they will not take into account the torus wrapping.) However, there are new named quantity methods that will do quadratic model torus domain.

Volumes and volume constraints are available. However, if the torus is completely partitioned into bodies of prescribed volume, then the volumes must add up to the volume of the unit cell and the `TORUS_FILLED` keyword must be given in the datafile.

Vertex coordinates are given as Euclidean coordinates within the unit cell, not as linear combinations of the basis vectors. The coordinates need not lie within the parallelpiped, as the exact shape of the unit cell is somewhat arbitrary. The way the surface wraps around in the torus is given by saying how the edges cross the faces of the unit cell. In the datafile, each edge has one symbol per dimension indicating how the edge

vector crosses each identified pair of faces, and how the vector between the endpoints needs to be adjusted to get the true edge vector:

- `*` does not cross face
- `+` crosses in same direction as basis vector, so basis vector added to edge vector
- `-` crosses in opposite direction, so basis vector subtracted from edge vector.

There are several options for displaying a torus surface:

Raw cell - Graph the facets as they are. Good for checking your datafile if it's all triangles. Faces that get subdivided may be unrecognizable.

Connected bodies - Each body's facets are unwrapped in the torus, so the body appears in one connected piece. Nicest option.

Clipped cell - Shows the unit cell specified in the datafile. Facets are clipped on the parallelpiped faces.

§4.8. Quotient spaces.

As a generalization of the torus domain, you may declare the domain to be the quotient space of R^n with respect to some symmetry group. This cannot be completely specified in the datafile, but requires you to write some C routines to define group operations. Group elements are represented by integers attached to edges (like the wrap specifications in the torus model). You define the integer representation of the group elements. See the files `quotient.c` and `symtest.fe` for an example. See `khyp.c` and `khyp.fe` for a more intricate example modelling an octagon in Klein hyperbolic space identified into a genus 2 surface. The datafile requires the keyword `SYMMETRY_GROUP` followed by your name for the group in quotes. Edges that wrap have their group element specified in the datafile by the phrase "`wrap` n", where n is the number of the group element.

§4.9. Symmetric surfaces.

Symmetric surfaces can often be done more easily by evolving just one fundamental domain. This is easiest if the fundamental region is bounded by planes of mirror symmetry. These planes become constraint surfaces for the fundamental domain (see Constraints below). Multiple images of the fundamental domain may be displayed by using transformation matrices (see `view_transforms` in the Datafile chapter).

§4.10. Constraints.

A constraint is a restriction on the motion of vertices. It may be represented as a level set of a function or as a parametric manifold. The term "constraint" as used in the Evolver refers to the level set formulation, and "boundary" refers to the parametric formulation. The term "volume constraint" is something entirely else, refering to bodies.

A constraint may have several roles:

1. Vertices may be required to lie on a constraint (equality constraint) or on one side (inequality constraint). A constraint may be declared `GLOBAL`, in which case it applies to all vertices. See `mound.fe` for an example.

2. A constraint may have a vectorfield associated with it that is integrated over edges lying in the constraint to give an energy. This is useful for specifying wall contact angles and for calculating gravitational energy. Integrals are not evaluated over edges that are FIXED. See `mound.fe` for an example.

3. A constraint may be declared `CONVEX`, in which case edges in the constraint have an energy associated with them that is proportional to the area between the straight edge and the curved wall. This energy (referred to as "gap energy") is meant to compensate for the tendency for flat facets meeting a curved wall to minimize their area by lengthening some edges on the wall and shortening others, with the net effect of increasing the net gap between the edges and the wall. See `tankex.fe` for an example.

4. A constraint may have a vectorfield associated with it that is integrated over edges lying in the constraint to give a volume contribution to a body whose boundary facets contains the edges. This is useful

for getting correct volumes for bodies without completely surrounding them with otherwise useless facets. It is important to understand how the content is added to the body in order to get the signs right. The integral is evaluated along the positive direction of the edge. If the edge is positively oriented on a facet, and the facet is positively oriented on a body, then the integral is added to the body. This may wind up giving the opposite sign to the integrand from what you think may be natural. Integrals are not evaluated over edges that are FIXED. See `tankex.fe` for an example.

5. A constraint may have a vectorfield associated with it that is integrated as a surface integral over facets lying in the constraint to give a contribution to the total energy. This is useful for having gravity in an arbitrary direction. Integrals are not evaluated over facets that are FIXED. See `tankex.fe` for an example.

Edge integrands are evaluated by Gaussian quadrature. The number of points used is controlled by the `INTEGRAL_ORDER` option in the datafile.

§4.11. Boundaries.

Boundaries are one or two dimensional parameterized manifolds. Vertices, edges, and facets may be deemed to lie in a boundary. For a vertex, this means that the fundamental parameters of the vertex are the parameters of the boundary, and its coordinates are calculated from these. Vertices on boundaries may move during iteration, unless declared fixed. Edges on boundaries do not have energy and content integrals (yet), since one-parameter boundaries are most frequent. See `cat.fe` for an example.

A delicate point is how to handle wrap-arounds on a boundary such as a circle or cylinder. Subdividing a boundary edge requires a midpoint, but taking the average parameters of the endpoints can give nonsense. Therefore the average coordinates are calculated, and that point projected on the boundary as continued from one endpoint.

A general guideline is to use constraints for two-dimensional walls and boundaries for one-dimensional wires. If you are using a boundary wire, you can probably declare the vertices and edges on the boundary to be `FIXED`. Then the boundary becomes just a guide for refining the boundary edges.

NOTE: A vertex on a boundary cannot also have constraints.

§4.12. Energy.

The Evolver works by minimizing the total energy of the surface. This energy can have several components:

1. Surface tension. Soap films and interfaces between different fluids have an energy content proportional to their area. Hence they shrink to minimize energy. The energy per unit area can also be regarded as a surface tension, or force per unit length. Each facet has a surface tension, which is 1 unless the datafile specifies otherwise (see `TENSION` option for faces). Different facets may have different surface tensions. Facet tensions may be changed interactively with the '`set facet tension ...`' command. The contribution to the total energy is the sum of all the facet areas times their respective surface tensions. The surface tension of a facet may also be specified as depending on the phases of the bodies it separates. See `PHASE`.

2. Crystalline integrands. The Evolver can model energies of crystalline surfaces. These energies are proportional to the area of a facet, but they also depend on the direction of the normal. The energy is given by the largest dot product of the surface normal with a set of vectors known as the **Wulff vectors**. Surface area can be regarded as a crystalline integrand whose Wulff vectors are the unit sphere. See the datafile section on Wulff vectors for more. A surface has either crystalline energy or surface tension, not both.

3. Gravitational potential energy. If a body has a density (see `DENSITY` option for bodies), then that body contributes its gravitational energy to the total. The acceleration of gravity G is under user control. Letting ρ be the body density, the energy is defined as

$$E = \int\int\int_{body} G\rho z dV \tag{1}$$

but is calculated by the Divergence Theorem as

$$E = \int\int_{body\ surface} G\rho\frac{z^2}{2}\vec{k}\cdot d\vec{S}. \tag{2}$$

This integral is done over each facet that bounds a body. If a facet bounds two bodies of different density, then the appropriate difference in density is used. Facets lying in the $z = 0$ plane make no contribution, and may be omitted if they are otherwise unneeded. Facets lying in constraints may be omitted if their contributions to the gravitational energy are contained in constraint energy integrals.

4. Constraint edge integrals. An edge on a constraint may have an energy given by integrating a vectorfield $\vec{F}$ over the oriented edge:

$$E = \int_{edge} \vec{F}\cdot d\vec{l}. \tag{3}$$

This is useful for prescribed contact angles on walls (in place of wall facets with equivalent tension) and for gravitational potential energy that would otherwise require facets in the constraint.

5. Surface energy integrals. A facet may contribute an energy resulting from the integration of a vectorfield over the facet as a surface integral. This is useful in modelling gravity from various directions, when the implicit gravity energy doesn't apply. Because this may apply to every facet, it can slow things down. See the **Surface Energies** section of the datafile.

6. Convex constraints. Consider a soap film spanning a circular cylinder. The Evolver must approximate this surface with a collection of facets. The straight edges of these facets cannot conform to the curved wall, and hence the computed area of the surface leaves out the gaps between the outer edges and the wall. The Evolver will naturally try to minimize area by moving the outer vertices around so the gaps increase, ultimately resulting in a surface collapsed to a line. This is not good. Therefore there is provision for a "gap energy" to discourage this. A constraint may be declared `CONVEX` in the datafile. For an edge on such a constraint, an energy is calculated as

$$E = k\left\|\vec{S}\times\vec{Q}\right\|/6 \tag{4}$$

where $\vec{S}$ is the edge vector and $\vec{Q}$ is the projection of the edge on the tangent plane of the constraint at the tail vertex of the edge. The constant k is a global constant called the "gap constant". A gap constant of 1 gives the best approximation to the actual area of the gap. A larger value minimizes gaps and gets vertices nicely spread out along a constraint.

The gap energy falls off quadratically as the surface is refined. That is, refining once reduces the gap energy by a factor of four. You can see if this energy has a significant effect on the surface by changing the value of k with the `k` command.

7. Compressible bodies. If the ideal gas mode is in effect (see `PRESSURE` keyword for datafile), then each body contributes an energy

$$E = P_{amb}V_0\ln(V/V_0) \tag{5}$$

where P_{amb} is the ambient pressure, V_0 is the volume prescribed in the datafile, and V is the actual volume of the body. To account for work done against the ambient pressure, each body also makes a negative contribution of

$$E = -P_{amb}V. \tag{6}$$

8. Prescribed pressure. Each body with a prescribed pressure P contributes energy

$$E = PV. \tag{7}$$

where V is the actual volume of the body. This can be used to generate surfaces of prescribed mean curvature, since mean curvature is proportional to pressure.

9. Squared mean curvature. An average mean curvature around each vertex can be calculated, and the integral of the square of this average counted as energy. This component is included by the

SQUARE_CURVATURE phrase in the datafile. A curvature offset h_0 (so the energy is $(h-h_0)^2$) can be specified with H_ZERO value in the datafile. The weighting factor can be changed with the A command by changing the value of the adjustable constant square curvature modulus. For details of exactly how the integral of squared curvature is calculated, see the Technical Reference section. (This feature is not implemented for the quadratic model.) Several variants of squared mean curvature are available, toggled by effective_area and normal_curvature commands. See the technical reference chapter for details of the formulas. [HKS] reports some experimental results.

10. Mean curvature integral. The energy can include the integral of the signed mean curvature by including the MEAN_CURVATURE_INTEGRAL keyword with weighting factor in the datafile.

11. Squared Gaussian curvature. The Gauss map of a surface maps the surface to a unit sphere by mapping a point to its normal. The Gaussian curvature at a point is the Jacobian of this map. This definition can be extended to piecewise linear surfaces. The Evolver can include the integral of the squared Gaussian curvature in the energy, but it is not yet part of the force calculation.

§4.13. Named quantities and methods.

These are an effort to provide a more systematic way of adding new energies and constraints.

A "method" is a way of calculating a scalar value from some particular type of element (vertex, edge, facet, body). Each method is implemented internally as a set of functions for calculating the value and its gradient as a function of vertex positions. Methods are referred to by their names. See the Datafile chapter for the specifications each needs. See the Technical Reference chapter for detailed descriptions. Methods available in the quadratic model are indicated by a Q below, and methods for which the Hessian can be calculated are indicated with H. D means valid in any dimensional ambient space, and S means valid in the simplex model. Currently defined methods are:

1. vertex_scalar_integral: Function value at a vertex. QHDS.
2. edge_tension or edge_length: Length of edge. QHD.
3. edge_scalar_integral: Integral of a scalar function over arclength. QHD.
4. edge_vector_integral: Integral of a vectorfield over an edge. QHD.
5. edge_general_integral: Integral of a scalar function of position and tangent over an edge. QHD.
6. edge_area: Integral of ydx over an edge. With wrap corrections for torus domain. QH.
7. facet_tension or facet_area: Area of facet. QHDS.
8. facet_area_u: Area of facet. In quadratic model, is an upper bound of area. For the paranoid. QHD.
9. facet_scalar_integral: Integral of a scalar function over facet area. QHD.
10. facet_vector_integral: Integral of a vectorfield over a facet. QH.
11. facet_2form_integral: Integral of a 2-form over a facet. HD.
12. facet_general_integral: Integral of a scalar function of position and normal vector over a facet. QH.
13. facet_volume: Integral of $zdxdy$ over a facet. Includes torus wrapping corrections in the torus domain. QH.
14. simplex_vector_integral: Integral of an (n-1) form over a simplicial facet in n-space. S.
15. gravity_method: Gravitational energy, integral of $(z^2/2)dxdy$ over a facet. HQ.
16. mean_curvature_integral: Integral of signed scalar mean curvature.
17. sq_mean_curvature: Integral of squared mean curvature. D.
18. eff_area_sq_mean_curvature: Integral of squared mean curvature, with effective area corrections.
19. normal_sq_mean_curvature: Integral of squared mean curvature, with normal corrections.
20. Gauss_curvature_integral: Integral of Gaussian curvature.
21. hooke_energy: Energy of edges as springs with reference to a global equilibrium length. D.
22. hooke2_energy: Energy of edges as springs with reference to equilibrium lengths for individual edges. D.

23. `local_hooke_energy`: Energy of edges as springs with equilibrium length being average of lengths of neighbor edges. D. (by John Sullivan).
24. `knot_energy`: An "electrostatic" energy in which vertices are endowed with equal charges. Power law of potential is adjustable. D.
25. `uniform_knot_energy` or `edge_knot_energy`: A knot energy where vertex charge is proportional to neighboring edge length. D.
26. `uniform_knot_energy_normalizer`: Supposed to approximate the part of `uniform_knot_energy` that is singular in the continuous limit.
27. `edge_edge_knot_energy`: Between pairs of edges, energy is inverse square power of distance between midpoints of edges. (by John Sullivan) D.
28. `facet_knot_energy`: Charge on vertex is proportional to area of neighboring facets. D.
29. `buck_knot_energy`: Energy between pair of edges given by formula suggested by Greg Buck.
30. `proj_knot_energy`: Only the normal component of force between vertices is used to desingularize energy.
31. `circle_knot_energy`: Another weird way to calculate a nonsingular energy between pairs of edges.
32. `sphere_knot_energy`: Another weird way to calculate a nonsingular energy between pairs of facets.
33. `sin_knot_energy`: Another weird way to calculate a nonsingular energy between midpoints of pairs of edges. (by John Sullivan)
34. `curvature_function`: Calculates forces as function of mean and Gaussian curvatures at vertices. Function may be changed by user by altering teix.c. No energy, just forces.
35. `average_crossings`: To calculate the average crossing number in all projections of a knot. (by John Sullivan)

Adding a new method involves writing C routines to calculate the value and the gradient as a function of vertex coordinates, and adding a structure to the method name array in `quantity.c`. All the other syntax for invoking it from the datafile is already in place.

A "method instance" is a particular use of a method, with whatever particular parameters may be needed. A method instance may be created explicitly and given a name, or they may be created implicitly by defining quantities to use methods. See the Datafile chapter for details. Every method instance has a "modulus", which is multiplied times the basic method value to give the instance value. A modulus of 0 causes the entire instance calculation to be omitted.

A "quantity" is the sum total of various method instances although usually just one instance is involved. Any quantity may be declared to be one of three types: 1) "energy" quantities which are added to the overall energy of the surface; 2) "fixed" quantities that are constrained to a fixed target value (by Newton steps at each iteration); and 3) "info_only" quantities whose values are merely reported to the user. Each quantity has a "modulus", which is just a scalar multiplier of the sum of all instance values. A modulus of 0 will turn off calculation of all the instances.

The sample datafile `knotty.fe` contains some examples. Quantity values can be seen with the `v` or `A` command, and the `A` command can be used to change the target value of a fixed quantity, the modulus of a quantity, or some parameters associated to various methods.

It is planned that eventually all energies and global constraints will be converted to this system. However, existing syntax will remain valid wherever possible.

§4.14. Numbered surface integrals (obsolete).

An *integral quantity* in the Evolver is a number that can be expressed as the sum of integrals of vector-fields over surfaces and edges. Quantities can be evaluated for informational purposes, or they can be used as constraints (in the mathematical sense). Body volumes and gravitational energy are examples of built-in quantities. Surface tension energy is not a quantity in this sense, since it cannot be written as a vector integral.

The Evolver has a mechanism to add user-defined quantities. These might include center of mass, moment of inertia, magnetic flux, etc. The key to many of these is the Divergence Theorem, which permits volume integrals to be written as surface integrals. You can also use a quantity in place of a body volume that is awkward to do with the built-in volume mechanisms.

Each quantity when first defined in the datafile has given the surface integrand, which may be integrated over all or some facets. For edge integrals, each constraint specification may include integrands for quantities, which are applied to edges subject to that constraint. A quantity acts as a mathematical constraint when it has the `FIXED` attribute and a specified value. These may be displayed and changed interactively with the `Q` command. Values may also be displayed with the `v` command (since volumes are themselves quantities, anyway). See `qmound.fe` for an example of body volume implemented as a quantity.

At present, these are implemented as numbered "surface_energy" integrals. This mechanism is being replaced by the named quantity method "facet_vector_integral", and should be regarded as obsolete.

§4.15. Pressure.

Pressure is force per unit area perpendicular to a surface. In the Evolver, pressure can arise in three ways:

1. If a body has a volume constraint, then the boundary surface is unlikely to be a minimal surface. Hence pressure is needed to counteract the desire of the surface to shrink. When there are volume constraints, the Evolver automatically calculates the pressure needed. The value of the pressure can be seen with the `v` command.

2. A body may have a prescribed pressure. Then the appropriate force is added to the forces on the vertices when calculating the motion of the surface. This is the way to get a surface of prescribed mean curvature, since pressure = surface tension × mean curvature. NOTE: Prescribed volume and prescribed pressure on the same body are illegal. CAUTION: Prescribed pressure can make a surface expand to infinity if the pressure is too large.

3. The Evolver can treat bodies as being made up of an isothermal ideal gas, that is, bodies can be compressible. This happens if the `PRESSURE` keyword comes in the first part of the datafile. The pressure given there is the ambient pressure outside all bodies. Each body must have a volume specified, which is the volume of the body at the ambient pressure.

§4.16. Volume or content.

The terms "volume" and "content" are used for the highest dimensional measure of a region in n-space: area in R^2, volume in R^3, etc. Bodies may have a volume specified in the datafile, which then becomes a volume constraint. The volume of a body can be written as

$$V = \int\int\int_{body} 1 dV, \tag{1}$$

which by the Divergence Theorem can be written a surface integral:

$$V = \int\int_{body\ surface} z\vec{k} \cdot d\vec{S}. \tag{2}$$

This integral is evaluated over all the boundary facets of a body.

The part of the boundary of a body lying on a constraint need not be given as facets. In that case, Stokes' Theorem can be used to convert the part of the surface integral on the constraint to a line integral over the edges where the body surface meets the constraint. The line integral integrands are given as constraint content integrands in the datafile.

An alternate surface integral is

$$V = \frac{1}{3}\int\int_{body\ surface} (x\vec{i} + y\vec{j} + z\vec{k}) \cdot d\vec{S}. \tag{3}$$

This is used if SYMMETRIC_CONTENT is specified in the datafile. It is useful if the constraint content integral (which is evaluated by an approximation) leads to asymmetric results on what should be a symmetric surface.

As with surface area, the gap between flat facets and curved constraints causes problems. You can use constraint content integrals to overcome this. See the tank and sphere examples in the tutorial section.

§4.17. Diffusion.

The Evolver can simulate the real-life phenomenon of gas diffusion between neighboring bubbles. This diffusion is driven by the pressure difference across a surface. This is invoked by the keyword DIFFUSION in the first part of the datafile, followed by the value of the diffusion constant. The amount diffused across a facet during an iteration is calculated as

$$dm = (scale\ factor)(diffusion\ constant)(facet\ area)(pressure\ difference). \tag{1}$$

The scale factor is included as the time step of an iteration. The amount is added to or subtracted from the prescribed volumes of the bodies on either side of the facet.

§4.18. Motion.

The heart of the Evolver is the iteration step that reduces energy while obeying any constraints. The surface is changed by moving the vertices. No changes in topology or triangulation are made (unless certain options are toggled on). The idea is to calculate the velocity at each vertex and move the vertex in that direction. If the conjugate gradient option is in effect, the direction of motion is adjusted accordingly.

The force is the negative gradient of the energy. At each vertex, the gradient of the total energy (see the **Energy** section above) as a function of the position of that vertex is calculated. By default, the velocity is taken to be equal to the force. If the area normalization option is in effect, then the force is divided by 1/3 the area of the neighboring vertices to get an approximation to the mean curvature vector for velocity. If relevant, the gradients of quantity constraints (such as body volumes), and level set constraints are calculated at each vertex. For fixed vertices, all of these are taken as zero. Forces and quantity constraint gradients are projected onto the tangent space of the relevant level set constraints at each vertex. To enforce quantity constraints, a restoring motion along the volume gradients is calculated (there is found a constant for each quantity such that when each vertex is moved by the sum of $(constant)(quantity\ gradient)$ for all quantities including that vertex, then the quantity come out right, at least in a linear approximation). Then multiples of the quantity gradients are added to the forces to keep quantities constant (for volumes, the multiplying factors are the pressures of the bodies, which are actually found as the Lagrange multipliers for the volume constraints).

The actual motion of a vertex is the quantity restoring motion plus a universal scale factor times the velocity. The scale factor can be fixed or it can be optimized (see command m). If optimized, then the Evolver calculates the energy for several values of the scale (doubling or halving each time) until the minimum energy is passed. The optimum scale is then calculated by quadratic interpolation. One can also move by a multiple of the optimum scale by assigning a value to the variable scale_scale. A Runge-Kutta step is also available.

The vertices are then moved. If jiggling is in effect, each non-fixed vertex is moved in a random direction from a Gaussian distribution with standard deviation = (temperature)(characteristic length), where the characteristic length starts out as 1 and is halved at each refinement.

Finally, all level set constraints are enforced. Vertices violating an inequality or equality constraint are projected to the constraint (Newton's method). Several projection steps may be needed, until the violation is less that a certain tolerance or a certain number of steps are done (which generates a warning message). The default constraint tolerance is 1e-12, but it can be set with the CONSTRAINT_TOLERANCE option in the datafile.

§4.19. Hessian.

There is another motion available in restricted circumstances that tries to get to the minimum in one step by calculating the second derivative matrix (Hessian) for energy, and then solving for the minimum energy. The command to do one iteration is "`hessian`". There are some restrictions on its use. The energies it applies to are area, constraint edge integrals, simplex model facet areas, and the named quantity methods so labelled earlier. Note particularly it does not apply to the string model or to ordinary gravity. One can fake strings in the soapfilm model with edge_length quantity, and use gravity_method instead of ordinary gravity. The constraints that are handled are body volumes, level set constraints, and fixed named quantities involving the afore mentioned methods. Unfixed vertices on parameterized boundaries are not handled. Some of these restrictions will be removed in future versions.

The Hessian method should be tried only when the surface is extremely close to a minimum (or some critical point). I advise evolving with other methods (like conjugate gradient) until the energy has converged to 8 places or so. If you do try the Hessian from too far away, it is likely to explode your surface. But if you do "`check_increase ON`", the surface will be restored to its previous state if the Hessian method would increase its energy.

Running the Hessian method is liable to produce a number of warning messages when the matrix is not positive definite. This is normal when there are constraints (such as volumes) or degenerate critical points (for example, due to translational degrees of freedom). A message like

```
WARNING: sdrv:  Not positive definite.  Diag[25] = -3.84845;
```

indicates the raw energy Hessian is indefinite. If the constraints don't make the net Hessian positive semidefinite, then you will get a message like

```
WARNING: Constrained Hessian not positive definite.  Index 3
```

where the index is the number of negative eigenvalues. This may show up in the first few iterations. Don't worry about it unless it shows up when the Hessian method has converged all the way. The first and third types of warning are normally suppressed; if you want to see them, do `hessian_quiet off`.

For degenerate critical points, nullspace directions generate messages like

```
WARNING: sdrv:  Diag[39] = 3.28904e-15; max in row:  3.1778e-15; adding 1
```

As long as the max in row is also small, all is fine. The "adding 1" is just an internal gimmick to get a nonzero pivot.

The criterion for treating a value as zero in solving the Hessian is set by the variable "hessian_epsilon". Its default value is 1e-8.

To get a feel for the Hessian method, try it out with cube.fe.

For more details, see the Hessian section of the Technical Reference chapter.

§4.20. Mobility.

There is a choice to be made in the conversion of the forces on vertices into velocities of vertices. Technically, force is the gradient of energy, hence a covector on the manifold of all possible configurations. In the Evolver, that global covector can be represented as a covector at each vertex. The velocity is a global vector, which is represented as a vector at each vertex. Conversion from the global covector to the global vector requires multiplication by a metric tensor, i.e. singling out a particular inner product on global vectors and covectors. The tensor converting from force to velocity is the *mobility tensor*, represented as the *mobility matrix* M in some coordinate system. Its inverse, converting from velocity to force, is the *resistance tensor* $S = M^{-1}$. The same inner product has to be used in projecting the velocity tangent to the constraints, whether they be level set constraints on vertices or constraints on body volumes or quantity integrals. There are several choices implemented in the Evolver, corresponding to several different physical pictures of how the medium resists the motion of the surface through it.

§4.20.1. Vertex mobility.

This is the default mobility, in which the velocity is equal to the force. Hence M and S are the identity matrices in standard coordinates. The physical interpretation of this is that there is a resistance to motion of

each vertex through the medium proportional to its velocity, but not for the edges. This does not approximate motion by mean curvature, but it is very easy to calculate.

§4.20.2. Area normalization.

In motion by mean curvature, the resistance to motion is really due to the surfaces, not the vertices. One way to approximate this is to say the resistance to motion of a vertex is proportional to the area associated with the vertex. So this scheme makes the resistance of a vertex equal to 1/3 of the area of the star of facets around it (or 1/2 the area of the star of edges in the string model). This is easy to calculate, since it is a local calculation for each vertex. S and M are diagonal matrices.

§4.20.3. Area normalization with effective area.

Simple area normalization as described in the previous paragraph isn't what's really wanted in certain circumstances. It has equal resistance for motion in all directions, both parallel and normal to the surface. If a vertex is a triple junction and migrating along the direction of one of the edges, it shouldn't matter how long that edge is. Therefore, if the effective area mode is in effect, the area associated with a vertex is the area of its star projected normal to the force at the vertex. This is a little more complicated calculation, but it is still local. S and M are block diagonal matrices, with one block for each vertex. At a free edge not on any constraint, the force is tangent to the surface, the resistance is zero, and the mobility is infinite. But this accurately describes a popping soapfilm.

§4.20.4. Approximate polyhedral curvature.

Following a suggestion of Gerhard Dzuik and Alfred Schmidt, the inner product of global vectors is taken to be the integral of the scalar product of their linear interpolations over the facets (or edges in the string model). This has the advantage that the rate of area decrease of the surface is equal to the rate volume is swept out by the surface, which is a characteristic of motion by mean curvature. A big disadvantage is that the matrices M and S are no longer local. See chapter 7 for the details. S is a sparse matrix with entries corresponding to each pair of vertices joined by an edge, and M is its dense inverse.

§4.20.5. Approximate polyhedral curvature with effective area.

The previous section did not make any distinction between motion parallel and perpendicular to the surface. A better approximation is to count only motion perpendicular to the surface. This can be done by projecting the interpolated vectorfields normal to the facets before integrating their scalar product. Now the rate of area decrease is equal to the rate geometric volume is swept out, as opposed to the slightly flaky way one had to calculate volume sweeping in the previous paragraph. Again S is a sparse matrix with entries corresponding to each pair of vertices joined by an edge, and M is its dense inverse.

§4.20.6. User-defined mobility.

The user may define a mobility tensor in the datafile. There is a scalar form with the keyword `MOBILITY` and a tensor form with `MOBILITY_TENSOR`. When in effect, this mobility is multiplied times the velocity to give a new velocity. This happens after any of the previous mobilities of this section have been applied and before projection to constraints. The formulas defining the mobility may include adjustable parameters, permitting the mobility to be adjusted during runtime.

§4.21. Stability.

The timestep of an iteration should not be so large as to amplify perturbations of the surface. Short wavelength perturbations are most prone to amplification. This section contains a sketch of the stability characteristics of the various mobility modes, enough to let the user relate the maximum timestep to the minimum facet or edge size. Two examples are discussed: a zigzag string and a nearly flat surface with equilateral triangulation. Effective area is not included, as it is an insignificant correction for nearly flat surfaces. The general moral of this section is that the maximum time step in iteration is limited by the length of the shortest edge or the area of the smallest facet, except in one case.

§4.21.1. Zigzag string.

Let the amplitude of the perturbation about the midline be Y and the edge length L. Then the force on a vertex is $F = -4Y/L$ for small Y. Let the timestep (the Evolver scale factor) be Δt. Let V be the vertex velocity. Then the critical timestep for amplification of the perturbation is given by $V\Delta t = -2Y$, or $\Delta t = -2Y/V$.

Vertex mobility. Here $V = F$, so $\Delta t = L/2$.

Area normalization. Here the vertex star has length $2L$, so $V = F/L$ and $\Delta t = L^2/2$.

Approximate curvature. It turns out that the zigzag is an eigenvector of the mobility matrix M for the largest eigenvalue 3/L, so $V = 3F/L$ and $\Delta t = L^2/6$. This is a major disadvantage of approximate curvature. If perturbation instability is the limitation on the timestep, it will take three times as many iterations as with area normalization to do the same evolution.

§4.21.2. Perturbed sheet with equilateral triangulation.

Consider a plane surface triangulated with equilateral triangles of area A. The perturbation consists of a tiling of hexagonal dimples with their centers of height Y above their peripheries. The force at a central vertex turns out to be $-\sqrt{3}Y$ and the force at a peripheral vertex $\sqrt{3}Y/2$.

Vertex mobility. The critical time step is given by

$$(\sqrt{3}Y + \sqrt{3}Y/2)\Delta t = 2Y,$$

so $\Delta t = 4/3\sqrt{3}$. Note that this is independent of the triangle size. This is consistent with experience in evolving with optimizing scale factor, where the optimum time step is in the range 0.2 - 0.3 indenpendent of triangle size. This is a definite advantage of this version of mobility, since different parts of the surface can have different size triangulations and one size time step can work for all.

Area normalization. The star area of each vertex is $6A$, so the velocities become $-\sqrt{3}Y/2A$ and $\sqrt{3}Y/4A$, and the critical time step $\Delta t = 4/6\sqrt{3}A$. Hence on a surface with varying size triangles, the timestep is limited by the area of the smallest triangles.

Approximate area. This force turns out to be an eigenvector of the mobility matrix with eigenvalue $2/A$. Hence the velocity is four times that of the area normalization, and the critical time step four times shorter.

§4.22. Topology changes.

The term "topology of the surface" refers to the topology of the union of the facets. The term "triangulation" refers to the specfic way facets subdivide the surface. Some operations, such as iteration, change neither. Some, such as refinement, change the triangulation but not the topology. Some, such as short edge elimination, can change both. Some operations, such as vertex popping, are meant to change the topology.

§4.23. Refinement.

"Refinement" of a triangulation refers to creating a new triangulation by subdividing each triangle of the original triangulation. The scheme used in the Evolver is to create new vertices at the midpoints of all edges and use these to subdivide each facet into four new facets each similar to the original. (See the Technical Reference chapter for simplex refinement.)

Certain attributes of new elements are inherited from the old elements in which they were created. Fixedness, constraints, and boundaries are always inherited. Torus wrapping on edges is inherited by some but not all new edges. Surface tension and displayability are inherited by the new facets.

Refinement can change surface area and energy if there are curved constraints or boundaries. Likewise for body volumes.

§4.24. Adjustable constants and parameters.

For flexibility in the interactive manipulation of the surface, there are several ways in which various constants may be changed:

1. The gravitational constant may be changed with the `G` command. A value of zero turns off evaluation of gravitational energy.
2. Prescribed body volumes or pressures may be changed with the `b` command.
3. You can declare identifiers to be adjustable constants in the datafile and use them in constraints and boundaries in their formulas and integrands. These can be changed interactively with the `A` command. Changing these results in automatic recalculation of the surface, unless `AUTORECALC` has been toggled off.
4. The diffusion constant can be changed with the `f` command.
5. The "gap constant" for gap energies can be changed with the `k` command.
6. The ambient pressure can be changed with the `p` command.
7. The jiggling temperature can be changed with the `j` or `J` commands.

§4.25. The String Model.

This section lists the differences you need to be aware of when using the string model.

In general, a face takes on the role of a body, and an edge takes on the role of a facet. Coordinates are still in 3D. If you want cells of prescribed volume, always put z = 0 for the vertices and for each face make a body with just that one face as boundary.

The face section of the datafile is optional.

Faces are not subdivided on input.

Face area is calculated solely using x,y coordinates, even though vertices are still 3D.

Content refers to area.

Constraint energy and content integrands are scalars (have only one component, `E1` or `C1` as the case may be, and are evaluated at vertices on constraints. Tails of edges count negative, and heads positive.

Chapter 5. The Datafile.

The initial configuration of the surface is read from an ASCII datafile.

§5.1. Lexical format.

For those who know about such things, the datafile is read with a lexical analyzer generated by the `lex` program. The specification is in `datafile.lex`.

§5.1.1. Comments.

Comments may be enclosed in /* */ pairs (as in C) and may span lines. // indicates the rest of the line is a comment, as in C++.

§5.1.2. Lines and line splicing.

The file is made up of lines. Line breaks are significant. The next physical line can be spliced onto the current line by having '\' be the last character of the current line. Line splicing is not effective in // comments. Blank lines and comment lines may be placed freely anywhere in the datafile.

§5.1.3. Including files.

The standard C language method of including other files is available. The file name must be in quotes. If the file is not in the current directory, EVOLVERPATH will be searched. Includes may be nested to something like 10 deep. Example:

```
#include  "common.stuff"
```

§5.1.4. Macros.

Simple macros (no parameters) may be defined as in C:

```
#DEFINE   identifier  string
```

identifier must be an identifier without other special meaning to the parser (see the keyword list below). *string* is the rest of the logical line, not including comments. It will be substituted for *identifier* whenever *identifier* occurs as a token subsequently. Substitutions are re-scanned. No checks for recursiveness are made. There is a maximum length (currently 500 characters) on a macro definition. Note: macro identifiers are separate tokens, so if "-M" translates into "-2", this will be read as two tokens, not a signed number.

§5.1.5. Case.

Case is not significant. All letters are converted to lower case on input.

§5.1.6. Whitespace.

Whitespace consists of spaces, tabs, commas, colons, and semicolons. So it's fine if you want to use commas to separate coordinate values.

§5.1.7. Identifiers.

Identifiers follow standard C rules (composed of alphanumeric characters and '_' with the leading character not a digit) and must not be keywords. Identifiers are used for macros and adjustable constants. Use at least two characters, since single characters can be confused with commands.

§5.1.8. Real numbers.

Values may be in any form acceptable to `atof()`. This includes integers, fixed point, and scientific notation such as

```
2    -3    .5    23.        5e-10    +0.7D2
```

§5.1.9. Keywords.

These words have special meaning to Evolver and should not be used for user-defined names. Also, single-letter names should not be used, as Evolver thinks single letters are commands. Letter-number combinations such as "`Xn`" include `X1, X2, ...`

ABS
ACOS,ACOSH
AMBIENT_PRESSURE
APPROX[IMATE]_CURV[ATURE]
AREA
AREA_FIXED
AREA_NORMALIZATION
AREAWEED
ASIN,ASINH
ASSUME_ORIENTED
ATAN,ATAN2,ATANH
ATTRIBUTE
AUTOCHOP
AUTOPOP
AUTORECALC
AVG
BARE
BACKCOLOR
BACKGROUND
BLUE
BLACK
BODY,BODIES
BODY_COUNT
BOUNDARY,BOUNDARIES
BOUNDARY_CURVATURE
BROWN
BYE
CEIL
CHECK
CHECK_INCREASE
CLEAR
CLIPPED
CLIPPED_CELLS
CLOSE_SHOW
COLOR
COLORMAP
Cn
CONF_EDGE
CONFORMAL_METRIC
CONJ_GRAD
CONNECTED
CONNECTED_CELLS
CONSTRAINT
CONSTRAINTS
CONSTRAINT_TOLERANCE
CONTEXT
CONVEX
COS
COSH
CYAN
DARKGRAY
DEBUG
DELETE
DELETE_COUNT
DEFINE
DENSITY
DIFFUSION
DIHEDRAL
DIRICHLET
DISSOLVE
DISSOLVE_COUNT
DIV_NORMAL_CURVATURE
DO
DUMP
En
EDGE,EDGES
EDGE_COUNT
EDGE_DIVIDE
EDGEWEED
EFFECTIVE_AREA
ELSE
ENERGY,ENERGIES
EPRINT
EQUI_COUNT
ESTIMATE
EXIT
EXP
EXTRAPOLATE
FACE,FACES
FACET,FACETS
FACET_COLORS
FACET_COUNT
FACET_EDGES
FIX
FIXED
FIXED_AREA
FLOOR
FOREACH
FORMULA
FRONTCOLOR
FUNCTION
GAP_CONSTANT
GLOBAL
GO
GRAVITY_CONSTANT
GREEN
HELP
HESSIAN
HESSIAN_EPSILON
HISTORY
HISTOGRAM
HIT_CONSTRAINT
HOMOTHETY
ID
IDIV
IF
IMOD
INTEGER
INTEGRAL_ORDER
ITERATION_COUNTER
JIGGLE
LENGTH
LIGHTBLUE
LIGHTCYAN
LIGHTGRAY
LIGHTGREEN
LIGHTMAGENTA
LIGHTRED
LINEAR
LIST
LOAD
LOG
LOGHISTOGRAM
LONGJ
MAGENTA
MAX
MEAN_CURVATURE_INTEGRAL
MEMDEBUG
MERIT_FACTOR
METHOD
METHOD_INSTANCE
METRIC
MIN
MOBILITY
MOBILITY_TENSOR
MOD
MODULUS
NODISPLAY
NONNEGATIVE
NONPOSITIVE
NORMAL_CURVATURE
NORMAL_MOTION
NOT
NOTCH
NOTCH_COUNT
OFF
OID
ON
ON_BOUNDARY
ON_CONSTRAINT
OPACITY
OPTIMIZE
OR
ORIGINAL
Pn
PARAMETER
PARAMETERS
PERIODS
PI
PHASE
PHASEFILE
PINNING
POP_COUNT
POST_PROJECT
PRESSURE
PRINT
PRINTF
PROCEDURE,PROCEDURES
QUADRATIC
Qn
QUANTITY
QUIET
QUIT
RAW_CELLS
RAWESTV
RAWV
READ
REAL
REBODY
RECALC
RED
REFINE
REFINE_COUNT
RIBIERE
RUNGE_KUTTA
SCALAR_INTEGRAND
SCALE
SCALE_LIMIT
SCALE_SCALE
SET
SHADING
SHELL
SHOW
SHOW_EXPR
SHOW_INNER
SHOW_OFF
SHOW_OUTER
SHOW_TRANS
SHOW_VOL
SHOWQ
SIMPLEX_REPRESENTATION
SIN
SINH
SOAPFILM
SPACE_DIMENSION
SPRING_CONSTANT
SPRINTF
SQR
SQCURV
SQGAUSS
SQRT
SQUARE_CURVATURE
STRING
SUM
SURFACE_DIMENSION
SURFACE_ENERGY
SYMMETRIC_CONTENT
SYMMETRY_GROUP
SYSTEM
TAG
TAN,TANH
TEMPERATURE
TENSION
THEN
THICKEN
TOPINFO
TORUS
TORUS_FILLED
TOTAL
TOTAL_AREA
TOTAL_ENERGY
TOTAL_LENGTH
TOTAL_TIME
TRANSFORM_DEPTH
TRANSFORM_EXPR
TRANSFORMS
UNFIX
UNSET
VALENCE
VECTOR_INTEGRAND
VERTEX,VERTICES
VERTEX_COUNT
VIEW_4D
VIEW_MATRIX
VIEW_TRANSFORMS
VIEW_TRANSFORM_GENERATORS
VOLCONST
VOLUME
WEED_COUNT
WHERE
WHILE
WHITE
WRAP
WULFF
Xn
X,Y,Z,W
YELLOW
ZOOM
ZOOM_RADIUS
ZOOM_VERTEX

§5.1.10. Colors.

The colors of edges and facets are recorded as integers. How these integers translate to colors on the screen is determined by how the graphics drivers are written. The following synonyms are supplied for the integers 0 through 15, and it is hoped that the graphics drivers will be written to display these correctly: `BLACK`, `BLUE`, `GREEN`, `CYAN`, `RED`, `MAGENTA`, `BROWN`, `LIGHTGRAY`, `DARKGRAY`, `LIGHTBLUE`, `LIGHTGREEN`, `LIGHTCYAN`, `LIGHTRED`, `LIGHTMAGENTA`, `YELLOW`, and `WHITE`. The special color value `CLEAR` (-1) makes a facet transparent. These tokens are simply translated to integer values wherever they occur, so these are reserved words.

§5.1.11. Expressions.

Variable expressions are used in constraint and boundary formulas and integrands. Constant expressions can be used wherever a real value is needed. Expressions are given in algebraic notation with the following tokens:

`x1,x2,...`	coordinates
`x,y,z,w`	coordinates
`p1,p2`	parameters for boundaries
constant	any number acceptable to atof()
`G`	current gravitational constant
identifier	adjustable constant
`E, PI`	special constants
`+,-,*,/,%,mod`	real arithmetic
`imod,idiv`	integer arithmetic
`=`	treated as low-precedence -
`(,)`	grouping and functional notation
`^`*n*	raise to integer n power
`**`	raise to real power
`? :`	conditional expression, as in C language

functions:

`abs`	absolute value
`sqr`	square
`sin,cos,tan`	trig functions
`acos,asin,atan`	inverse trig functions
`atan2`	inverse tangent, atan2(y,x)
`sqrt`	square root
`log,exp`	natural log, exponentiation base e
`sinh,cosh,tanh`	hyperbolic functions
`asinh,acosh,atanh`	inverse hyperbolic functions
`pow`	pow(x,y): raise x to real power y
`ceil,floor`	round up or down to integer
`usr`*n*	user-defined functions

User-defined functions can be defined in C in `userfunc.c`. They are meant for situations where expression interpretation is too slow, or functions such as elliptic integrals are wanted. Currently, they are automatically functions of the coordinates. Do not give any arguments in the expression; for example "`(usr1 + usr3)/usr10`".

Expressions are parsed into evaluation trees, which are interpreted when needed. Constant subtrees are folded into constant nodes at parse time.

Constant expressions must evaluate to values when they are read, i.e. they have no parameters or coordinates.

In parsing an expression, the longest legal expression is used. This permits coordinates to be specified by several consecutive expressions with no special separators.

NOTES: A '+' or '-' preceded by whitespace and followed by a number is taken to be a signed number. Thus "3 - 5" and "3-5" are single expressions, but "3 -5" is not. This is for convenience in separating multiple expressions listed on the same line for vertex coordinates, metric components, etc.

The mod operator '%' or `mod` does a real modulus operation:

$$x\%y = x - floor(x/y) * y.$$

The integer operator `idiv` rounds its operands toward zero before doing integer division (as implemented in C). `imod` rounds its operands down:

$$x \text{ imod } y = floor(x) - floor(floor(x)/floor(y)) * floor(y).$$

§5.2. Datafile organization.

The datafile is organized into six parts:

1. Definitions and options
2. Vertices
3. Edges
4. Faces
5. Bodies
6. Commands

In the syntax descriptions below, keywords will be in upper case. *const_expr* means a constant expression, and *expr* means any expression. *n* or *k* means an integer, which may be signed if it is being used as an oriented element label. Square brackets denote optional items. '|' means 'or'.

§5.2.1. Definitions and options.

Each line starts with a keyword. The order is immaterial, except that identifiers must be defined before use and quantities must be defined before referring to them in constraints. None of these are required, but those marked as default will be assumed unless an overriding option is present.

1. Macros.

`#DEFINE` *identifier string*

See Macros section above.

2. Adjustable constants.

`PARAMETER` *identifier* [= *const_expr*]

This declares *identifier* to be an adjustable constant with the given initial value. The default initial value is 0. The value may be changed with the `A` command. Adjustable constants may be used in any subsequent expression. Changing these results in automatic recalculation of the surface, unless `AUTORECALC` has been toggled off.

3. Dimensionality.

`STRING`

The Evolver is to use the string model (see the **String Model** section)

`SOAPFILM` (default)

The Evolver is to use the standard two-dimensional surface model.

`SURFACE_DIMENSION` *const_expr*

Surface is of given dimension. Dimension over 2 is valid only in the simplex model.

4. Domain.

`EUCLIDEAN` (default)

The surface lives in Euclidean space.

`SPACE_DIMENSION` *const_expr*

The surface lives in Euclidean space of the given dimension. Default is 3. The dimension must be at most the value of `MAXCOORD` in `model.h`, which is 4 in the distributed version.

`TORUS`

The surface lives in a 3 dimensional flat torus. Surface is equivalent to a periodic surface.

`TORUS_FILLED`

Indicates the entire torus is filled by bodies to enable the program to avoid degenerate matrices when adjusting constrained volumes.

`PERIODS`
expr *expr* *expr*
expr *expr* *expr*
expr *expr* *expr*

Used with `TORUS` domain. Specifies that the side vectors (basis vectors) of the unit cell parallelpiped follow on the next lines. Each vector is given by its components. The size of this matrix depends on the space dimension. Default is unit cube. Adjustable parameters may be used in the expressions, so the fundamental domain may be changed interactively with either the 'A' command or by assigning new values to the parameters. Be sure to do a '`recalc`' to get the period matrix re-evaluated.

`SYMMETRY_GROUP "`*name*`"`

The domain is the quotient of R^n by a user-defined symmetry group. The user must link in C functions that define the group operations. See `quotient.c` for an example. "*name*" is a double-quoted name that is checked against a name in `quotient.c` to be sure the right symmetry group is linked in.

5. Representation.

`LINEAR` (default)

Facets are flat triangles.

`QUADRATIC`

Facets are quadratic patches. See the **Quadratic Representation** section.

`SIMPLEX_REPRESENTATION`

Facets are defined by oriented vertex list rather than edge list. See the section above on **Simplex Model**.

6. Extra attributes. It is possible to dynamically define extra attributes for elements, which may be single values or vectors. The definition syntax is

`DEFINE` *elementtype* `ATTRIBUTE` *name* `REAL|INTEGER [ [`*dim*`] ]`

where *elementtype* is `vertex, edge, facet,` or `body`, *name* is an identifier of your choice, and *dim* is an optional expression for the vector dimension. There is no practical distinction between real and integer types at the moment, since everything is stored internally as reals. But there may be more datatypes added in the future. Examples:

```
define edge attribute charlie real
```

```
define vertex attribute oldx real[3]
```

7. Surface tension energy. The surface tension energy is always included in the total energy by default. It can be turned off only by giving the facets (or edges in the string model) the "`density 0`" attribute.

`AREA` (default)

Surface energy of a facet is its area times its surface tension.

`WULFF "`*filename*`"`

Specifies that a crystalline integrand is to be used. The next token should be a double-quoted filename (with path) of a file giving the Wulff vectors of the integrand. The format of the file is one Wulff vector per line with its three components in ASCII decimal format separated by spaces. The first blank line ends the specification. Some special integrands can be used by giving a special name in place of the file name. Currently, these are `"hemisphere"` for a Wulff shape that is an upper unit hemisphere, and `"lens"` for two unit spherical caps of thickness 1/2 glued together on a horizontal plane. These two don't need separate files.

`PHASEFILE "`*filename*`"`

This permits the surface tension of a grain boundary to depend on the phases or types of the adjacent grains. The information is read from an ASCII file. The first line of the file has the number of different phases. Each line after consists of two phase numbers and the surface tension between them. If a pair of phases is not mentioned, the surface tension between them is taken to be 1.0. Facets in the string model or bodies in the soapfilm model can be labelled with phases with the `PHASE` phrase.

8. Surface energy integrals.

`SURFACE_ENERGY` *n* `[GLOBAL]`
`E1:` *expr*
`E2:` *expr*
`E3:` *expr*

This defines surface energy integral *n*. *n* must be between 0 and 31. See facet attributes and the Energy section. `GLOBAL` means this energy applies to all facets. This form is obsolete; use the facet_vector_integral named quantity method instead.

9. Squared mean curvature.

`SQUARE_CURVATURE` *const_expr*

This phrase indicates that the integral of squared mean curvature will be included in the energy with a weight given by *const_expr*. The weight can be changed with the `A` command by changing the value of the adjustable constant `square curvature modulus`.

10. Integrated mean curvature.

`MEAN_CURVATURE_INTEGRAL` *const_expr*

This phrase indicates that the integral of mean curvature will be included in the energy with a weight given by *const_expr*. The weight can be changed with the `A` command by changing the value of the adjustable constant `mean curvature modulus`.

11. Squared Gaussian curvature.

`SQUARE_GAUSSIAN_CURVATURE` *const_expr*

This phrase indicates that the integral of squared Gaussian curvature will be included in the energy with a weight given by *const_expr*. The weight can be changed with the `A` command by changing the value of the adjustable constant `square Gaussian modulus`.

12. Ideal gas model.

`PRESSURE` *const_expr*

This specifies that bodies are compressible and the ambient pressure is the given value. The default is that bodies with given volume are not compressible.

13. Gravity.

`GRAVITY_CONSTANT` *const_expr*

Specifies gravitational constant G. Default 1.0.

14. Gap energy.

`GAP_CONSTANT` *const_expr*

Multiplier for convex constraint gap energy. Default 1.0.

15. Knot energy. There are a bunch of named quantity methods for knot energies, and that syntax should be used. But there are a couple of synonyms floating around.

`INSULATING_KNOT_ENERGY` *const_expr*

The total energy will include the insulating knot energy with multiplier *const_expr*. Abbreviation for a named quantity.

`CONDUCTING_KNOT_ENERGY` *const_expr*

The total energy will include the conducting knot energy with multiplier *const_expr*. Abbreviation for a named quantity.

16. Mobility and motion by mean curvature.

`GRADIENT_MODE` (default)

Velocity is equal to the force.

`AREA_NORMALIZATION`

The velocity of a vertex is the force divided by 1/3 area of neighboring facets (or 1/2 length of neighboring edges in string model) to approximate motion by mean curvature.

`APPROXIMATE_CURVATURE`

Calculates vertex velocity from force by means of polyhedral linear interpolation inner product. Do not use together with `AREA_NORMALIZATION`.

`EFFECTIVE_AREA`

For both area normalization and approximate curvature modes, the resistance to motion is only on the component of velocity normal to the surface.

17. Annealing.

`JIGGLE`

Continuous jiggling. Default none.

`TEMPERATURE` *const_expr*

Gives temperature for jiggling. Default 0.05.

18. Diffusion.

`DIFFUSION` *const_expr*

Specifies that diffusion between bodies is in effect with diffusion constant as given. Default 0.

19. Named method instances.

These are methods of calculating scalar values for geometric elements that are referred to by name. They are used by named quantities (see next subsection). For which models each is valid in (linear, quadratic, simplex, etc.), see Chapter 4.

`METHOD_INSTANCE` *name* `METHOD` *methodname* [`MODULUS` *constexpr*] [`GLOBAL`] *parameters*

This is an explicit definition of a named method instance for a named quantity. Such an explicit definition is useful if your quantity has several method instances, and you want to see their individual values or apply the instances to different elements. The modulus multiplies the method value to give the instance value. The default modulus is 1. `GLOBAL` makes the method apply to all elements of the appropriate type. Non-global instances may be applied to elements individually.

Each method may have various parameters to specialize it to an instance. Currently the only parameters specified here are scalar integrands, with syntax

`SCALAR_INTEGRAND`: *expr*

vector integrands, with syntax

`VECTOR_INTEGRAND:`
`Q1:` *expr*
`Q2:` *expr*
`Q3:` *expr*

and 2-form integrands, with syntax

`FORM_INTEGRAND:`
`Q1:` *expr*
`Q2:` *expr*
`Q3:` *expr*
...

where the form components are listed in lexicographic order, i.e. in 4D the six components 12,13,14,23,24,34 would be listed as Q1 through Q6.

Some methods use global parameters (a holdover that will be done away with eventually.) The instance definition does not have to be on one line.

The current methods, their element types, and parameters are listed here:

1. `vertex_scalar_integral`: Function evaluated at vertex. Type: vertex. Parameters: scalar_integrand.
2. `edge_tension` or `edge_length`: Length of edge. Type: edge. Parameters: none.
3. `edge_scalar_integral`: Integral of a scalar function of position over arclength. Type: edge. Parameters: scalar_integrand.
4. `edge_vector_integral`: Integral of a vectorfield over an edge. Type: edge. Parameters: vector_integrand.
5. `edge_general_integral`: Integral of a scalar function of position and tangent over an edge. Type: edge. Parameters: scalar_integrand, with tangent components referred to as coordinates $x_{n+1}, \cdots, x_{2n}$. Example in 3D:

   ```
   quantity ex energy method edge_general_integral
   scalar_integrand:  x^2 - y + z - x4^2 + x5*x6
   ```

6. `edge_area`: Integral of ydx over an edge. With wrap corrections for torus domain. Type: edge. Parameters: none.
7. `facet_tension` or `facet_length`: Area of facet. Type: facet. Parameters: none.
8. `facet_area_u`: Area of facet. In quadratic model, is an upper bound of area. For the paranoid. Type: facet. Parameters: none.
9. `facet_scalar_integral`: Integral of a scalar function over facet area. Type: facet. Parameters: scalar_integrand.

10. `facet_vector_integral`: Integral of a vectorfield over a facet in 3D. Type: facet. Parameters: vector_integrand.
11. `facet_2form_integral`: Integral of a 2-form over a facet in any dimension space. Type: facet. Parameters: form_integrand.
12. `facet_general_integral`: Integral of a scalar function of position and normal vector over a facet. Type: facet. Parameters: scalar_integrand, with normal components referred to as coordinates $x_{n+1}, \cdots, x_{2n}$.
13. `facet_volume`: Integral of $zdxdy$ over a facet. Includes torus wrapping corrections in the torus domain. QH. Type: facet. Parameters: none.
14. `simplex_vector_integral`: Integral of an (n-1) form over a simplicial facet in n-space. Form represented as dual vectorfield. Type: facet. Parameters: vector_integrand.
15. `gravity_method`: For use in calculating the gravitational energy of bodies in 3D. Does the integral of $(z^2/2)dxdy$ over facets. Does not use G, and does not use body densities. To account for body densities, use different instances with different moduli. Type: facet. Parameters: none.
16. `mean_curvature_integral`: Integral of signed scalar mean curvature. Type: edge. Parameters: none.
17. `sq_mean_curvature`: Integral of squared mean curvature. Type: vertex. Parameters: none.
18. `eff_area_sq_mean_curvature`: Integral of squared mean curvature, effective area version of discrete mean curvature. Type: vertex. Parameters: none.
19. `normal_sq_mean_curvature`: Integral of squared mean curvature, normal curvature version of discrete mean curvature. Type: vertex. Parameters: none.
20. `Gauss_curvature_integral`: Integral of Gaussian curvature. Type: facet. Parameters: none.
21. `hooke_energy`: Energy of edges as springs with reference to a global equilibrium length. Type: edge. Global parameters: hooke_power, hooke_length.
22. `hooke2_energy`: Energy of edges as springs with reference to equilibrium lengths for individual edges. Type: edge. Parameters: the extra attribute `hooke_size` for each edge.
23. `local_hooke_energy`: Energy of edges as springs with equilibrium length being average of lengths of neighbor edges. Type: vertex. Parameters: none.
24. `knot_energy`: An "electrostatic" energy in which vertices are endowed with equal charges. Power law of potential is adjustable. Type: vertex. Global parameters: knot_power.
25. `uniform_knot_energy` or `edge_knot_energy`: A knot energy where vertex charge is proportional to neighboring edge length. Type: vertex. Global parameters: knot_power.
26. `uniform_knot_energy_normalizer`: Supposed to approximate the part of `uniform_knot_energy` that is singular in the continuous limit. Type: vertex. Global parameters: knot_power.
27. `edge_edge_knot_energy`: Between pairs of edges, energy is inverse square power of distance between midpoints of edges. (by John Sullivan) Type: edge. Parameters: none.
28. `facet_knot_energy`: Charge on vertex is proportional to area of neighboring facets. Type: vertex. Global parameters: knot_power.
29. `buck_knot_energy`: Energy between pair of edges given by formula suggested by Greg Buck. Type: edge. Global parameters: knot_power.
30. `proj_knot_energy`: Only the normal component of force between vertices is used to desingularize energy. Type: edge. Parameters: knot_power.
31. `circle_knot_energy`: Another weird way to calculate a nonsingular energy between pairs of edges. Type: edge. Parameters: none.
32. `sphere_knot_energy`: Another weird way to calculate a nonsingular energy between pairs of facets. Type: facet. Parameters: none.
33. `sin_knot_energy`: Another weird way to calculate a nonsingular energy between midpoints of pairs of edges. Type: edge. Parameters: none.

34. `curvature_function`: Calculates forces as function of mean and Gaussian curvatures at vertices. Function may be changed by user by altering teix.c. No energy, just forces. Type: vertex. Parameters: none.
35. `average_crossings`: To calculate the average crossing number in all projections of a knot. (by John Sullivan) Type: edge. Parameters: none.

20. Named quantities.

`QUANTITY` *name* `ENERGY`| `FIXED =` *value*| `INFO_ONLY` `MODULUS` *constexpr* *methodlist*

These are an effort to provide a more systematic way of adding new energies and constraints. A "method" is a way of calculating a scalar value from some particular type of element (vertex, edge, facet, body). A "quantity" is the sum total of various methods applied to various elements, although usually just one method is involved. The name is an identifier. Any quantities may be declared to be one of three types: 1) energy quantities are added to the overall energy of the surface; 2) fixed quantities that are constrained to a fixed target value (by a single Newton step at each iteration); and 3) information quantities whose values are merely reported to the user.

Each quantity has a "modulus", which is just a scalar multiplier of the whole quantity. A modulus of 0 will turn off an energy quantity. The default modulus is 1. Adding a new method involves writing C routines to calculate the value and the gradient as a function of vertex coordinates, and adding a structure to the method name array in `quantity.c`.

The quantity definition may contain one or more method instances. To incorporate a previously explicitly defined instance, include

`METHOD` *instancename*

To instantiate a method in the quantity definition, you essentially incorporate the instance definition, but without an instance name:

`METHOD` *methodname* [`MODULUS` *constexpr*] [`GLOBAL`] *parameters*

See the previous subsection for method details. Usually the second, implicit definition will be more convenient, as there is usually only one method per quantity. If `GLOBAL_METHOD` is used instead of `GLOBAL`, then the method is applied to all elements of the proper type. It is equivalent to using the `GLOBAL` keyword in the method specification. Nonglobal instances must be applied individually to elements. That is done by simply adding the quantity or instance name to the line defining the element. If a quantity name is used, then all instances of that quantity of the appropriate type are applied to the element.

Quantity values can be seen with the `Q` or `A` command, and the `A` command can be used to change the target value of a fixed quantity, the modulus of a quantity, or some parameters associated to various methods.

Examples:

Hooke energy:

```
quantity hooke ENERGY modulus 10 global_method hooke_energy
```

A little sample datafile:

```
// test of quantity integrands on constraints

method_instance len method edge_length
quantity lenny info_only method len

quantity sam info_only method facet_scalar_integral
scalar_integrand z

vertices
1   0 0 1 fixed
```

```
2   1 1 2 fixed
3   0 1 3 fixed

edges
1   1 2 lenny
2   2 3
3   3 1 len

faces
1   1 2 3 sam
```

The sample datafile `knotty.fe` contains more examples.

21. Numbered quantities (obsolete).

`QUANTITY` *n* `[GLOBAL] [FIXED =` *value*`]`
`Q1:` *expr*
`Q2:` *expr*
`Q3:` *expr*

This defines quantity number *n*, where *n* is between 0 and 31, inclusive. `GLOBAL` means that it applies to all facets; otherwise, the facet definitions have to specify which quantities they contribute to. If `FIXED` is present, then the quantity acts as a mathematical constraint on the surface, with the quantity being forced to the given *value*. The three expressions following are the components of the vector integrand over facets. The integral is done with the original orientations of the edges. See the **Constraints** section for more on specifying quantities. This style quantity should be considered obsolete; instead use the facet_vector_integral named quantity.

22. Constraints.

`CONSTRAINT` *n* `[GLOBAL] [CONVEX] [NONNEGATIVE | NONPOSITIVE]`
`EQUATION | FORMULA | FUNCTION` *expr*
`[ ENERGY`
`E1` *expr*
`E2` *expr*
`E3` *expr*`]`
`[ CONTENT`
`C1` *expr*
`C2` *expr*
`C3` *expr*`]`
`[ QUANTITY` *n*
`Q1` *expr*
`Q2` *expr*
`Q3` *expr*`]`
`[ QUANTITY ...]`

This defines constraint number *n*, where *n* is an integer between 0 and `MAXCONSTR` (currently 31, except 15 in MS-DOS). `GLOBAL` means the constraint automatically applies to all vertices (but not automatically to edges or faces). `GLOBAL` constraints count in the number limit. If `CONVEX` is given, then an additional gap energy is attributed to edges on the constraint to prevent them from trying to short-circuit a convex boundary; see the Constraints and Energy sections above and the `k` command. If `NONNEGATIVE` or `NONPOSITIVE` is given, then all vertices will be forced to conform appropriately to the constraint at each iteration. The `EQUATION` expression defines the zero level set which is the actual constraint. It may be written as an equation, since '=' is parsed as a low-precedence minus sign. Do not use '>' or '<' to indicate inequalities; use `NONNEGATIVE` or `NONPOSITIVE` and an expresson. Conditional expressions, as in C language, are useful

for defining constraints composed of several surfaces joined smoothly, such as a cylinder with hemispherical caps.

NOTE: One-sided constraints can cause the optimal scale factor algorithm to misbehave. It may be necessary to use a fixed scale factor. See the `m` command below.

IMPORTANT NOTE: Do not let two constraints with the same formula apply to a vertex; that leads to a singular matrix inversion when trying to project the vertex onto the constraints. For example, do not have a vertex subject to X1 = 0 and also have a global X1 `NONNEGATIVE`.

`ENERGY` signifies that vertices or edges on the constraint are deemed to have an energy. In the `SOAPFILM` model, the next three lines give components of a vectorfield that will be integrated along each edge on the constraint. In the `STRING` model, just one component is needed, which is evaluated at each vertex on the constraint. The main purpose of this is to permit facets entirely on the constraint to be omitted. Any energy they would have had should be included here. One use is to get prescribed contact angles at a constraint. This energy should also include gravitational potential energy due to omitted facets. Integrals are not evaluated on FIXED edges.

`CONTENT` signifies that vertices (`STRING` model) or edges (`SOAPFILM` model) on the constraint contribute to the area or volume of bodies. If the boundary of a body that is on a constraint is not given as facets, then the body volume must get a contribution from a content integral. It is important to understand how the content is added to the body in order to get the signs right. The integral is evaluated along the positive direction of the edge. If the edge is positively oriented on a facet, and the facet is positively oriented on a body, then the integral is added to the body. This may wind up giving the opposite sign to the integrand from what you think may be natural. Always check a new datafile when you load it to be sure the integrals come out right.

`QUANTITY` *n* means that edges subject to this constraint contribute to quantity *n*. The three expressions that follow are the components of the integrand for the edges. The integral is done with the original orientations of the edges. Any number of quantities may be included with a constraint, as long as they have been previously defined.

Warning: These integrals are evaluated only for edges which are on the constraints and both of whose endpoints are on the constraints. It is a bad idea to put any of these integrals on one-sided constraints, as both endpoints must actually hit the constraint to count.

23. Constraint tolerance.

`CONSTRAINT_TOLERANCE` *const_expr*

This is the tolerance within which a vertex is deemed to satisfy a constraint. Default 1e-12.

24. Area constraint.

`AREA_FIXED` *const_expr*

This makes the total area of the surface a constraint with the given value. May be changed with the " `area_fixed` := value" command. Obsolete; use a facet_area fixed quantity.

25. Boundaries.

`BOUNDARY` *n* `PARAMETERS` *k* `[CONVEX]`
`X1` *expr*
`X2` *expr*
`X3` *expr*

This defines boundary number *n*, where *n* is an integer between 1 and `MAXBDRY` (currently 20) and *k* is the number of parameters (1 or 2). If `CONVEX` is given, then an additional energy is attributed to edges on the boundary to prevent them from trying to short-circuit a convex boundary; see the `k` menu option below. The following three lines have the functions for the three coordinates in terms of the parameters `P1` and maybe `P2`. Energy and content integrals for boundaries are not implemented.

26. Integration order.

`INTEGRAL_ORDER` *n*

Edge integrals are done by n-point Gaussian quadrature. This give exact values for polynomials of degree $2n-1$. . Default is $n = 2$, which will do cubic polynomials exactly. No limit on order, as weights and abscissas are calculated by Evolver. Facet integrals are done with 1, 3, or 7 point integration, depending on whether $n \le 1$, $n \le 3$, or $n > 3$.

27. Scale factor.

`SCALE` *const_expr* `[FIXED]`

Sets the initial scale factor. If `FIXED` is present, sets fixed scale factor mode. Default is scale = 0.1 and optimizing mode.

`SCALE_LIMIT` *const_expr*

Sets upper bound on scale factor to prevent runaway motions. Default value is 1. If you use surface tensions and densities not near unity, you may have to set this value.

28. Merit factor.

`MERIT_FACTOR` *const_expr*

When the user requests a report of information (command `i`), Evolver also reports the area/volume merit factor, which is $(total\ area)^3/(total\ volume)^2$ multiplied by this factor. It is useful for comparing different configurations in seeking to minimize area for given volume, as in beating Kelvin's tetrakaidecahedron.

29. Mobility.

`MOBILITY_TENSOR`
expr *expr* *expr*
expr *expr* *expr*
expr *expr* *expr*

or

`MOBILITY` *expr*

The force vector is multiplied by the mobility scalar or tensor to get the velocity. Good for, say, having grain boundary mobility depend on temperature.

30. Metric.

`METRIC`
expr *expr* *expr*
expr *expr* *expr*
expr *expr* *expr*

or

`CONFORMAL_METRIC`
expr

or

`KLEIN_METRIC`

The user may define a background metric for the string model only. The keyword `METRIC` is follwed by the N^2 components of the metric tensor, where N is the dimension of space. The components do not have to obey any particular line layout; they may be all on one line, or each on its own line, or any combination. It is up to the user to maintain symmetry. A conformal metric is a scalar multiple of the identity matrix, and only the multiple need be given. A conformal metric will run about twice as fast. The Klein metric is a built-in metric for hyperbolic n-space modelled on the unit disk or ball.

31. Autochopping.

AUTOCHOP *const_expr*

This turns on autochopping of long edges. The constant is the maximum edge length.

32. Autopopping.

AUTOPOP

This turns on autopopping of short edges and improper vertices.

33. Total time.

TOTAL_TIME *const_expr*

This permits setting the initial time of a surface evolving with a fixed scale. Used primarily when resuming from a dump file.

34. Runge-Kutta.

RUNGE_KUTTA *const_expr*

This turns on doing iteration with the Runge-Kutta method.

35. Homothety scaling.

HOMOTHETY *const_expr*

This turns on doing homothety scaling each iteration. The scaling is a uniform scaling from the origin to keep the total volume of all bodies at the given value.

36. Viewing matrix.

VIEW_MATRIX
const_expr const_expr const_expr const_expr
const_expr const_expr const_expr const_expr
const_expr const_expr const_expr const_expr
const_expr const_expr const_expr const_expr

For the specification of the initial viewing transformation matrix of the surface. The matrix is in homogeneous coordinates with translations in the last column. The size of the matrix is one more than the space dimension. This matrix will be part of all dump files, so the view can be saved between sessions. This matrix only applies to internal graphics (Postscript, Xwindows, etc.) and not external graphics (geomview).

37. View transforms.

VIEW_TRANSFORMS *integer*
[color *color*]
const_expr const_expr const_expr const_expr
const_expr const_expr const_expr const_expr
const_expr const_expr const_expr const_expr
const_expr const_expr const_expr const_expr
...

For the display of several transformations of the surface simultaneously, a number of viewing transformation matrices may be given. The transforms apply to all graphics, internal and external, and are prior to the viewing transformation matrix for internal graphics. The identity transform is always done, so it does not need to be specified. The number of matrices follows the keyword VIEW_TRANSFORMS. Each matrix is in homogeneous coordinates. The size of each matrix is one more than the space dimension. Individual matrices need no special separation; Evolver just goes on an expression reading frenzy until it has all the numbers it wants. Each matrix may be preceded by a color specification that applies to facets transformed by that matrix. The color applies to one transform only; it does not continue until the next color specification. Transforms may be activated or deactivated interactively with the **transforms on** or **transforms off**. See the next paragraph for a more sophisticated way to control view transforms.

38. View transform generators.

VIEW_TRANSFORM_GENERATORS *integer*
const_expr const_expr const_expr const_expr
const_expr const_expr const_expr const_expr
const_expr const_expr const_expr const_expr
const_expr const_expr const_expr const_expr
...

Listing all the view transforms as in the previous paragraph is tedious and inflexible. An alternative is to list just a few matrices that can generate transforms. See the `transform_expr` command for instructions on entering the expression that generates the actual transforms.

§5.2.2. Element lists.

The lists of geometric elements follow a general format. Each element is defined on one line. The first entry on a line is the element number. Numbering need not be consecutive, and may omit numbers, but be aware that internally elements will be renumbered in order. The original number in the datafile is accessible as the "original" attribute of an element. After the element number comes the basic defining data, followed by optional attributes in arbitrary order. Besides the particular attributes for each element type listed below, one may specify values for any extra attributes defined earlier. The syntax is attribute name followed by the appropriate number of values. Also an arbitrary number of named quantities or method instances may be listed. These add method values for this element to the named quantity. The named quantity or instance must have been declared in the top section of the datafile. See the **Named quantity** section above.

§5.2.3. Vertex list.

The vertex list is started by the keyword `VERTICES` at the start of a line. It is followed by lines with one vertex specification per line in one of these formats:

k x y z [FIXED] [CONSTRAINT *c1* [*c2*]] [BARE] [*quantityname ...*] [*methodname ...*]
k p1 [*p2*] BOUNDARY *b* [FIXED] [BARE] [*quantityname ...*] [*methodname ...*]

Here *k* is the vertex number, a positive integer. Vertices do not need to be listed in order, and there may be gaps in the numbering. However, if they are not in consecutive order, then the numbering in dump files will be different. *x*, *y*, and *z* are constant expressions for coordinates in the domain; *p1* and *p2* are constant expressions for parameter values. If `FIXED` is given, then the vertex never moves, except possibly for an initial projection to constraints. If `CONSTRAINT` is given, then one or two constraint numbers must follow. (Actually, you can list as many constraints as you want, as long as they are consistent.) The given coordinates need not lie exactly on the constraints; they will be projected onto them.

If `BOUNDARY` is given, then the boundary parameter values are given instead of the coordinates. The vertex coordinates will be defined by the coordinate formulas of boundary number *b*. A vertex may be on only one boundary.

The `BARE` attribute is just an instruction to the checking routines that this vertex is not supposed to have an adjacent facet in the soapfilm model, so spurious warnings will not be generated. This is useful when you want to show bare wires or outline fundamental domains.

§5.2.4. Edge list.

The edge list is started by the keyword `EDGES` at the start of a line. It is followed by lines with one edge specification per line in this format (linespliced here):

k v1 v2 [*midv*] [*s1 s2 s3*] [FIXED] [BOUNDARY *b*] [CONSTRAINTS *c1* [*c2*]]\
[TENSION | DENSITY *const_expr*] [COLOR *n*] [BARE] \
[*quantityname ...*] [*methodname ...*]

Here *k* is the edge number, with numbering following the same rules as for vertices. *v1* and *v2* are the numbers of the tail and head vertices of the edge. In the quadratic model, the edge midpoint may be listed as a third vertex *midv* (by default, a midpoint will be created). In a TORUS model, there follow three signs *s1 s2 s3* indicating how the edge wraps around each unit cell direction: + for once positive, * for none, and - for once negative. FIXED means that all vertices and edges resulting from subdividing this edge will have the FIXED attribute. Likewise the BOUNDARY and CONSTRAINT attributes will be inherited by all edges and vertices derived from this edge. If a constraint has energy or content integrands, these will be done for this edge. IMPORTANT: If a constraint number is given as negative, the edge energy and content integrals will be done in the opposite orientation. In the string model, the default tension is 1, and in the soapfilm model, the default tension is 0. However, edges may be given nonzero tension in the soapfilm model, and they will contribute to the energy.

If the simplex model is in effect, edges are one less dimension than facets and given by an ordered list of vertices. Only edges on constraints with integrals need be listed.

The BARE attribute is just an instruction to the checking routines that this ede is not supposed to have an adjacent facet in the soapfilm model, so spurious warnings will not be generated. This is useful when you want to show bare wires or outline fundamental domains.

§5.2.5. Face list.

The face list is started by the keyword FACES at the start of a line. It is followed by lines with one facets specification per line in this format:

k e1 e2 ... [FIXED] [TENSION | DENSITY *const_expr*] [BOUNDARY *b*] [CONSTRAINTS *c1* [*c2*]] \
[ENERGY *n*] [QUANTITY *n*] [NODISPLAY] [TAG *const_expr*]\
[COLOR *n*] [FRONTCOLOR *n*] [BACKCOLOR *n*] [PHASE *n*] \
[*quantityname ...*] [*methodname ...*]

Here *k* is the face number, with numbering following the same rules as for vertices. There follows a list of oriented edge numbers in counterclockwise order around the face. A negative edge number means the opposite orientation of the edge from that defined in the edge list. The head of the last edge must be the tail of the first edge (except if you're being tricky in the STRING model). There is no limit on the number of edges. The face will be automatically subdivided into triangles if it has more than three edges. The TENSION or DENSITY value is the energy per unit area (the surface tension) of the facet; the default is 1. Density 0 facets exert no force, and can be useful to define volumes or in displays. Fractional density is useful for prescribed contact angles. (Obsolete: QUANTITY *n* means that quantity integrand *n* applies to this facet. Actually, any number of quantities can apply; their numbers just need to be listed after QUANTITY or QUANTITIES. ENERGY *n* means that surface energy integrand *n* applies to this facet. Any number of energies can apply; their numbers just need to be listed after ENERGY or ENERGIES. Please use named quantities instead.) NODISPLAY prevents the facet from being displayed. The TAG number is inherited by refined facets; it is useful for refering to groups of facets with the show query. The COLOR attribute applies to both sides of a facet; FRONTCOLOR applies to the positive side (edges going counterclockwise) and BACKCOLOR to the negative side. The PHASE number is used in the string model to determine the surface tension of edges between facets of different phases, if phases are used. The FIXED, BOUNDARY, CONSTRAINT, DENSITY and NODISPLAY attributes will be inherited by all facets, edges, and vertices resulting from the subdivision of the interior of the face.

If the simplex model is in effect, the edge list should be replaced by an oriented list of vertex numbers.

The faces section is optional in the STRING model.

§5.2.6. Bodies.

The body list is started by the keyword BODIES at the start of a line. It is followed by lines with one body specification per line in this format:

k f1 f2 f3 .... [VOLUME v] [VOLCONST *v*] [PRESSURE *p*] [DENSITY *d*] \

`[PHASE` *n*`]` [*quantityname* ...] [*methodname* ...]

Here *k* is the body number, and *f1 f2 f3* ... is an unordered list of signed facet numbers. Positive sign indicates that the facet normal (as given by the right-hand rule from the edge order in the facet list) is outward from the body and negative means the normal is inward. Giving a `VOLUME` value *v* means the body has a volume constraint, unless the ideal gas model is in effect, in which case *v* is the volume at the ambient pressure. `VOLCONST` is a value added to the volume; it is useful when the volume calculation from facet and edge integrals differs from the true volume by a constant amount. Giving a `PRESSURE` value *p* means that the body is deemed to have a constant internal pressure *p*; this is useful for prescribed mean curvature problems. It is incompatible with prescribed volume. Giving a `DENSITY` value *d* means that gravitational potential energy (gravitational constant G) will be included. *v*, *p*, and *d* are constant expressions.

To endow a facet with `VOLUME`, `PRESSURE`, or `DENSITY` attributes in the `STRING` model, define a body with just the one facet.

The `PHASE` number is used in the soapfilm model to determine the surface tension of facets between bodies of different phases, if phases are used.

The `BODIES` section is optional.

§5.2.7. Commands.

Encountering the keyword `READ` in the datafile causes the Evolver to switch from datafile mode to command mode and read the rest of the datafile as command input. This feature is useful for automatic initialization of the surface with refining, iteration, defining your own commands, etc.

Chapter 6. Operation.

§6.1. System command line.

Syntax:

```
evolver [-ffilename] [-d] [-x] datafile
```

The name of a datafile is a required argument. The current directory and `EVOLVERPATH` will be searched. If the datafile is not found, then a new search with extension "`.fe`" is done.

Options:

`-d` Prints YACC debugging trace as datafile is parsed. May be helpful if you can't figure out why your datafile doesn't get read in properly AND you know YACC.

`-f` Specifies the name of a file to be used as command input. At the end of this file, input reverts to stdin. The effect is the same as redirecting input from the file, except that -f will echo commands to the screen and revert to stdin at the end. Also note that errors will cause input to revert to stdin.

`-t` On NeXTs, sets up a terminal interface instead of menus and dialog boxes. Hence the interface is much more like that on other machines.

`-u` On NeXTs, prevents menus and displays. Pure tty interface. Meant for running on a NeXT from a remote site. But doesn't work since it still wants a DPS interface. Maybe next time.

`-x` Causes Evolver to exit whenever an error occurs. Meant to be used when Evolver is run in a shell script, so that Evolver doesn't get hung up waiting for input in response to an error.

§6.2. Initialization.

The following steps occur when a new datafile is read in:

1. Any previous surface has all memory deallocated.
2. Defaults are initialized.
3. Datafile is read in.
4. Any non-triangular faces are divided into triangles.
5. The order of facets around each edge is determined geometrically.
6. Vertices are projected to their constraints.
7. Checks as described under the `C` command are run.
8. Initial areas, energies, and volumes are calculated.
9. The viewing transformation matrix is reset to center the surface on the screen.
10. The main command interface is started.

§6.3. Error handling.

There are several categories of errors:

1. `WARNING`. Something has happened that you should know about, but it is possible to proceed.
2. `EXPRESSION ERROR`. There is an error in parsing an expression.
3. `PARSING ERROR`. Error in datafile syntax, but parsing will continue as best it can.
4. `DATAFILE ERROR`. Error in datafile semantics, but parsing will continue as best it can.
5. `ERROR`. The current operation cannot continue. It is abandoned and you return to the command prompt.
6. `FATAL ERROR`. The program cannot continue. Exits immediately.

All error messages go to stderr. Errors in the datafile report line numbers and print the current line so far. Note that the real error may have been at the end of the previous line. If command input is being taken from a file at the time an error occurs, the line number of the offending command will be printed and command input will revert to stdin. If the `-x` option was given when Evolver was started, then Evolver will exit immediately with a nonzero error code.

§6.4. Commands.

Commands are of two main types. The first type is one letter (case is significant). These perform simple and common actions. Single-letter commands are listed below in functional groups. The second type is composed of spelled-out words, and is a sort of combination SQL type query language and a programming language.

Commands may be read from the end of the datafile, from a file given on the system command line, from stdin (the terminal), or from a file given in a `READ` command. The interactive command prompt is "`Enter command:  `".

§6.4.1. General language syntax.

Commands are entered one line at a time, parsed, and executed. Multi-line commands may be entered by enclosing them in braces. If a line ends while nested in braces or parenthesis, Evolver will ask for more input. It will also ask for more if the line ends with certain tokens (such as '+') that cannot legally end a command. Explicit continuation to the next line may be indicated by ending a line with a backslash (linesplicing). You may want to use the `read` command to read long commands from a file.

Successfully parsed commands are saved in a history list. They may be accessed with `!!` for the last command or `!`*string* for the latest command with matching initial string. `!`*number* will repeat a command by number. The command will be echoed. The saved history list may be printed with the `history` command.

Some single-letter commands require interactive input. For those, there are equivalent commands listed below that take input information as part of the command. This is so commands may be read from a script without having to put input data on additional lines after the command, although that can still be done for the single-letter versions.

General note: Some commands will prompt you for a value. A null response (just `RETURN`) will leave the old value unchanged and return you to the command prompt. On options where a zero value toggles OFF, the zero must be explicitly entered. Commands that need a real value will accept an arbitrary expression.

Many commands that change the surface or change the model will cause energies and volumes to be recalculated. If you suspect a command has not done this, the `recalc` command will recalculate everything. It will also update any automatic display.

General control structures.

command ; *command* ...

Several commands on the same line may be separated by a semicolon. A semicolon is not needed after the last command. Example:

```
g 10; r; g 10; u
```

{*command* ; ... }

Curly braces group a list of commands into one command. This is useful in the various control structures. Note that '} ' is not a command separator. You still need a semicolon to separate a command list from another command.

command expr

For execution of a command a number of times. Be sure to leave a space between a single-letter command and the expression lest your command be interpreted as one identifier. To avoid several types of confusion, only certain types of commands are repeatable:

1. single letter commands that don't have optional arguments (l,t,j,m,n,w have optional arguments)
2. command list in braces
3. user-defined procedure names

command `|` *stringexpr*

The output of the command is piped to the system command. The *stringexpr* needs to be a quoted string or a string variable. It is interpreted as a system command. Redirection with '>' instead of '—' is not available due to the use of '>' as an comparison operator. If you want output to go to a file, use `"tee file"` or use ordinary redirection in the system command, `"cat >file"`. On systems (such as DOS and Macs) without true piping, the string is interpreted as a filename, so output goes directly to a file instead of a command.

Examples:

```
list facets | "more"
list vertices | "tee vlist" ; g 10
```

`IF` *expr* `THEN` *command* [`ELSE` *command*]

For conditional execution of commands. expr is true if nonzero. Example:

```
if max(edges,length) > 0.02 then {r; g 100 } else g 4
```

`WHILE` *expr* `DO` *command*

`DO` *command* `WHILE` *expr*

For iterated execution of command controlled by a logical expression. Expression is true if nonzero. Example:

```
while max(edges,length) > 0.02 do {r; {g 40; u} 5 }
```

§6.4.2. Single-letter command summary.

There are five groups of commands:

Reporting:

`C` Run consistency checks.
`c` Report count of elements.
`e` Extrapolate.
`i` Information on status.
`v` Report volumes.
`z` Do curvature test.

Model characteristics:

`A` Set adjustable constants.
`a` Toggle area normalization
`b` Set body pressures.
`f` Set diffusion constant.
`G` Set gravity.
`J` Toggle jiggling on every move.
`k` Set boundary gap constant.
`M` Toggle linear/quadratic model.
`m` Toggle fixed motion scale.
`p` Set ambient pressure.
`Q` Report or set quantities.

`U` Toggle conjugate gradient method.

`W` Homothety toggle.

Surface modification:

`g` Go one iteration step. Often followed by a repetition count.

`j` Jiggle once.

`K` Skinny triangle long edge divide.

`l` Subdivide long edges.

`N` Set target volumes to actual.

`n` Notch ridges and valleys.

`O` Pop non-minimal edges.

`o` Pop non-minimal vertices.

`r` Refine triangulation.

`t` Remove tiny edges.

`u` Equiangulate.

`V` Vertex averaging.

`w` Weed out small triangles.

`y` Torus duplication.

`Z` Zoom in on vertex.

Output:

`D` Toggle display every iteration.

`d` Dump surface to datafile.

`P` Create graphics display file.

`s` Show triangulation graphically.

Miscellaneous:

`F` Toggle command logging.

`H,h,?` Help screen.

`q,x` Exit.

The `j`, `l`,`m`,`n`,`t`, and `w` commands require real values, which may be entered on the same line, or given in response to a prompt if not.

§6.5. Alphabetical single-letter command reference.

`A` Adjustable constants. Displays current values and allows you to enter new values. New value is entered as the number of the constant (from the list) and the new value. Values of named quantities, their moduli, and the target values of fixed named quantities also appear here. The modulus and target value may be changed.

`a` Toggles area normalization of vertex forces and other gradient. Be sure you have a small enough scale factor, or else things tend to blow up. Reduce scale factor temporarily after refinement, since triangle areas are cut by a factor of 4 but the old creases remain. When this option is ON, there is an optional check that can be made for facets that move too much. This is done by computing the ratio of the length of the normal change to the length of the old normal. If this exceeds the user-specified value, then all vertices are restored to their previous position. The user should reduce the motion scale factor and iterate again.

`b` Permits user to change body prescribed volumes and pressures. Prints old value for each body and prompts for new.

`C` Runs various internal consistency checks. If no problems, just prints "Checks completed." The checks are:

Element list integrity - checks that data structures are intact.

Facet-edge check - that if a facet adjoins an edge, then the edge adjoins the facet, and that the three edges around a facet link up.

Facet-body check - whether adjacent facets have the same body on the same side.

Collapsed elements - check if endpoints of an edge are the same, and whether neighboring facets share more than one edge and two vertices.

`c` Prints count of elements and memory used and prints various model parameters.

`D` Toggles displaying every iteration. Initially does not display.

`d` Dumps data to ASCII file in same format as initial data file. You will be prompted for a filename. An empty reponse will use the default dump name, which is the datafile name with a ".dmp" extension. Useful for checking your input is being read correctly, for saving current configuration, and for debugging.

`e` Extrapolates total energy to infinite refinement if at least two refinements have been done. Uses last energy values at three successive levels of refinement.

`F` Toggle logging of commands in file. If starting logging, you will be prompted for the name of a log file. Any existing file of that name will be overwritten. Logging stops automatically when the surface is exited. Only commands that change the surface are logged.

`f` Set diffusion constant. Prints old and prompts for new.

`G` Toggles gravity on or off. Gravity starts ON if any body has `DENSITY`; otherwise OFF. Prints old value of gravitational constant and prompts for new.

`g` Do iteration step. Each iteration calculates the force on each vertex due to its contribution to the total energy and moves the vertex by a multiple of the force. There is a global scale factor that multiplies the force to give the displacement. If area normaliztion is turned on, the force at each vertex is also divided by the total area of facets adjacent to the vertex to better approximate motion by mean curvature (but this seems to be often numerically badly behaved due to long skinny facets). If any bodies have prescribed volumes, the vertices are also displaced to bring the volumes back to near the prescribed values.

If scale optimizing (see command `m`) is ON, then different global scale values will be tried until a quadratic interpolation can be done to find the optimal value. (This can blow up under certain circumstances.) The scale factor used for motion is then multipied by the `scale_scale` variable (default value 1).

The output consists of the number of iterations left (for people who wonder how close their 1000 iterations are to ending), the area and energy, and the scale factor. The user can abort repeated iterations by sending an interrupt to the process (SIGINT, to be precise; CTRL-C or whatever on your keyboard).

`h,H,?` Prints help screen listing these commands.

`i` Prints miscellaneous information:

Total energy

Gap energy for convex constraints

Total area of facets

Count of elements and memory usage

Area normalization, if on

LINEAR or QUADRATIC facets

Scale factor value and option (fixed or optimizing)

Diffusion option and diffusion constant value

Gravity option and gravitational constant value

Jiggling status and temperature

Gap constant (for gap energy)

Ambient pressure (if ideal gas model in effect)

Area-volume figure of merit, the ratio of energy cubed (usually energy is area) to volume squared. This ratio is dimensionless and useful in comparing the efficiencies of different shaped surfaces in partitioning space (trying to beat Kelvin's tetrakaidecahedron).

`J` Toggles jiggling on every iteration. If jiggling gets turned on, prompts for temperature value.

`j` Jiggles all vertices once. Useful for shaking up surfaces that get in a rut, especially crystalline integrands. You will be prompted for a "temperature" which is used as a scaling factor, if you don't give a temperature with the command. The actual jiggle is a random displacement of each vertex independently with a Gaussian distribution. See the `longj` command below for a user-definable perturbation.

`K` Finds skinny triangles whose smallest angle is less than a specified cutoff. You will be prompted for a value. Such triangles will have their longest edge subdivided. Should be followed with tiny edge removal (t) and equiangulation (u).

`k` Sets "gap constant" for gap energy for `CONVEX` boundaries. Adds energy roughly proportional to area between edge and boundary. You will be prompted for a value. Normal values are on the order of magnitude of unity. Value k = 1 is closest to true area. Use 0 to eliminate the energy.

`l` Subdivides long edges, creating new facets as necessary. You will be prompted for a cutoff edge length, if you don't give a value with the command. Existing edges longer than the cutoff will be divided once only. Newly created edges will not be divided. Hence there may be some long edges left afterward. If you enter `h`, you will get a histogram of edge lengths. If you hit RETURN with no value, nothing will be done. It is much better to refine than to subdivide all edges.

`M` Sets model type to `LINEAR` or `QUADRATIC`. Changing from `LINEAR` to `QUADRATIC` adds vertices at the midpoints of each edge. Changing from `QUADRATIC` to `LINEAR` deletes the midpoints.

`m` Toggles quadratic search for optimal global motion scale factor. If search is toggled OFF, you will be prompted for a scale factor. If you give a value with the command, then you are setting a fixed scale factor. Values around 0.2 work well when the triangulation is well-behaved and area normalization (command `a`) is off. In optimizing mode, a scale factor getting small, say below 0.01, indicates triangulation problems. Too large a scale factor will show up as total energy increasing. If you have motion by area normalization ON (command `a`), use a small scale factor, like 0.001, until you get a feel for what works.

`N` Normalize body prescribed volumes to current actual volumes.

`n` Notching ridges and valleys. Finds edges that have two adjacent facets, and those facets' normals make an angle greater than some cutoff angle. You will be prompted for the cutoff angle (radians) if you don't give a value with the command. Qualifying edges will have the adjacent facets subdivided by putting a new vertex in the center. Should follow with equiangulation. In the string model, it will refine edges next to vertices with angle between edges (parallel orientation) exceeding the given value.

`O` Pop non-minimal edges. Scans for edges with more than three facets attached. Splits such edges into triple-facet edges. Splits propagate along a multiple edge until they run into some obstacle. Try `octa.fe` for an example.

`o` Pop non-minimal vertices. This command scans the surface for vertices that don't have the topologies of one of the three minimal tangent cones. These are "popped" to proper local topologies. Not all types are properly treated as yet, and this command tends to create a lot of small edges and skinny triangles. Try `popstr.fe` and `octa.fe` for examples.

`P` Produce graphics output files. The view is the same as seen with the `s` command. Several formats are currently available, and a menu will appear. These are now Pixar, geomview, PostScript, SoftImage, and a personal format called Triangle. If you are doing a torus surface, you will be asked for a display option, for which see the **Torus** section. You will be prompted for a filename. For Pixar format, you will be asked whether vertices should have normal vectors for normal interpolation (calculated as the average normal of all facets around a vertex); whether inner facets (adjacent to two bodies) outer facets (adjacent to zero or one body), or all facets are to be plotted; and whether different colors should be used for different bodies. If so, you are asked for the name of a file with a colormap in the format of RGB values, one set per line, values between 0 and 1. (This map may not be effective on all devices.)

You may also be asked if you want thickening. If you do, each facet will be recorded twice, with opposite orientations, with vertices moved from their original positions by the thickening distance (which the option lets you enter) in the normal direction. The normal used at each vertex is the same as used for normal interpolation, so all the facets around a planar vertex will have that vertex moved the same amount. Triple junctions will be separated. Thickening is good for rendering programs that insist on consistently oriented surfaces, or that can't see the backside of a surface. The default thickening distance is one one-thousandth of the diameter of the object.

For file formats, see the section on Graphics file formats.

For those of you that have `geomview`, the relevant commands are here. `Geomview` uses a named pipe interface at the moment. Besides options for starting and stopping simultaneous `geomview`, there are options for starting a named pipe without invoking `geomview`. You will be told the name of the pipe, and it is up to you to start a pipe reader. Evolver blocks until a pipe reader is started. This is useful for having a second instance of Evolver feed a second surface to `geomview` by having `geomview` load the pipe.

`p` Sets ambient pressure in ideal gas model. Large p gives more incompressible bodies.

`Q` Report current values and optionally change target values of user-defined quantities.

`q` Exit program. You will be given a chance to have second thoughts. You may also load a new datafile. Automatically closes graphics if you really quit. Does not save anything.

`r` Refines the triangulation. Edges are divided in two, and `SOAPFILM` facets are divided into four facets with inherited attributes. Reports the number of structures and amount of memory used.

`s` Shows the surface on the screen. The proper display routines must have been linked in for the machine the display is on. Goes into the graphics command mode (see below). Torus surfaces have display options you will be asked for the first time, for which see the **Torus** section. The graphics window may be closed with the `CLOSE_SHOW` command.

`t` Eliminates tiny edges and their adjacent facets. You will be prompted for a cutoff edge length if you don't give a value with the command. If you enter `h`, you will get an edge length histogram. If you hit `RETURN` without a value, nothing will happen. Some edges may not be eliminable due to being `FIXED` or endpoints having different attrtibutes from the edge.

`U` This toggles conjugate gradient mode, which will usually give faster convergence to the minimum energy than the default gradient descent mode. The only difference is that motion is along the conjugate gradient direction, and the maximum scale factor is not in effect. The scale factor should be in optimizing mode. The history vector is reset after every surface modification, such as refinement or equiangulation. After large changes (say, to volume), run without conjugate gradient a few steps to restore sanity.

`u` This command, called "equiangulation", tries to polish up the triangulation. Each edge that has two neighboring facets (and hence is the diagonal of a quadrilateral) is tested to see if switching the quadrilateral diagonal would make the triangles more equiangular. For a plane triangulation, a fully equiangulated triangulation is a Delauney triangulation, but the test makes sense for skew quadrilaterals in 3-space also. It may be necessary to repeat the command several times to get complete equiangulation.

`V` Vertex averaging. For each vertex, computes new position as area-weighted average of centroids of adjacent facets. Only adjacent facets with the same constraints and boundaries are used. Preserves volumes, at least to first order. See the `rawv` command below for vertex averaging without volume preservation, and `rawestv` for ignoring likeness of constraints. Does not move vertices on triple edges or fixed vertices. Vertices on constraints are projected back onto their constraints.

`v` Shows prescribed volume, actual volume, and pressure of each body. Also shows constrained quantities and information-only quantities. Pressures are really the Lagrange multipliers.

`W` Toggles homothety. If homothety ON, then after every iteration, the surface is scaled up so that the total volume of all bodies is 1. Meant to be used on surfaces without any constraints of any kind, to see the limiting shape as surface collapses to a point.

`w` Tries to weed out small triangles. You will be prompted for the cutoff area value if you don't give a value with the command. If you enter `h`, you will get a histogram of areas to guide you. If you hit `RETURN` with no value, nothing will be done. Some small triangles may not be eliminable due to constraints or other such obstacles. The action is to eliminate an edge on the triangle, eliminating several facets in the process. Edges will be tried for elimination in shortest to longest order. WARNING: Although checks are made to see if it is reasonable to eliminate an edge, it is predicated on facets being relatively small. If you tell it to eliminate all below area 5, Evolver may eliminate your entire surface without compunction.

`x` Exit program. You will be given a chance to have second thoughts. You may also load a new datafile. Automatically closes graphics if you really quit. Does not save anything.

`y` Torus duplication. In torus model, prompts for a period number (1,2, or 3) and then doubles the torus unit cell in that direction. Useful for extending simple configurations into more extensive ones.

`Z` Zooms in on a vertex. Asks for vertex number and radius. Number is as given in vertex list in datafile. Beware that vertex numbers change in a dump (but correct current zoom vertex number will be recorded in dump). Eliminates all elements outside that distance from vertex 1. New edges at the radius are made `FIXED`. Meant to investigate tangent cones and intricate behavior, for example, where wire goes through surface in the overhand knot surface. Zooming is only implemented for surfaces without bodies.

`z` Do curvature test on `QUADRATIC` model. Supposed to be useful if you're seeking a surface with monotone mean curvature. Currently checks angle of creases along edges and samples curvature on facet interiors. Orientation is with respect the way facets were originally defined.

§6.6. Command and query language.

The Evolver command language continues to grow by accretion, and it looks like it's headed towards a full programming language. It has variables, expressions, subroutines, conditionals, and iteration constructs. But not subroutine arguments, local variables, structures, or arrays. Variables are either floating point, string, or subroutine names. Some longer examples of command scripts follow the language description.

Command syntax: Keywords are shown in upper case, although case is irrelevant in actual commands, except for single-letter commands. Square brackets enclose optional parts of commands.

Expressions:

Expressions are of two types: numeric and string. String expressions are either quoted strings or are created by the SPRINTF command. Numeric expressions are always floating-point, not integer. Boolean values for conditions are also floating point, 0 for false, nonzero for true. Numeric expressions are given in algebraic notation with the following terms and operators (in precedence order):

constants:	
constant	an explicit number: integer, fixed point, or scientific notation
identifier	adjustable constant (listed by `A` command)
`G`	current gravitational constant
`E, PI`	special constants
element attributes:	
`X1,X2,...`	coordinates
`X,Y,Z,W`	coordinates
`P1,P2`	parameters for boundaries
`ID`	element identifying number
`ORIGINAL`	number of parent datafile element
`TAG`	facet tag number from datafile
`COLOR`	integer representing color of facet, color of front if back different
`FRONTCOLOR`	color of front of facet
`BACKCOLOR`	color of back of facet
`VALENCE`	number of edges on a vertex, facets on edge, edges on a facet, or facets on a body
`AREA`	area of facet
`LENGTH`	length of edge
`VOLUME`	volume of body
`DENSITY`	density of edge, facet, or body
`DIHEDRAL`	dihedral angle of facets on an edge
`ON_CONSTRAINT` n	test if element on given constraint
`HIT_CONSTRAINT` n	test if element on a one-sided constraint

`ON_BOUNDARY` n	test if element on given boundary
`WRAP`	numerical edge wrap in torus model or other quotient space
`MIDV`	in the quadratic model, the midpoint of an edge.
quantity_name	contribution to a named quantity of an element
extra_attribute[expr]	name of user-defined extra attribute, with subscript if needed.

operators:

`()`	grouping and functional notation
`^`*n*	raise to integer n power
`**`	raise to real power
`*,/,%,mod,imod,idiv`	arithmetic
`+,-`	arithmetic
`==,>,<,<=,>=,!=`	comparison
`NOT, !`	logical NOT
`AND, &&`	logical AND
`OR, ||`	logical OR
`?  :`	conditional expression, as in C language

functions: `SQR, SQRT, SIN, COS, TAN, ACOS, SINH, COSH, ASIN, ATAN, ATAN2, LOG, EXP, ABS, FLOOR, CEIL TANH, ASINH, ACOSH, ATANH, POW`

and some internal read-only values:

`vertex_count`	number of vertices
`edge_count`	number of edges
`facet_count`	number of faces
`body_count`	number of bodies
`total_energy`	total energy of the surface
`total_area`	total area of the surface (film model)
`total_length`	total length of the surface (string model)
`space_dimension`	dimension of ambient space
`surface_dimension`	dimension of surface
`torus`	whether torus domain (Boolean)
`torus_filled`	whether `torus_filled` specified in effect (Boolean)
`symmetry_group`	whether any symmetry active (Boolean)
`simplex_representation`	whether facets are represented as simplices (Boolean)
`iteration_counter`	value of index of current iteration loop
`equi_count`	number of edges flipped in last equiangulation
`delete_count`	number of deletions in last delete command
`notch_count`	number of edges notched in last notch command
`dissolve_count`	number of items dissolved in last dissolve command
`pop_count`	number of items popped in last '`o`' or '`O`' command
`where_count`	number of items satisfying last `where` clause
`total` *quantity_name*	value of a named quantity

and some internal read-write values:

`constraint_tolerance`	constraint value regarded as equivalent to zero.
`hessian_epsilon`	magnitude regarded as zero by `hessian` command.
`integration_order`	points used in Gaussian integration
`scale`	current scale factor

Also any toggle command may be used as a Boolean variable in an expression (full word toggles, not single letters). But beware the ambiguity in interpreting a toggle as a command or a value. You may have

to force the toggle to be interpreted as a value. `ad := autodisplay` sets `ad` as a command synonym for `autodisplay`, while `ad := (autodisplay)` records the current boolean value.

NOTES: A '+' or '-' preceded by whitespace and followed by a number is taken to be a signed number. Thus "3 - 5" and "3-5" are single expressions, but "3 -5" is not. This is for convenience in separating multiple expressions listed on the same line in the datafile.

The boolean AND and OR operators use short-circuit evaluation; i.e. the second operand is evaluated only if necessary.

The mod operator '%' does a real modulus operation:

$$x\%y = x - floor(x/y) * y,$$

but it works fine on integer values. The integer operator `idiv` rounds its operands toward zero before doing integer division (as implemented in C). `imod` rounds its operands down:

$$x \bmod y = floor(x) - floor(floor(x)/floor(y)) * floor(y).$$

Elements inherit the original number of their parent element from the datafile; this can be referred to as `original`. New vertices and edges that subdivide facets have an `original` value of -1.

Coordinates for edges are components of the edge vector. Coordinates for a facet are the components of its normal vector, whose length is the facet area (valid in 3D only).

The wrap number for an edge in a quotient space such as a torus is the internal numerical representation of the wrap, as defined by the writer of the quotient group. For the torus, the current encoding is four bits per dimension, with 1 for '+' wrap and 7 for '-' wrap, low dimension in low bits.

In queries and aggregate expressions, the iterating element may be named, and the name may be use to qualify an element attribute to clarify which element it refers to. The syntax is *name.attribute*. The following command uses a named element, although it is not necessary:

```
list facets ff where ff.area < 2
```

Element iterators. One feature different from ordinary C is the presence of iterators over geometric elements. These occur wherever an element type (vertices, edges, facets, bodies, singular or plural) appears in a command. Attributes of the iteration element may be used later in the command. The general form of an iterator is

elementtype [*name*] [`WHERE` *condition*]

The iteration element may be named (useful in nested iterations), in which case the name must be used when the attribute is referenced. Element types used as attributes will just generate the elements associated with the parent element, so if ff is a facet, then ff.vertex will generate its three vertices. Currently implemented subelements are vv.EDGE, vv.FACET, ee.VERTEX, ee.FACET, ff.VERTEX, ff.EDGE, ff.BODY, and bb.FACET, where vv, ee, ff, and bb are the are names of vertices, edges, facets, and bodies respectively. But be sure to remember that in a nested iteration, an unqualified element type generates all elements of that type, not just those associated with the parent element. Also, each iterator can take a "where" clause to limit the elements included.

Aggregate expressions. The maximum, minimum, sum, and average of an expression over a set of elements may be done with aggregate expressions. The general form is

aggregate(*iterator* ,*expr*)

where *aggregate* may be `max`, `min`, `sum`, or `avg`. The iterator generates elements as discussed above. Max and min over logical expressions may be used for logical any and all.

Example: This displays facet 4 and all its neighboring facets:

```
show facets ff where max(ff.edge ee,max(ee.facet fff, fff.id == 4))
```

SQL-type queries on sets of elements:

These commands generally operate on a set of elements defined by an element iterator.

`FOREACH` *iterator* `DO` *command*

Repeat a command for each element generated by the iterator. Examples:

```
foreach vertex do print x^2 + y^2 + z^2
foreach edge ee where ee.dihedral > .4 do \
{  printf "id %g\n",id; foreach ee.vertex do printf " %g %g %g\n",x,y,z; }
```

`LIST` *iterator*

List elements on the screen in the same format as in the datafile. Piping to `more` can be used for long displays. Examples:

```
list vertices | "more"
list vertices where x < 1 and y > 2 and z >= 3 | "tee vfile"
list edges where id == 12
```

`REFINE` *iterator*

Subdivides edges by putting a vertex in the middle of each edge and splitting neighboring facets in two. It is the same action as the long edge subdivide command (command `l`). Facets will be subdivided by putting a vertex in the center and creating edges out to the old vertices. It is strongly suggested that you follow this with equiangulation to nicen up the triangulation. Edge refinement is better than facet refinement as facet refinement can leave long edges even after equiangulation. Example:

```
refine edges where not fixed and length > .1
```

`DELETE` *iterator*

Deletes edges by shrinking the edge to zero length (as in the tiny edge weed command `t`) and facets by eliminating one edge of the facet. Facet edges will be tried for elimination in shortest to longest order. Edges will not be deleted if both endpoints are fixed, or both endpoints have different constraints or boundaries from the edge. Example:

```
delete facets where area < 0.0001
```

`DISSOLVE` *iterator*

Removes elements from the surface without closing the gap left. The effect is the same as if the line for the element were erased from a datafile. Hence no element can be dissolved that is used by a higher dimensional element. Good for poking holes in a surface.

```
dissolve facets where original == 2
```

`SET` *elements* [*name*] *attrib expr* [`WHERE` *expr*]

Sets an attribute to the indicated value for qualifying elements. The new value expression may refer to the element in question. `SET` can change the following attributes: constraint, coordinates, density, non-global named quantity, user-defined extra attributes, tag, target volume, pressure, color, frontcolor, backcolor, and opacity (for the appropriate type elements). For color, the color value is an integer. The integers from 0 to 15 can be referred to by the predefined names `BLACK`, `BLUE`, `GREEN`, `CYAN`, `RED`, `MAGENTA`, `BROWN`, `LIGHTGRAY`, `DARKGRAY`, `LIGHTBLUE`, `LIGHTGREEN`, `LIGHTCYAN`, `LIGHTRED`, `LIGHTMAGENTA`, `YELLOW`, and `WHITE`. The special color value `CLEAR` (-1) makes a facet transparent. Edge colors may not show up in `geomview` unless you do '`show edges where 1`' to have Evolver explicitly feed edges to `geomview` instead of letting `geomview` just show facet edges on its own. On certain systems (Iris and Pixar at present) the opacity value sets the transparency of ALL facets. A value of 0.0 corresponds to transparent, and a value of 1.0 to opaque. Examples:

```
set facets density 0.3 where original == 2
set vertices x 3*x where id < 5
```

```
set bodies volume 5 where id == 1
set vertices constraint 1 where id == 4
set facet color red where tag == 2
set facet color clear where original < 5
set facet opacity 0.5
```

`SET` *elements* [*name*] `FIXED` [`WHERE` *expr*]

Sets the FIXED attribute for qualifying elements. Example:

```
set vertices fixed where id == 4
```

`SET` *name attrib expr*

Inside a FOREACH loop with a named element, one can set an attribute for the named element.

`SET BACKGROUND` *color*

Sets the backgound color for native graphics (not geomview). The color is an integer 0-15 or a color name listed in the general `SET` command below. Example:

```
set background black
```

`UNSET` *elements* [*name*] *attrib* [`WHERE` *expr*]

Removes the attribute for qualifying elements. Attributes here are `FIXED`, `VOLUME`, `PRESSURE`, `DENSITY`, non-global named quantities, `CONSTRAINT` *n*, or `BOUNDARY` *n*. A use for the last is to use a boundary or constraint to define an initial curve or surface, refine to get a decent triangulation, then use "unset vertices boundary 1" and "unset edges boundary 1" to free the curve or surface to evolve.

`UNSET` *elements* [*name*] `CONSTRAINT` *expr* [`WHERE` *expr*]

Removes constraint of given number from qualifying elements.

Single elements:

The verbs set, unset, list, delete, refine, fix, unfix, dissolve can be used on single named elements inside an iteration construct. Examples:

```
foreach edge ee where ee.length < .01 do {
printf "Refining edge %g.",ee.id; refine ee; }
```

Assignment:

Values can be assigned to variables. The variable names must be two or more letters, in order they not be confused with single-letter commands. Note that '`:=`' is used for assignment, not '`=`'. Numeric, string, and command values may be assigned.

identifier `:=` *expr*

identifier `::=` *expr*

Evaluates expression and assigns it to the named variable. If the variable does not exist, it will be created. These are the same class of variables as the adjustable parameters in the datafile, hence are all of global scope and may also be inspected and changed with the '`A`' command. If "::=" is used instead of ":=", then the variable becomes permanent and will not be forgotten when a new surface is begun. (Well, that was the intention. But the semantics got tricky, so for now "::=" means the same as ":=".)

identifier `:=` *command*

identifier `::=` *command*

Makes *identifier* an abbreviation for *command*. Subsequently, *identifier* may be used as a command itself. If "::=" is used instead of ":=", then the variable becomes permanent and will not be forgotten when a new surface is begun. Example:

```
gg := {g 10; u }
gg 12
```

`AMBIENT_PRESSURE :=` *expr*

Sets the ambient pressure outside bodies.

`AREA_FIXED :=` *expr*

Sets the target value for the fixed area constraint. Does not activate constraint.

`AUTOCHOP :=` *expr*

Sets autochop length, so edges longer than this will automatically be subdivided each iteration when autochopping is on. Does not toggle autochopping on.

`COLORMAP` *integer* `:=` "*filename*"

Sets the colormap file name.

`DIFFUSION :=` *expr*

Sets diffusion constant. Does not toggle diffusion on.

`GAP_CONSTANT :=` *expr*

Sets the gap constant for assigning energy to gaps between facets and curved walls. Use 1 for best approximation to area.

`GRAVITY :=` *expr*

Sets gravitational constant. Does not toggle gravity ON if it is OFF.

`QUANTITY` *integer* `:=` *expr*

Sets the target value for a quantity. Does not automatically make it a constraint; use `QUANTITY` *integer* `ON` for that.

`THICKEN :=` *expr*

Sets thickness for double layer display. Does not toggle it on.

Information:

`LIST TOPINFO`

Prints the first section of the datafile on the screen. This is everything before the vertices section.

`PRINT` *expr*

Prints the value of the expression. `PRINT` *expr* can also be used inside an expression, where it prints the expression and evaluates to the value of its expression. Examples:

```
print max(edge,length)   print max(vertex, print (x^2+y^2+z^2) )
```

`PRINT` *procedure_name*

Prints the commands assigned to the named procedure. These are reconstructed from the parse tree, so may not be identical in appearance to the original commands.

`PRINTF` *string*,*expr*,*expr*,...

Prints to standard output using the standard C printf function. Only numeric expressions are valid, so the format string should use only `%f` and `%g` formats. The format string can be a string variable or a quoted string.

identifier `:= SPRINTF` *string*,*expr*,...

Prints to a string variable using the standard C printf function. Only numeric expressions are valid, so the format string should use only `%f` and `%g` formats. The format string can be a string variable or a quoted string.

`HISTOGRAM(`*element* [`WHERE` *expr1*], *expr2*)

`LOGHISTOGRAM(`*element* [`WHERE` *expr1*], *expr2*)

Prints a histogram of the values of *expr2* for the qualifying elements. The syntax is the same as the aggregate expressions. It uses 20 bins, and finds its own maximum and minimum values, so the user does not have to specify binsize. The log version will lump all zero and negative values into one bin. Example:

```
histogram(edge,dihedral*180/pi)
```

General commands:

single-letter

Any of the single letter commands discussed in the last section may be used as a command. If commands are being read from a file, and if the command requires interactive input, each response should be on a separate line following the command.

`AREAWEED` *expr*

Weeds out facets smaller than given area. Same as 'w' command, except does not need interactive response.

`CLOSE_SHOW`

Closes the native graphics window started by the 's' or `SHOW` commands. Does not affect geomview.

`DEFINE` It is possible to dynamically define extra attributes for elements, which may be single values or vectors. The definition syntax is

`DEFINE` *elementtype* `ATTRIBUTE` *name* `REAL|INTEGER` [[*dim*]]

where *elementtype* is `vertex, edge, facet,` or `body`, *name* is an identifier of your choice, and *dim* is an optional expression for the vector dimension. There is no practical distinction between real and integer types at the moment, since everything is stored internally as reals. But there may be more datatypes added in the future. Examples:

```
define edge attribute charlie real
define vertex attribute oldx real[3]
```

`DIRICHLET`

Does one iteration of minimizing the Dirichlet integral of the surface. The current surface is the domain, and the Dirichlet integral of the map from the current surface to the next. This is according to a scheme of Konrad Polthier and Ulrich Pinkall. At minimum Dirichlet integral, the area is minimized also. Works only on area with fixed boundary; no volume constraints or anything else. Seems to converge very slowly near minimum, so not a substitute for other iteration methods. But if you have just a simple soap film far, far from the minimum, then this method can make a big first step.

`DUMP` *filename*

Dumps current surface to named file in datafile format. With no filename, dumps to the default dump file, which is the datafile name with ".dmp" extension.

`EDGEWEED` *expr*

Weeds out edges shorter than given value. Same as '`t`' command, except does not need interactive response.

`HESSIAN`

Attempt to minimize energy in one step using Newton's method with the Hessian matrix of the energy. See the Hessian section of the Model chapter, and the Hessian section of the Technical Reference chapter.

`HISTORY` *filename*

Print the saved history list of commands.

`LOAD` *filename*

Terminates the current surface and loads a new datafile. The filename is the datafile name, and can be either a quoted string or a string variable.

`LONGJ`

Long jiggle once. This provides long wavelength perturbations that can test a surface for stability. The parameters are a wavevector, a phase, and a vector amplitude. The user will be prompted for values. Numbers for vectors should be entered separated by blanks, not commas. An empty reply will accept the defaults. A reply of `r` will generate random values. Any other will exit the command without doing a jiggle. In the random cases, a random amplitude $\vec{A}$ and a random wavelength $\vec{L}$ are chosen from a sphere whose radius is the size of the object. The wavelength is inverted to a wavevector $\vec{w}$. A random phase ψ is picked. Then each vertex $\vec{v}$ is moved by $\vec{A}\sin(\vec{v}\cdot\vec{w}+\psi)$. More control over perturbations may be had with the "`set vertex` *coord* ..." type of command.

`LINEAR`

Changes to linear model.

`NOTCH` *expr*

Notches ridges and valleys with dihedral angle greater than given value. Same as '`n`' command.

`QUADRATIC`

Changes to quadratic model.

`QUIT`

Exits Evolver or starts new datafile. Same as '`q`' single-letter command.

`RAWV`

Does vertex averaging without conserving volume on each side of surface. Will only average vertices with those of like type of constraints. Doesn't move vertices on boundaries.

`RAWESTV`

Does vertex averaging without regard for conserving volume or whether averaged vertices have like constraints. But doesn't move vertices on boundaries.

`READ` *filename*

Reads commands from the named file. The filename can be either a quoted string or a string variable.

`REBODY`

Recalculates connected bodies. Useful after a body has been disconnected by a neck pinching off. Facets of an old body are divided into edge-connected sets, and each set defines a new body (one of which gets the old body number). The new bodies inherit the attributes of the old body. If volume is fixed, then the target volume becomes the new actual volume. New bodies descended from an original body may be queried with the 'original' atttribute.

RECALC

Recalculates everything. Useful after changing some variable or something and recalculation is not automatically done.

SHELL

Invokes a system subshell for the user.

STABILITY_TEST

Calculates the largest eigenvalue of the mobility matrix. Generates a random vector and applies mobility matrix 20 times. Prints out ratios of successive vector lengths. Useful in investigating stability when using approximate curvature.

SYSTEM *systemcommand*

Invokes a subshell to execute the given command. Command must be a quoted string or a string variable. Will wait for command to finish before resuming.

ZOOM [*integer expr*]

Zooms in on vertex whose id is the given integer, with radius the given expression. Same as 'Z' command, but not interactive. If id and radius omitted, then uses current values.

Toggles:

Various features can be toggled on or off by giving the toggle name with ON or OFF. The default is ON. This is different from the single-letter command toggles, which always change the state. The toggle names below have brief descriptions of their actions in the ON state.

APPROX_CURV

Use polyhedral curvature (linear interpolation over facets) for mean curvature vector. Actually establishes the inner product for forms or vectors to be integration over facets of euclidean inner products of linear interpolation of values at vertices.

AREA_FIXED

Activation of fixed total area constraint.

AREA_NORMALIZATION

Convert force on vertex to mean curvature vector by dividing force by area of star around vertex.

ASSUME_ORIENTED

Tells squared mean curvature routines that they can assume the surface is locally consistently oriented. Significant only for extreme shapes.

AUTOCHOP

Do autochopping of long edges each iteration. Use AUTOCHOP := *expr* to set autochop length. Each iteration, any edge that is projected to become longer than the cutoff is bisected. If any bisections are done, the motion calculation is redone.

AUTOPOP

Toggles automatic deletion of short edges and popping of improper vertices each iteration. Before each iteration, any edge projected to shorten to under the critical length is deleted by identifying its endpoints. The critical length is calculated as $L_c = \sqrt{2\Delta t}$, where Δt is the time step or scale factor. Hence this should be used only with a fixed scale, not optimizing scale factor. The critical length is chosen so that instabilities do not arise in motion by mean curvature. If any edges are deleted, then vertices are examined for improper vertices as in the 'o' command. Useful in string model. Not fully implemented in soapfilm model yet, since it doesn't check facet areas.

AUTORECALC

Toggles automatic recalculation of the surface whenever adjustable parameters or energy quantity moduli are changed. Default is ON.

BOUNDARY_CURVATURE

When doing integrals of mean curvature or squared curvature, the curvature of a boundary vertex cannot be defined by its neighbor vertices, so the area of the boundary vertex star instead is counted with an adjacent interior vertex.

CHECK_INCREASE

Toggles checking for increase of energy in an iteration loop. If energy increases, then the iteration loop is halted. Meant for early detection of instabilities and other problems causing the surface to misbehave. Useful in doing a multiple iteration with a fixed scale. Caution: there are circumstances where an energy increase is appropriate, for example when there are volume or quantity constraints and conforming to the constraints means an energy increase initially.

CLIPPED

Sets torus quotient space display to clip to fundamental region. Not an on-off toggle. 3-way toggle with RAW_CELLS and CONNECTED.

COLORMAP

Use colormap from file. Use `COLORMAP := "filename"` to set file.

CONF_EDGE_SQCURV

Calculation of squared curvature by fitting sphere to edge and adjacent vertices (conformal curvature).

CONJ_GRAD

Use conjugate gradient method. See also RIBIERE

CONNECTED

Sets quotient space display to do each body as a connected, wrapped surface. Not an on-off toggle. 3-way toggle with CLIPPED and RAW_CELLS.

DEBUG

Print YACC debug trace of parsing of commands.

DETURCK

Motion by unit velocity along normal, instead of by curvature vector.

DIFFUSION

Activates diffusion step each iteration.

EFFECTIVE_AREA

In area normalization, the resistance factor to motion is taken to be only the projection of the vertex star area perpendicular to the motion. If squared mean curvature is being calculated, this projected area is used in calculating the curvature.

ESTIMATE

Activates estimation of energy decrease in each iteration step. Useful only for a fixed scale factor much less than optimizing, so linear approximation is good.

FACET_COLORS

Enables coloring of facets in certain graphics interfaces (e.g. xgraph). If off, facet color is white. Default on.

`GRAVITY`

Includes gravitational energy in total energy.

`GV_BINARY`

Toggles sending data to geomview in binary format, which is faster than ascii. Default is binary on SGI, ascii on other systems, since there have been problems with binary format on some systems. Ascii is also useful for debugging.

`HOMOTHETY`

Adjust total volume of all bodies to fixed value after each iteration by uniformly scaling entire surface.

`INTERP_NORMALS`

Display using interpolated vertex normals for shading for those graphics interfaces that support it.

`KUSNER`

Calculation of squared curvature by edge formula rather than vertex formula.

`NORMAL_CURVATURE`

Calculation of squared curvature by taking area of vertex to be the component of the volume gradient parallel to the mean curvature vector.

`NORMAL_MOTION`

Projects motion to surface normal, defined as the volume gradient. May be useful with squared curvature if vertices tend to slither sideways into ugly patterns.

`OLD_AREA`

In the string model with area normalization, at a triple vertex Evolver normally tries to calculate the motion so that Von Neumann's law will be obeyed, that is, the rate of area change is proportional to the number of sides of a cell. If old_area is ON, then motion is calculated simply by dividing force by star area.

`QUIET`

Suppresses all normal output messages. Good while running scripts.

`QUIETGO`

Suppresses only iteration step output.

`POST_PROJECT`

Introduces extra projections to volume and fixed quantity constraints each iteration. If convergence fails after 10 iterations, you will get a warning message, repeated iterations will stop, and the variable `iteration_counter` will be negative.

`RAW_CELLS`

Sets quotient space display for plain, unwrapped facets. Not an on-off toggle. 3-way toggle with `CLIPPED` and `CONNECTED`.

`RIBIERE`

Makes the conjugate gradient method use the Polak-Ribiere version instead of Fletcher-Reeves. (The toggle doesn't turn on conjugate gradient.) Polak-Ribiere seems to recover much better from stalling. If you have to stop and restart conjugate gradient often, try "ribiere".

`RUNGE_KUTTA`

Use Runge-Kutta method in iteration step (fixed scale factor only).

`SHADING`

Toggles facet shading in certain graphics interfaces (xgraph, psgraph). Darkness of facet depends on angle of normal from vertical, simulating a light source above surface. Default is ON.

`SHOW_INNER`

Display interior facets, those on 2 bodies.

`SHOW_OUTER`

Display outer facets, those on 0 or 1 body.

`SQGAUSS`

Include squared Gaussian curvature in energy. Soapfilm model only. Included in energy only, not force. This command included just as a convenient way to calculate the integral of the squared Gaussian curvature of a surface.

`THICKEN`

Display thickened surface. Use `THICKEN :=` *expr* to set thickness.

§6.7. Graphics.

Graphics commands control the display of the surface, both the viewing transformation and which elements are seen. Keep in mind that there are two ways to display graphics on many systems: a native or internal mode entirely under the control of the Evolver (such as the X-windows display), and an external mode where information is provided to an external program such as geomview. Remember that hardcopy output (such as Postscript) will show what the native mode shows, not what geomview shows. Some general commands that affect both modes can be made from the main prompt **Enter command:**. Others, that control the native graphics, are made in a special graphics command mode entered by the '**s**' or '**show**' commands.

Note: native mode graphics are assumed to be slow, and don't automatically redraw by default. In particular, there usually is no polling for window redraw events from the operating system, so after moving or resizing a graphics window you may have to give an explicit 's' command to redraw.

The display consists entirely of facets and edges. Special edges (fixed edges, boundary edges, constraint edges, triple edges) are always shown, unless you make their color CLEAR. The individual facet edges can be toggled with the graphics command '`e`' or the geomview command 'ae'.

This section lists the graphics mode commands first and then the general commands.

The graphics mode prompt is "`Graphics command: `". A graphics command is a string of letters followed by RETURN. Each letter causes an action. Some commands may be preceded by an integer count of how many repetitions to do. Example command: `rr15u2z` Rotation commands may be preceded by a real number giving the degrees of rotation; an integer will give a repetition count with the default angle of 6 degrees. If you mean to specify the angle, be sure to include a decimal point.

Commands in graphics command mode:

Repeatable commands:

`u` Tip up. Rotates image six degrees about horizontal axis.

`d` Tip down. Rotates image six degrees other way.

`r` Rotate right. Rotates by six degrees about vertical axis.

`l` Rotate left. Rotates by six degrees the other way.

`c` Rotate clockwise by six degrees about center of screen.

`C` Rotate counterclockwise by six degrees about center of screen.

`z` Zoom. Expands image by factor of 1.2.

`s` Shrink. Contracts image by factor of 1.2.

`arrow keys` Move image half screen width in appropriate direction. May not work on all terminals.

Non-repeatable commands:

`R` Reset viewing angles to original defaults and rescale the image to fit the viewing window.

`e` Toggle showing all the facet edges.

`h` Toggle hiding hidden surfaces. When ON, takes longer to display images, but looks better.

`b` Toggles display of bounding box. Useful for visualizing orientation.

`t` Reset mode of displaying torus surfaces. Choice of raw cell, connected bodies, or clipped unit cell. See the **Torus** section for more explanation.

`w` Toggles display of facets entirely on constraints. Meant to show traces where surfaces meet constraints. "w" stands for "wall". Applies to facets run up against inequality constraints.

`B` Toggles display of facets on boundaries or equality constraints attribute.

`v` Toggles showing of convex and concave edges in different colors. "v" stands for "valleys".

`+` Increments color number used for facet edges.

`-` Decrements color number used for facet edges.

`?` Prints help screen for graphics commands.

`q,x` Exit from graphics mode, and return to main command mode.

Graphics commands in main command mode.

The following commands are entered at the main command prompt:

`SHOW` *elements* [*name*] [`WHERE` *expr*]

Shows surface with screen graphics and goes into graphics command mode. The condition will prescibe which facets or edges will be displayed with graphics commands. The prescription will remain in effect until the next `show` query. It will also be saved in any dump file. Example:

```
show facets where area < .01
```

The default for facets is to show all facets. This can be done with '`show facets`'. But since many graphics displays (such as `geomview`) like to handle showing edges themselves, the default for edges is just to show triple junctions, borders, and other special edges. To force showing of all edges, do '`show edges where 1`'. Such edges will be displayed by `geomview` despite the status of its `ae` command.

`SHOWQ`

Will show surface without going into graphics command mode, with whatever condition is in effect.

`SHOW_EXPR` *elements* [*name*] [`WHERE` *expr*]

This sets the display prescription without actually doing any graphics. Useful when graphics are not available, as when working remotely, and you want to generate graphical file output with a prescription.

`SHOW_TRANS` *string*

Applies string of graphics commands to the image transformation matrix without doing any graphic display. The string must be in double quotes or be a string variable, and is the same format as is accepted by the regular graphics command prompt. Example:

```
show_trans "rrdd5z"
```

`TRANSFORMS [ON|OFF]`

Toggles displaying of multiple viewing transforms. These are either those listed explicitly in the datafile or those generated with a previous `transform_expr` command.

`TRANSFORM_EXPR` *string*

If view transform generators were included in the datafile, then a set of view transforms may be generated by a expression with a syntax much like a regular expression. An expression generates a set of transforms, and are compounded by the following rules. Here a lower-case letter stands for one of the generators, and an upper-case letter for an expression.

a	Generates set I, a.
AB	Generates all ordered products of pairs.
nA	Generates all n-fold ordered products.
$A\|B$	Generates union of sets A and B.
(A)	Grouping; generates same set as A.

The precedence order is that nA is higher than AB which is higher that $A|B$. Note that the expression string must be enclosed in double quotes or be a string variable. Examples:

`transform_expr "3(a|b|c)"` (All products of 3 or fewer generators.)

`transform_expr "abcd"` (Generates sixteen transforms)

All duplicate transforms are removed, so the growth of the sets do not get out of hand. Note that the identity transform is always included. The letter denoting a single generator may be upper or lower case. The order is the same order as in the datafile. If 26 generators are not enough for somebody, let me know.

`VIEW_4D [ON|OFF]`

For `geomview` graphics, sends a full 4D file in 4OFF and 4VECT format. Default is OFF, so `geomview` gets just the 3D projection.

§6.8. Script examples.

Here are some longer examples using the command language. Since the language expects one command per line, long commands have line breaks only within braces so Evolver can tell the command continues. I tend to break long commands up into several little named commands. The best way to use these longer commands is to put their definitions at the end of your datafile in a "read" section, or have them in a separate file you can read with the "read" command.

1. A script to evolve and regularly save dumps in different files:

```
nn := 1
while nn < 100 do { g 100; ff := sprintf "stage%g.dmp",nn; dump ff; nn:=nn+1}
```

2. Your own iterate command to print out what you want, like energy change each step:

```
olde := total_energy;
gg := { g; printf "Change:  %10.5g\n",total_energy-olde; olde:=total_energy}
```

3. A command to print a file listing vertices and edges (happens to be the OFF format for geomview):

```
aa:=foreach vertex vv do { printf "%f %f %f \n",x,y,z }
bb:=foreach facet ff do { printf "3 ";
foreach ff.vertex do printf "%g ",id-1; printf "\n"}
do_off:= { printf "OFF\n%g %g %g\n",vertex_count,facet_count,edge_count;aa;bb}
```

This prints to stdout, so you would use it with redirection:

```
Enter command:  do_off | "cat >test.off"
```

4. A command to duplicate the fundamental region of a symmetric surface across a plane of mirror symmetry.

```
// Producing datafile surface duplicated across a mirror.
// This is set up to do constraint 1 only.
// Mirrored constraints given x numbers.
// Resulting datafile needs mirrored constraints added by hand.
// Usage:  mm | "cat >filename.fe"

// Mirror plane aa*x + bb*y + cc*z = dd
// You have to set these to the proper coefficients for constraint 1
// before doing mm.
aa := 1; bb := 0; cc := 0; dd := 0

ma := foreach vertex do { printf "%g  %g %g %g ",id,x,y,z;
if fixed then printf "fixed ";
if on_constraint 1 then printf "constraint 1 " ;
printf "\n";
}
mb := { voff := vertex_count }
mc := foreach vertex do if not on_constraint 1 then {
lam := 2*(dd-aa*x-bb*y-cc*z)/(aa*aa+bb*bb+cc*cc);
printf "%g  %g %g %g ",id+voff,x+lam*aa,y+lam*bb,z+lam*cc;
if fixed then printf "fixed ";
if on_constraint 1 then printf "constraint 1x " ;
printf "\n";
}
md := foreach edge ee do {
printf "%g   ",id;
foreach ee.vertex do printf "%g ",oid;
if ee.fixed then printf "fixed ";
if ee.on_constraint 1 then printf "constraint 1 " ;
printf "\n";
}
me := { eoff := edge_count }
mf := foreach edge ee do if not on_constraint 1 then {
printf "%g   ",id+eoff;
foreach ee.vertex do {
```

```
if on_constraint 1 then { printf "%g ",oid;}
else { printf "%g ", id+voff;}  } ;
if ee.fixed then printf "fixed ";
if ee.on_constraint 1 then printf "constraint 1x " ;
printf "\n";
}
mg := foreach facet ff do {
printf "%g   ",id;
foreach ff.edge do printf "%g ",oid;
if ff.fixed then printf "fixed ";
if ff.on_constraint 1 then printf "constraint 1 " ;
printf "\n";
}
mh := { foff := facet_count}
mi := foreach facet ff do if not on_constraint 1 then  {
printf "%g   ",id+foff;
foreach ff.edge do
{ if on_constraint 1 then { printf "%g ",id;}
else printf "%g ",(oid<0?-(id+eoff):id+eoff); } ;
if ff.fixed then printf "fixed ";
if ff.on_constraint 1 then printf "constraint 1x " ;
printf "\n";
}
mm := { list topinfo;
printf "\nVertices\n"; ma;mb;mc;
printf "\nEdges\n"; md;me;mf;
printf "\nFaces\n"; mg;mh;mi;
}
```

§6.9. Interrupts.

Evolver operation may be interrupted with the standard keyboard interrupt, CTRL-C usually (SIGINT for you unix gurus). During repeated iteration steps, this will set a flag which causes the repetition to cease after the current step. Otherwise, the current command is aborted and control returns to the main prompt. If Evolver receives SIGTERM (say from the unix kill command), it will dump to the default dump file and exit. This is useful for stopping background processes running on a script and saving the current state. The same thing will happen with SIGHUP, so losing a modem connection will save the current surface.

§6.10. Graphics output file formats.

This section explains the file formats produced by the `P` command.

§6.10.1. Pixar .

A file extension "`.quad`" is automatically added to the filename.

This format lists the facets as quadrilaterals, with the third vertex being repeated. Two options are available:

1. Interpolated normals. This requires recording the normal vector at each vertex.
2. Colors. This requires recording color values (red,green,blue,alpha) at each vertex.

The file starts with a keyword:

`CNPOLY`	colors and normals
`NPOLY`	normals
`CPOLY`	colors

`POLY` vertices only.

There follows one facet per line. Each vertex is printed as three coordinates, three normal vector components (if used), and four color values (if used).

The coordinates are the true coordinates, not transformed for viewing. Facets are not ordered back to front, since Pixar handles viewing and hidden surfaces itself.

§6.10.2. Geomview.

The `P` command menu option 8 starts the geomview program and feeds it data through a named pipe. The file fed into the named pipe follows the geomview command file format. Parts of it may be in binary format for speed. A copy of the file may be created by using the P menu option A to create a pipe, and then using cat on the pipe to read the pipe into your own file. End the file with P option B.

Some handy geomview keyboard commands (to be entered with mouse in the geomview image window):

r Set mouse to rotate mode.

t Set mouse to translate mode.

z Set mouse to zoom mode.

ab Toggle drawing bounding box.

ae Toggle facet edge drawing.

af Toggle drawing facets.

Remember that what you see in geomview is not what you will get with a Postscript output, since Evolver knows nothing about the commands you give geomview.

§6.10.3. PostScript.

The output file is suitable for direct input to a PostScript device. The view is from the current viewing angle as established with the `s` command or the `show_trans "string"` command. Edges and facets are drawn back to front. You are given a choice whether to draw all the grid lines (all the facet edges). Even if you don't choose to, all special edges (fixed, boundary, triple edges, bare edges) will still be drawn. You can prevent an edge from being drawn by giving it the color CLEAR. Color data is optionally included; you will be prompted for your choice. For a string model in at least 3 dimensions, you will also be asked whether you want to show edge crossings with breaks in the background edge, which helps in depth perception. There is also a label option, which prints element numbers, for easy cross-referencing with datafiles. Edge orientation is indicated by the labels being slightly displaced toward the edge head, and face labels are signed according to which side you are seeing. By responding with 'i' or 'o' at the labels prompt, you can get either current id numbers or original id numbers.

§6.10.4. Triangle file.

This is a format I put in to get the data I wanted for a certain external application. This lists one facet per line. Coordinates are viewing transformed to the screen plane. Facets are listed back to front. The format for a line is

x1 y1 x2 y2 x3 y3 w1 w2 w3 d

Here *(x1,y1)*, *(x2,y2)*, and *(x3,y3)* are the vertex coordinates, and *w1*, *w2*, and *w3* are types of edges:

type 0: ordinary edge, no constraints or boundaries, two adjacent facets.

type 1: edge on constraint or boundary, but not fixed.

type 3: fixed edge.

type 4: edge adjacent to at least 3 facets.

These values can be used to weight different types of edges to illustrate the structure of the surface. *d* is the cosine of the angle of the facet normal to the screen normal. Useful for shading facets.

§6.10.5. SoftImage file.

This consists of two files, one with extension `.mdl` and one with `.def`. The extensions are added automatically.

The `.mdl` file has fixed content, except for the name of the picture:

```
SOFTIMAGE 4D Creative Environment   v 1.6  "ASCII"

MODL   "picname"
{
type    PMSH
nbdef   1
scal      1.000000  1.000000  1.000000
rot       0.000000  0.000000  0.000000
trans     0.000000  0.000000  0.000000
}
```

The `.def` file contains a vertex list followed by a quadrilateral list in terms of the vertices.

```
SOFTIMAGE 4D Creative Environment   v 1.6  "ASCII"

PMSH   "picfile"
{
vertex 14
1   0.000000   0.000000   0.000000
2   1.000000   0.000000   0.000000
3   1.000000   1.000000   0.000000
4   0.000000   1.000000   0.000000
5   0.000000   0.000000   1.000000
6   1.000000   0.000000   1.000000
7   1.000000   1.000000   1.000000
8   0.000000   1.000000   1.000000
9   0.500000   0.000000   0.500000
10   1.000000   0.500000   0.500000
11   0.500000   1.000000   0.500000
12   0.000000   0.500000   0.500000
13   0.500000   0.500000   1.000000
14   0.500000   0.500000   0.000000

polygon 24
5          1          9          9
6          2         10         10
7          3         11         11
8          4         12         12
8          5         13         13
2          1         14         14
9          1          2          2
9          2          6          6
9          6          5          5
10          2          3          3
10          3          7          7
10          7          6          6
```

```
11          3          4          4
11          4          8          8
11          8          7          7
12          4          1          1
12          1          5          5
12          5          8          8
13          5          6          6
13          6          7          7
13          7          8          8
14          1          4          4
14          4          3          3
14          3          2          2
}
```

Chapter 7. Technical Reference.

This chapter explains the mathematics and algorithms used by the Evolver. You don't need to know this stuff to use the Evolver, but it's here for anybody who want to know what exactly is going on and for a programmer's reference.

This chapter currently describes mostly the linear soapfilm model, although some of the named quantity methods are done for quadratic model.

§7.1. Notation.

The term "original orientation" refers to the orientation of an element as recorded in its structure. Original orientations begin with the orientations in the datafile, and are inherited thereafter during refinement and other operations.

Edges.

In referring to a edge e:

$\vec{t}$ and $\vec{h}$ are the tail and head of the side.

$\vec{s}$ is the edge vector, $\vec{s} = \vec{h} - \vec{t}$.

a_i and w_i are the abscissas and weights for Gaussian quadrature on the interval [0,1].

Facets.

In referring to a facet f:

T is the facet surface tension.

v_0, v_1, and v_2 are the vertices around a facet in counterclockwise order.

$\vec{s}_0$, $\vec{s}_1$, and $\vec{s}_2$ are the edges in counterclockwise order around a facet, and v_0 is the tail of $\vec{s}_0$.

a_{ij} and w_i are the barycentric coordinates (j is the vertex index) and weights for evaluation point i for Gaussian quadrature on a triangle.

§7.2. Surface representation.

The basic geometric elements are vertices, edges, three-sided facets, and bodies. There is a structure type for each (see `skeleton.h` for definitions). In addition, there is a facet-edge structure for each incident facet and edge pair. Edges, facets, and facet-edges are oriented. Vertices and bodies could in principle be oriented, but they are not. Elements can be referred to by identifiers which implicitly contain an orientation for the element. Currently these identifiers are 32-bit bitfields with one bit for an orientation bit and the rest for a list pointer. Thus one structure is used for both orientations, and the programmer doesn't have to worry about the orientation of the stored structure; all the orientation conversions are taken care of by the structure access functions and macros.

The topology of the surface is defined by the cross-references among the elements. Each facet-edge is in two doubly-linked lists: one of facet-edges around the edge, and another of facet-edges around the facet. Each edge points to its two endpoints (called *head* and *tail*) and to one facet-edge in the facet-edge loop around it. Each facet points to one facet-edge in the facet-edge loop around it, and to the two bodies on its two sides. Each body points to one facet-edge on its boundary. The upshot of all this is that it is easy to find all the facets around an edge or all the edges around a facet. There are also various other linked lists connecting elements; see the Iterators section of the Operation chapter.

§7.3. Energies and forces.

As described in the **Energies** section of the **Model** chapter, all energies are carried by facets or edges. (Volumes for ideal gas energy are calculated from facets and edges also.) Hence it is straightforward to run through all the edges and facets, adding up their energies and accumulating their energy gradients onto the total forces on their vertices. This section gives the formulas used for all the types of energies and forces.

§7.3.1. Surface tension.

Energy of facet.

$$E = \frac{T}{2}\|\vec{s}_0 \times \vec{s}_1\|. \tag{1}$$

Force on vertex.

$$\vec{F}(v_0) = \frac{T}{2}\frac{\vec{s}_1 \times (\vec{s}_0 \times \vec{s}_1)}{\|\vec{s}_0 \times \vec{s}_1\|}. \tag{2}$$

§7.3.2. Crystalline integrand.

$\vec{W}$ is the Wulff vector corresponding to the normal of the facet. The facet has its original orientation.

Energy of facet.

$$E = \frac{T}{2}\vec{W} \cdot \vec{s}_0 \times \vec{s}_1. \tag{3}$$

Force on vertex.

$$\vec{F}(v_0) = \frac{T}{2}\vec{s}_1 \times \vec{W}. \tag{4}$$

§7.3.3. Gravity.

Let G be the acceleration of gravity. Let ρ_+ be the density of the body from which the facet normal is outward, and let ρ_- be the density of the body with inward normal. Let z_i be the z coordinate of v_i. The following formulas are exact for flat facets.

Energy of facet.

$$\begin{aligned} E &= G(\rho_+ - \rho_-)\int\int_{facet}\frac{1}{2}z^2\vec{k}\cdot d\vec{A} \\ &= G(\rho_+ - \rho_-)\frac{1}{12}(z_0^2 + z_1^2 + z_2^2 + z_0z_1 + z_0z_2 + z_1z_2)\frac{1}{2}(\vec{k}\cdot\vec{s}_0 \times \vec{s}_1). \end{aligned} \tag{5}$$

Force on vertex.

$$\vec{F}(v_0) = -\frac{G(\rho_+ - \rho_-)}{24}((2z_0 + z_1 + z_2)(\vec{k}\cdot\vec{s}_0 \times \vec{s}_1)\vec{k} + (z_0^2 + z_1^2 + z_2^2 + z_0z_1 + z_0z_2 + z_1z_2)(\vec{k} \times \vec{s}_1)). \tag{6}$$

§7.3.4. Constraint integrals.

This occurs for each constraint with energy integrand that an edge is deemed to satisfy. The edge orientation is the original one. The points evaluated for Gaussian quadrature are

$$\vec{x}_i = a_i\vec{h} + (1 - a_i)\vec{t}. \tag{7}$$

Energy of edge energy.

$$E = \int_{edge} \vec{E} \cdot \vec{ds} \quad \approx \quad \sum_i w_i \vec{E}(\vec{x}_i) \cdot \vec{s}. \tag{8}$$

Force on vertex.

Component notation and the Einstein summation convention are used here, as vector notation gets confusing. Comma subscript denotes partial derivative.

$$\begin{aligned} F_j(head) &= -w_i(a_i E_{k,j}(\vec{x}_i)s_k + E_j(\vec{x}_i)), \\ F_j(tail) &= -w_i((1-a_i)E_{k,j}(\vec{x}_i)s_k - E_j(\vec{x}_i)). \end{aligned} \tag{9}$$

§7.3.5. Surface integrands.

There is a contribution from each surface energy that a facet is deemed to have. The facet orientation is the original one. The points evaluated for Gaussian quadrature are

$$\vec{x}_i = \sum_j a_{ij} \vec{v}_j. \tag{10}$$

Energy of facet.

$$E = \int\int_{facet} \vec{E} \cdot d\vec{A} \quad \approx \quad \frac{1}{2} \sum_i w_i \vec{E}(\vec{x}_i) \cdot \vec{s}_0 \times \vec{s}_1. \tag{11}$$

Force on vertex.

Component notation and the Einstein summation convention are used here, as vector notation gets confusing. Comma subscript denotes partial derivative.

$$F_j(v_m) = -\frac{1}{2} w_i (a_{im} E_{k,j}(\vec{x}_i)(\vec{s}_0 \times \vec{s}_1)_k) + (E(\vec{x}_i) \times \vec{s}_1)_j). \tag{12}$$

§7.3.6. Gap areas.

Every edge on a `CONVEX` constraint contributes here. Let $\vec{q}_t$ be the projection of $\vec{s}$ on the constraint tangent space at the tail, and $\vec{q}_h$ likewise at the head. k is the gap constant.

Energy of edge.

$$E = \frac{k}{12} (\sqrt{(s^2 - q_t^2)q_t^2} + \sqrt{(s^2 - q_h^2)q_h^2}). \tag{13}$$

Force on vertex.

This energy is not the direct derivative of the previous formula. Rather it comes directly from the geometric decrease in gap area due to vertex motion. The formula is derived for the case of a flat gap surface, which should be close enough to the truth to be useful.

$$\begin{aligned} \vec{F}(tail) &= \frac{k\sqrt{(s^2 - q_t^2)q_t^2}}{2q_t^2} \vec{q}_t, \\ \vec{F}(head) &= -\frac{k\sqrt{(s^2 - q_h^2)q_h^2}}{2q_h^2} \vec{q}_h. \end{aligned} \tag{14}$$

§7.3.7. Ideal gas compressibility.

The ideal gas mode is in effect when the keyword is listed in the first part of the datafile. Then prescribed volumes become in essence moles of gas. P_{amb} is the ambient pressure. A body has prescribed volume V_0, actual volume V, and pressure P. The temperature is assumed constant, so $PV = P_{amb}V_0$.

Energy of body.

$$\begin{aligned} E &= \int P - P_{amb} dV = \int P_{amb}V_0/V - P_{amb} dV \\ &= P_{amb}V_0 \ln(V/V_0) - P_{amb}(V - V_0) \end{aligned} \tag{15}$$

Note the energy starts at 0 for $V = V_0$.

Force on vertex.

Let $\vec{g}_m$ be the gradient of the volume body m as a function of the coordinates of the vertex. Let P_m be the pressure of body m. Then

$$\vec{F}(v) = -\sum_m (P_m - P_{amb})\vec{g}_m. \tag{16}$$

§7.3.8. Prescribed pressure.

Ambient pressure is taken to be zero, and body pressures are constant.

Energy of body.

$$E = \int P dV = PV. \tag{17}$$

Force on vertex.

Let $\vec{g}_m$ be the gradient of the volume body m as a function of the coordinates of the vertex. Let P_m be the pressure of body m. Then

$$\vec{F}(v) = -\sum_m P_m \vec{g}_m. \tag{18}$$

§7.3.9. Squared mean curvature.

The integral of squared mean curvature in the soapfilm model is calculated as follows: Each vertex v has a star of facets around it of area A_v. The force due to surface tension on the vertex is

$$F_v = -\frac{\partial A_v}{\partial v}. \tag{19}$$

Since each facet has 3 vertices, the area associated with v is $A_v/3$. Hence the average mean curvature at v is

$$h_v = \frac{1}{2}\frac{F_v}{A_v/3}, \tag{20}$$

and this vertex's contribution to the total integral is

$$E_v = h_v^2 A_v/3 = \frac{1}{4}\frac{F_v^2}{A_v/3}. \tag{21}$$

The corresponding calculation is done for the string model. E_v can be written as an exact function of the vertex cooordinates, so the gradient of E_v can be fed into the total force calculation.

Philosophical note: The squared mean curvature on a triangulated surface is technically infinite, so some kind of approximation scheme is needed. The alternative to locating curvature at vertices is to locate it on the edges, where it really is, and average it over the neighboring facets. But this has the problem that a least area triangulated surface would have nonzero squared curvature, whereas in the vertex formulation it would have zero squared curvature.

Practical note: The above definition of squared mean curvature seems in practice to be subject to instablities. One is that sharp corners grow sharper rather than smoothing out. Another is that some facets want to get very large at the expense of their neighbors. Hence a couple of alternate definitions have been added.

Effective area curvature: The area around a vertex is taken to be the magnitude of the gradient of the volume. This is less than the true area, so makes a larger curvature. This also eliminates the spike instability, since a spike has more area gradient but the same volume gradient. Letting N_v be the volume gradient at v,

$$h_v = \frac{1}{2}\frac{F_v}{||N_v||/3}, \tag{22}$$

and

$$E_v = h_v^2 A_v/3 = \frac{3}{4}\frac{F_v^2}{||N_v||^2}A_v, \tag{23}$$

The facets of the surface must be consistently oriented for this to work, since the evolver needs an "inside" and "outside" of the surface to calculate the volume gradient. This mode is toggled by the "`effective_area ON | OFF`" command. There are still possible instabilities where some facets grow at the expense of others.

Normal curvature: To alleviate the instability of effective_area curvature, the normal_curvature mode considers the area around the vertex to be the component of the volume gradient parallel to the mean curvature vector, rather than the magnitude of the volume gradient. Thus

$$h_v = \frac{1}{2}\frac{F_v||F_v||}{N_v \cdot F_v/3}, \tag{24}$$

$$E_v = \frac{3}{4}\left[\frac{F_v \cdot F_v}{N_v \cdot F_v}\right]^2 A_v. \tag{25}$$

This is still not perfect, but is a lot better. This mode is toggled by the "`normal_curvature ON | OFF`" command. If you have effective area on, then normal curvature will supersede it, but effective area will be in effect when normal curvature is toggled off.

Curvature at boundary: If the edge of the surface is a free boundary on a constraint, then the above calculation gives the proper curvature under the assumption the surface is continued by reflection across the constraint. This permits symmetric surfaces to be represented by one fundamental region. If the edge of the surface is a fixed edge or on a 1-dimensional boundary, then there is no way to calculate the curvature on a boundary vertex from knowledge of neighboring facets. For example, the rings of facets around the bases of a catenoid and a spherical cap may be identical. Therefore curvature is calculated only at interior vertices, and when the surface integral is done, area along the boundary is assigned to the nearest interior vertex.

WARNING: For some extreme shapes, effective_area and normal_curvature modes have problems detecting consistent local surface orientation. The `assume_oriented` toggle lets Evolver assume that the facets have been defined with consistent local orientation.

§7.3.10. Squared Gaussian curvature.

The integral of squared Gaussian curvature over a soapfilm model surface only applies where the star of facets around each vertex is planar. It is calculated as follows. The total Gaussian curvature at a vertex is the angle deficit around the vertex, $2\pi - \sum \theta_i$, where θ_i are the vertex angles of the facets adjacent to the vertex. The average Gaussian curvature is the total Gaussian curvature divided by one third of the area of the star. The average is then squared and integrated over one third of the star.

At boundary: Treated the same way squared mean curvature is.

§7.4. Named quantities and methods.

This section gives details on the calculations of the methods used in named quantities. For those methods where exact evaluation is impossible (due to integrals of functions or quadratic model), evaluation is done by Gaussian integration with the number of evaluation points controlled by the `integration_order` variable. In the formulas below, edge are parameterized by $0 \le u \le 1$ and facets by $0 \le u_1 \le 1, \quad 0 \le u_2 \le 1 - u_1$. S is the differential of the immersion into space, $S_{ij} = \partial x_i / \partial u_j$. J is the Jacobian, $J = (\det(S^T S))^{1/2}$. $\vec{u}_m$ are Gaussian integration points in the domain, $\vec{x}_m$ are the corresponding points in space, and w_m are the Gaussian weights. For the linear model, S and J are constant, but in the quadratic model they are functions of u: $S(\vec{u}_m)$ and $J(\vec{u}_m)$. Likewise for the facet normal $\vec{N}$, which includes the Jacobian factor.

§7.4.1. Vertex value.

Method name `vertex_scalar_integral`. A scalar function $f(\vec{x})$ is evaluated at each vertex the method applies to.

§7.4.2. Edge length.

Method name `edge_tension` or `edge_length`. This method is entirely separate from the default energy calculation for strings. For each edge, the value is the length in Euclidean coordinates. The edge density attribute, used in the default energy calculation, is not used. No metric is used.

$$\sum_m w_m J(u_m) \tag{1}$$

§7.4.3. Facet area.

Method name `facet_tension` or `facet_area`. This method is entirely separate from the default energy calculation for surfaces. For each facet, the value is the area in Euclidean coordinates. The area density attribute, used in the default energy calculation, is not used. No metric is used.

$$\sum_m w_m J(\vec{u}_m) \tag{2}$$

Method name `facet_area_u`. In the quadratic model, this gives an upper bound of area, for the paranoids who don't trust the regular `facet_area` method. It uses the fact that

$$Area = \int\int (\det(S^T S))^{1/2} du dv \le \left(\int\int \det(S^T S) du dv \right)^{1/2} \left(\int\int du dv \right)^{1/2} \tag{3}$$

The integrand on the right is a fourth degree polynomial, and so may be done exactly with 7-point Gaussian integration.

§7.4.4. Path integrals.

Method name `edge_scalar_integrand`. A scalar integrand $f(\vec{x})$ is evaluated on a edge by Gaussian quadrature:

$$\sum_m w_m f(\vec{x}_m) J(u_m). \tag{4}$$

§7.4.5. Line integrals.

Method name `edge_vector_integrand`. A vector integrand $\vec{f}(\vec{x})$ is evaluated on a edge by Gaussian quadrature:

$$\sum_m w_m \vec{f}(\vec{x}_m) \cdot \vec{S}(u_m) \tag{5}$$

§7.4.6. Scalar surface integral.

Method name `facet_scalar_integral`. A scalar integrand $f(\vec{x})$ is evaluated on a facet by Gaussian quadrature:

$$\sum_m w_m f(\vec{x}_m) J(\vec{u}_m) \tag{6}$$

§7.4.7. Vector surface integral.

Method name `facet_vector_integral`. A vector integrand $\vec{f}(\vec{x})$ is evaluated on a facet by Gaussian quadrature:

$$\sum_m w_m \vec{f}(\vec{x}_i) \cdot \vec{N}(\vec{u}_m) \tag{7}$$

For 3D only.

§7.4.8. 2-form surface integral.

Method name `facet_2form_integral`. A 2-form integrand $\omega(\vec{x}_i)$ is evaluated on a facet by Gaussian quadrature:

$$\sum_m w_m < A(\vec{u}_m), \omega(\vec{x}_m) >$$

where A is the 2-vector representing the facet, w_i are the Gaussian weights, and x_i are the evaluation points. For any dimensional ambient space.

§7.4.9. General edge integral.

Method name `edge_general_integral`. A scalar function $f(\vec{x}, \vec{t})$ of position and tangent direction is integrated over the edge by Gaussian quadrature:

$$\sum_m w_m f(\vec{x}_m, \vec{S}(u_m)) \tag{8}$$

For proper behavior, f should be homogeneous of degree 1 in $\vec{t}$.

§7.4.10. General facet integral.

Method name `facet_general_integral`. A scalar function $f(\vec{x}, \vec{t})$ of position and normal direction is integrated over the edge by Gaussian quadrature:

$$\sum_m w_m f(\vec{x}_m, \vec{N}(u_m)) \tag{9}$$

For proper behavior, f should be homogeneous of degree 1 in $\vec{N}$.

§7.4.11. String area integral.

Method name `edge_area`. This is the contribution of one edge to the area of a cell in the string model.

$$\int -y dx$$

It includes corrections for torus domains, along the same lines as explained below for `facet_volume`.

§7.4.12. Volume integral.

Method name `facet_volume`. This is the contribution of one facet to the volume of a body, using the Divergence Theorem:

$$\int \int z\vec{k} \cdot \vec{N}$$

This is done exactly, without the need for Gaussian integration. Note that this method has no automatic connection to body volumes. If you want to use this to calculate body volumes, you must define a separate quantity for each body. Further, it applies to the positive orientation of the facet, so if your body has negative facets, you must define a separate method instance with modulus -1 for those facets. A little ugly, but maybe it will be cleaned up in a later version.

In a torus domain, wrap corrections are included. Assume the fundamental region is a unit cube. Otherwise, convert to parallelpiped coordinates and multiply the resulting volume by the volume of the fundamenatal parallelpiped. For a body B,

$$V = \int\int\int_B 1 dxdydz$$

Confine the body to one fundamental region by introducing cut surfaces where the body wraps around. Let M_k be the cut on the k period face of the fundamental region. Actually, one has two copies M_k^- and M_k^+, differing only by translation by the kth period vector. By the Divergence Theorem,

$$\begin{aligned} V &= \int\int_{\partial B} z dxdy + \sum_k \int\int_{M_k^+} z dxdy - \sum_k \int\int_{M_k^-} z dxdy \\ &= \int\int_{\partial B} z dxdy + \int\int_{M_z^+} 1 dxdy. \end{aligned}$$

The surface M_z^+ is bounded by interior curves ∂M_z^+ and by cut lines C_x^+, C_x^-, C_y^+, and C_y^-. So

$$\begin{aligned} V &= \int\int_{\partial B} z dxdy + \int_{\partial M_z^+} xdy \int_{C_x^+} 1 dy \\ &= \int\int_{\partial B} z dxdy + \int_{\partial M_z^+} xdy + \sum y^+ - \sum y^- \end{aligned}$$

where the positive and negative y's are at the endpoints of C_x^+. Note that all of the quantities in the last line can be computed locally on each facet just from the edge wraps. The only ambiguity is in the values of the y's by units of 1. So the final body volumes may be off by multiples of the torus volume. Careful set-up of the problem can avoid this.

§7.4.13. Gravity.

Method name `gravity_method`

This does the same calculation as the usual gravity, but users have to incorporate the gravitational constant and body densities through the modulus, possibly using several instances of the method with different moduli to account for different densities. Let z_i be the z coordinate of v_i. The following formulas are exact for flat facets.

$$\begin{aligned} E &= \int\int_{facet} \frac{1}{2} z^2 \vec{k} \cdot d\vec{A} \\ &= \frac{1}{12}(z_0^2 + z_1^2 + z_2^2 + z_0 z_1 + z_0 z_2 + z_1 z_2) \frac{1}{2}(\vec{k} \cdot \vec{s}_0 \times \vec{s}_1). \end{aligned} \tag{10}$$

It is also exactly calculable in the quadratic model.

§7.4.14. Hooke energy.

Method name `Hooke_energy`. One would often like to require edges to have fixed length. The total length of some set of edges may be constrained by defining a fixed quantity. This is used to fix the total length of an evolving knot, for example. But to have one constraint for each edge would be impractical, since projecting to n constraints requires inverting an $n \times n$ matrix. Instead there is a Hooke's Law energy available to encourage edges to have equal length. Its form per edge is

$$E = |L - L_0|^p \tag{11}$$

where L is the edge length, L_0 is the equilibrium length, embodied as an adjustable parameter 'hooke_length', and the power p is an adjustable parameter 'hooke_power'. The default power is $p = 2$, and the default equilibrium length is the average edge length in the initial datafile. You will want to adjust this, especially if you have a total length constaint. A high modulus will decrease the hooke component of the total energy, since the restoring force is linear in displacement and the energy is quadratic (when $p = 2$). As an extra added bonus, a 'hooke_power' of 0 will give

$$E = -\log|L - L_0|.$$

§7.4.15. Local Hooke energy.

Method name `local_hooke_energy`. Energy of edges as springs with equilibrium length being average of lengths of neighbor edges. Actually, the energy is calculated per vertex,

$$E = \left(\frac{L_1 - L_2}{L_1 + L_2}\right)^2 \tag{12}$$

where L_1 and L_2 are the lengths of the edges adjacent to the vertex.

§7.4.16. Integral of mean curvature.

Method name `mean_curvature_integral`. This computes the integral of the signed scalar mean curvature over a surface. The computation is exact, in the sense that for a polyhedral surface the mean curvature is concentrated on edges and singular there, but the total mean curvature for an edge is the edge length times its dihedral angle. The contribution of one edge is

$$L \arccos\left(\frac{(\vec{a}\cdot\vec{b})(\vec{a}\cdot\vec{b}) - (\vec{a}\cdot\vec{a})(\vec{b}\cdot\vec{c})}{((\vec{a}\cdot\vec{a})(\vec{b}\cdot\vec{b}) - (\vec{a}\cdot\vec{b})^2)^{1/2}((\vec{a}\cdot\vec{a})(\vec{c}\cdot\vec{c}) - (\vec{a}\cdot\vec{c})^2)^{1/2}}\right), \tag{13}$$

where L is the edge length, $\vec{a}$ is the edge, and $\vec{b}, \vec{c}$ are the two adjacent sides from the tail of $\vec{a}$.

§7.4.17. Integral of squared mean curvature.

Method name `sq_mean_curvature`. This is the named method version of the integral of squared mean curvature discussed earlier in this chapter.

Method name `sq_mean_curvature`. This is the named method version of the integral of squared mean curvature discussed earlier in this chapter, with the effective area discretization of mean curvature.

Method name `sq_mean_curvature`. This is the named method version of the integral of squared mean curvature discussed earlier in this chapter, with the normal curvature discretization of mean curvature.

§7.4.18. Integral of Gaussian curvature.

Method name `Gauss_curvature_integral`. This computes the total Gaussian curvature of a surface with boundary. The Gaussian curvature of a polyhedral surface may be defined at an interior vertex as the angle deficit of the adjacent angles. But as is well-known, total Gaussian curvature can be computed simply in terms of the boundary vertices, which is what is done here. The total Gaussian curvature is implemented as the total geodesic curvature around the boundary of the surface. The contribution of a boundary vertex is

$$\left(\sum_i \theta_i\right) - \pi. \tag{14}$$

The total over all boundary vertices is exactly equal to the total angle deficit of all interior vertices plus $2\pi\chi$, where χ is the Euler characteristic of the surface.

§7.4.19. Average crossing number.

Method name `average_crossings`. Between pairs of edges, energy is inverse cube power of distance between midpoints of edges, times triple product of edge vectors and distance vector:

$$E = 1/d^3 * (e1, e2, d). \tag{15}$$

§7.4.20. Knot energies.

One way of smoothing a knotted curve is to put "electric charge" on it and let it seek its minimum energy position. To prevent the curve from crossing itself and unknotting, the potential energy should have a high barrier (preferably infinite) to curve crossing. This is often done by using a inverse power law potential with a higher power than the standard inverse first power law of electrostatics. A length constraint on the curve is generally necessary to prevent the charges from repelling each other off to infinity.

The Evolver implements several discrete approximations of these potentials. All use the quantity-method feature described in the next section. That is, each type of energy is a method, and these methods can be attached to user-named quantities. The power in the power law is an adjustable parameter 'knot_power'. It may be changed interactively with the '`A`' command. The modulus is the multiple of the method added to the quantity. A modulus of 0 inactivates the method. The value of the quantity can be seen with the 'A' command under the name of the quantity.

One of the general problems with discretization is that edges don't know when they are crossing each other. Edges can cross without either their endpoints or midpoints getting close, especially if said edges get long. To keep edge lengths close to equal, there is also an energy called 'hooke energy' described in the Model chapter. Another energy of interest is total squared curvature, which is elastic bending energy. However, it does not provide any barrier to crossing.

All the knot energies proper correspond to double integrals in the continuous limit, so are double sums. Hence the computation time is quadratic in the number of vertices. Hooke energy and square curvature are linear time.

Generally, the continuous integrals are divergent, and in the literature have various regularization terms subtracted off. However, the Evolver discretizations do not have such regularization. The logic is that the discrete versions are finite, and the discete regularization terms are practically constant, so there is no sense in wasting time computing them.

A sample datafile incorporating some of these is `knotty.fe`.

These discrete knot energies are classified below by whether they are computed over all pairs of vertices, edges, or facets.

I. Vertex pair energies. The total energy is the sum over all pairs of vertices v_1, v_2:

$$E = \frac{1}{2} \sum_{v_1 \neq v_2} E_{v_1 v_2}.$$

Ia. Conducting wire. There is a unit charge on each vertex, and edge lengths are not fixed.

$$E_{v_1 v_2} = \frac{1}{|v_1 - v_2|^p}$$

This is approximating the continuous integral

$$E = \int \int \left(\frac{1}{|x(s) - x(t)|^p} - \frac{1}{d(s,t)^p} \right) \rho(s)\rho(t)\, ds\, dt$$

where s, t are arclength parameters, $d(s,t)$ is the shortest arc distance between points, and ρ is charge density. The second term in this integral is a normalization term to prevent infinite energy. It is not present in the discrete version, since the discrete energy is finite and the normalization term is approximately constant. Note that refining doubles the total charge, so refining should be accompanied by reducing the modulus by a factor of 4.

Note that the discrete energy can apply to any dimension surface in any dimension ambient space since it does not use the regularization. It can be used as a dust energy for sphere packing (high knot_power for a hard core potential) or an energy for knotted 2-spheres in 4-space.

The default power is 2.

Datafile line:

```
quantity knot_energy ENERGY modulus 1 global_method knot_energy
```

Ib. Insulating wire.

$$E_{v_1 v_2} = \frac{L_1 L_2}{|v_1 - v_2|^p}$$

where L_1 is the average length of the two edges adjacent to v_1 and L_2 is the average length of the two edges adjacent to v_2. This is approximating the continuous integral

$$E = \int\int \left(\frac{1}{|x(s) - x(t)|^p} - \frac{1}{d(s,t)^p} \right) ds\, dt$$

where s, t are arclength parameters, $d(s,t)$ is the shortest arc distance between points. This corresponds to a uniform charge density, which is why it is an 'insulating wire'. The second term in the integral is a normalization term, which is not included in the discrete version since it is approximately constant. However, a discrete normalization term can be calculated as a separate quantity.

This energy assumes that each vertex has exactly 2 edges attached to it, so it is not suitable for surfaces.

Datafile line:

```
quantity knot_energy ENERGY modulus 1 global_method edge_knot_energy
```

The 'edge' in the method name refers to the edge-weighting of the vertex charges. The default power is 2.

Datafile line for normalization term:

```
quantity norm_term INFO_ONLY modulus 1 global_method uniform_knot_energy_normalizer
```

Ic. Insulating surface.

$$E_{v_1 v_2} = \frac{A_1 A_2}{|v_1 - v_2|^p}$$

where A_1 is the area of the facets adjacent to v_1 and A_2 is the area of the facets adjacent to v_2. This corresponds to a uniform charge density, which is why it is an 'insulating surface'.

Datafile line:

```
quantity knot_energy ENERGY modulus 1 global_method facet_knot_energy
```

The 'facet' in the method name refers to the edge-weighting of the vertex charges. The default power is 4.

II. Edge pair energies. The total energy is the sum over all pairs of edges e_1, e_2 with endpoints $v_{11}, v_{12}, v_{21}, v_{22}$:

$$E = \frac{1}{2} \sum_{e_1 \neq e_2} E_{e_1 e_2}$$

IIa. Box energy. This energy is due to Gregory Buck. It has the form

$$E_{e_1 e_2} = \frac{L_1 L_2}{(d_1 + d_2 + d_3 + d_4 - 2(L_1 + L_2))^p}.$$

Here L_1, L_2 are the edge lengths and d_1, d_2, d_3, d_4 are the distances between endpoints on different edges. This provides an infinite barrier to crossing in the discrete case in a simple form involving only the edge endpoints. The denominator becomes zero for parallel coincident lines or for perpendicular lines on opposite

edges of a tetrahedron. This energy should not be turned on until the curve is refined enough that the denominator is always positive. The default power is 2.

Datafile line:

```
quantity buck_energy ENERGY modulus 1 global_method buck_knot_energy
```

IIb. Normal projection energy. This energy is also due to Gregory Buck. It tries to eliminate the need for a normalization term by projecting the energy to the normal to the curve. Its form is

$$E_{e_1e_2} = \frac{L_1 L_2 \cos^p \theta}{|x_1 - x_2|^p}$$

where x_1, x_2 are the midpoints of the edges and θ is the angle between the normal plane of edge e_1 and the vector $x_1 - x_2$. The default power is 2.

Datafile line:

```
quantity proj_energy ENERGY modulus 1 global_method proj_knot_energy
```

IIc. Conformal circle energy. This energy is due to Peter Doyle, who says it is equivalent in the continuous case to the insulating wire with power 2. Its form is

$$E_{e_1e_2} = \frac{L_1 L_2 (1 - \cos\alpha)^2}{|x_1 - x_2|^2},$$

where x_1, x_2 are the midpoints of the edges and α is the angle between edge 1 and the circle through x_1 tangent to edge 2 at x_2. Only power 2 is implemented.

Datafile line:

```
quantity circle_energy ENERGY modulus 1 global_method circle_knot_energY
```

III. Facet pair energies. These energies are sums over all pairs of facets.

IIIa. Conformal sphere energy. This is the 2D surface version of the conformal circle energy. Its form is

$$E_{f_1f_2} = \frac{A_1 A_2 (1 - \cos\alpha)}{|x_1 - x_2|^4},$$

where A_1, A_2 are the facet areas, x_1, x_2 are the barycenters of the facets, and α is the angle between f_1 and the sphere through x_1 tangent to $f2$ at x_2.

There is a nice expression for the general dimensional version of this energy:

$$4E_{f_1f_2} = \frac{A_1 A_2}{r^4} - \frac{1}{r^6} det \begin{bmatrix} r \cdot r & r \cdot s_1 & r \cdot s_2 \\ t_1 \cdot r & t_1 \cdot s_1 & t_1 \cdot s_2 \\ t_2 \cdot r & t_2 \cdot s_1 & t_2 \cdot s_2 \end{bmatrix}$$

where $r = |x_1 - x_2|$ and s_1, s_2, t_1, t_2 are the sides of the two facets.

Datafile line:

```
quantity sphere_energy ENERGY modulus 1 global_method sphere_knot_energy
```

§7.5. Volumes.

A body can get volume from a surface integral over its boundary facets and from content integrals of boundary facets edges on constraints. Also important are the gradients of body volumes at vertices. There are two choices built-in surface integrals: default and `SYMMETRIC_CONTENT`.

§7.5.1. Default facet integral.

A facet oriented with normal outward from a body makes a contribution to its volume of

$$V = \int\int_{facet} z\vec{k} \cdot d\vec{A} = \frac{1}{6}(z_0 + z_1 + z_2)\vec{k} \cdot \vec{s}_0 \times \vec{s}_1. \tag{1}$$

The gradient of the volume of the body as a function of the vertex v_0 coordinates is

$$\vec{g} = \frac{1}{6}\left((\vec{k} \cdot \vec{s}_0 \times \vec{s}_1)\vec{k} + (z_0 + z_1 + z_2)\vec{k} \times \vec{s}_1\right). \tag{2}$$

§7.5.2. Symmetric content facet integral.

A facet oriented with normal outward from a body makes a contribution to its volume of

$$V = \frac{1}{3}\int\int_{facet} (x\vec{i} + y\vec{j} + z\vec{k}) \cdot d\vec{A} = \frac{1}{6}\vec{v}_0 \cdot \vec{v}_1 \times \vec{v}_2. \tag{3}$$

This can be seen most easily by looking at the facet as the base of a tetrahedron with its fourth vertex at the origin. The integral over the three new faces is zero, so the integral over the original facet must be the volume of the tetrahedron.

The gradient of the volume of the body as a function of the vertex v_0 coordinates is

$$\vec{g} = \frac{1}{6}\vec{v}_1 \times \vec{v}_2. \tag{4}$$

§7.5.3. Edge content integrals.

Let body b have facet f with outward normal. Suppose f has edge s deemed to have content integrand $\vec{U}$. Then b gets volume

$$V = \int_e \vec{U} \cdot d\vec{s} \quad \approx \quad \sum_i w_i \vec{U}(\vec{x}_i)\vec{s}. \tag{5}$$

The volume gradients for the body are (summation convention again)

$$\begin{aligned} g_j(head) &= w_i(a_i U_{k,j}(\vec{x}_i)s_k + U_j(\vec{x}_i)), \\ g_j(tail) &= w_i((1 - a_i)U_{k,j}(\vec{x}_i)s_k - U_j(\vec{x}_i)). \end{aligned} \tag{6}$$

§7.5.4. Volume in torus domain.

The wrapping of the edges across the faces of the unit cell makes the calculation of volumes a bit tricky. Suppose body b has vertices v_k. Ideally, we would like to adjust the vertices by multiples of the unit cell basis vectors to get a body whose volume we could find with regular Euclidean methods. Unfortunately, all we know are the edge wraps, i.e. the differences in the adjustments to endpoints of edges. But this turns out to be enough, if we are a little careful with the initial volumes in the datafile.

Let $\vec{A}_k$ be the vertex adjustment for vertex k, and $\vec{T}_j$ be the wrap vector (difference in endpoint adjustments) for facet-edge j. Let m index facets. Then

$$\begin{aligned} V &= \frac{1}{6}\sum_{facets\ m} (\vec{v}_{m0} + \vec{A}_{m0}) \cdot (\vec{v}_{m1} + \vec{A}_{m1}) \times (\vec{v}_{m2} + \vec{A}_{m2}) \\ &= \frac{1}{6}(S_1 + S_2 + S_3 + S_4) \end{aligned} \tag{7}$$

where

$$\begin{aligned} S_1 &= \sum_{facets\ m} \vec{v}_{m0} \cdot \vec{v}_{m1} \times \vec{v}_{m2}, \\ S_2 &= \sum_{facet-edges\ j} \vec{v}_{j0} \cdot \vec{v}_{j1} \times \vec{A}_{j2}, \\ S_3 &= \sum_{facet-verts\ k} \vec{v}_k \cdot \vec{A}_{k1} \times \vec{A}_{k2}, \\ S_4 &= \sum_{facets\ m} \vec{A}_{m0} \cdot \vec{A}_{m1} \times \vec{A}_{m2}. \end{aligned} \tag{8}$$

The first of these sums is straightforward. The second sum can be regrouped, pairing the two oppositely oriented facet-edges j and $-j$ for each edge together:

$$\begin{aligned} S_2 &= \sum_{edges\ j} \vec{v}_{j0} \cdot \vec{v}_{j1} \times \vec{A}_{j2} + \vec{v}_{-j0} \cdot \vec{v}_{-j1} \times \vec{A}_{-j2} \\ &= \sum_{edges\ j} \vec{v}_{j0} \cdot \vec{v}_{j1} \times (\vec{A}_{j2} - \vec{A}_{-j2}) \\ &= \frac{1}{2} \sum_{edges\ j} \vec{v}_{j0} \cdot \vec{v}_{j1} \times (\vec{T}_{-j2} + \vec{T}_{j1} - \vec{T}_{j2} - \vec{T}_{-j1}) \end{aligned} \tag{9}$$

which can be regrouped into a sum over facet-edges, which can be done facet by facet:

$$S_2 = \sum_{facet-edges\ j} \vec{v}_{j0} \cdot \vec{v}_{j1} \times (\vec{T}_{j1} - \vec{T}_{j2}).$$

The third sum we group terms with a common vertex together, with the inner facet sum over facets around vertex k:

$$\begin{aligned} S_3 &= \sum_{vertices\ k} \left(\vec{v}_k \cdot \sum_{facetsi} \vec{A}_{i1} \times \vec{A}_{i2} \right) \\ &= \sum_{vertices\ k} \left(\vec{v}_k \cdot \sum_{facetsi} (\vec{A}_{i1} - \vec{A}_{k0}) \times (\vec{A}_{i2} - \vec{A}_k) \right) \\ &= \sum_{vertices\ k} \left(\vec{v}_k \cdot \sum_{facets\ i} \vec{T}_{i0} \times -\vec{T}_{i2} \right) \\ &= \sum_{facet-vertices\ k} \vec{v}_k \cdot \vec{T}_{k2} \times \vec{T}_{k0}, \end{aligned} \tag{10}$$

which again can be done facet by facet.

The fourth sum is a constant, and so only needs to be figured once. Also, it is a multiple of the unit cell volume. Therefore, if we assume the volume in the datafile is accurate to within $\frac{1}{12}V_c$, we can calculate the other sums and figure out what the fourth should be.

The body volume gradient at v_0 will be

$$\vec{g} = \frac{1}{6} \left(\sum_{facets\ m\ on\ v} \vec{v}_{m1} \times \vec{v}_{m2} + \frac{1}{2}\vec{v}_{m1} \times (\vec{T}_{m1} - \vec{T}_{m2}) + \vec{T}_{m0} \times \vec{T}_{m2} \right). \tag{11}$$

§7.6. Quantity integrands.

Both facets and edges may contribute to quantities. If the quantities are `FIXED`, then the quantity gradients as functions of the vvertices must be computed. The facet orientation is the original one. The points evaluated for Gaussian quadrature are

$$\vec{x}_i = \sum_j a_{ij}\vec{v}_j. \tag{1}$$

§7.6.1. Quantity of a facet.

Let $\vec{Q}$ be the facet integrand for the quantity in question. Then the contribution of a facet is

$$Q = \int\int_{facet} \vec{Q}\cdot d\vec{A} \quad \approx \quad \frac{1}{2}\sum_i w_i \vec{E}(\vec{x}_i)\cdot \vec{s}_0 \times \vec{s}_1. \tag{2}$$

The gradient at vertex v_m follows from this. Component notation and the Einstein summation convention are used here, as vector notation gets confusing. Comma subscript denotes partial derivative.

$$\nabla Q_j(v_m) = \frac{1}{2} w_i (a_{im} Q_{k,j}(\vec{x}_i)(\vec{s}_0 \times \vec{s}_1)_k) + (Q(\vec{x}_i)\times \vec{s}_1)_j). \tag{3}$$

§7.6.2. Quantity of an edge.

Let $\vec{q}$ be a quantity integrand applicable to an edge. Then the edge's contribution is

$$Q = \int_{edge} \vec{q}\cdot d\vec{s} \quad \approx \quad \sum_i w_i \vec{E}(\vec{x}_i)\cdot \vec{s}. \tag{4}$$

The gradients at the endpoints follow from this. Component notation and the Einstein summation convention are used here, as vector notation gets confusing. Comma subscript denotes partial derivative.

$$\begin{aligned} \nabla Q_j(head) &= w_i(a_i q_{k,j}(\vec{x}_i)s_k + q_j(\vec{x}_i)), \\ \nabla Q_j(tail) &= w_i((1-a_i) q_{k,j}(\vec{x}_i)s_k - q_j(\vec{x}_i)). \end{aligned} \tag{5}$$

§7.7. Constraint projection.

Suppose vertex v has constraints that are the zero sets of functions $f_1, \ldots, f_n$.

§7.7.1. Projection of vertex to constraints.

The solution will be by Newton's method. Several steps may be necessary to get within the tolerance desired of the constraint. Inequality constraints are included if and only if the inequality is violated.

For one step, we seek a displacement $\delta\vec{v}$ that is a linear combination of the constraint gradients and will cancel the difference of the vertex from the constraints:

$$\delta\vec{v} = \sum_i c_i \nabla f_i \qquad \text{such that} \qquad \delta\vec{v}\cdot\nabla f_j = -f_j(v) \qquad \text{for each } j. \tag{1}$$

Thus

$$\sum_i c_i \nabla f_i \cdot \nabla f_j = -f_j(v) \qquad \text{for each j.} \tag{2}$$

This is a linear system that can be solved for the c_i and thus $\delta\vec{v}$.

§7.7.2. Projection of vector onto constraint tangent space.

We want to project a vector $\vec{F}$ (say, a force vector) onto the intersection of all the tangent planes of the constraints at a vertex. We project $\vec{F}$ by subtracting a linear combination of constraint gradients:

$$\vec{F}_{proj} = \vec{F} - \sum_i c_i \nabla f_i \qquad \text{such that} \qquad \vec{F}_{proj} \cdot \nabla f_j = 0 \qquad \text{for each } j. \tag{3}$$

This leads to the system of linear equations for the c_i:

$$\sum_i c_i \nabla f_i \cdot \nabla f_j = \vec{F} \cdot \nabla f_j. \tag{4}$$

§7.8. Volume and quantity constraints.

This section explains how volume and quantity constraints are enforced. Henceforth in this section, everything referring to the volume of a body can also refer to the value of a quantity constraint. There are two parts to this enforcement on each iteration: a volume restoring motion that corrects for any volume deviations, and a projection of the vertex motions to the subspace of volume-preserving motions. Let g_{bv} be the gradient of the volume of body b as a function of the position of vertex v. We will also use B as a body index. If the bodies fill a torus, then one body is omitted to prevent singular systems of equations.

§7.8.1. Volume restoring motion.

Let the current excess volume of body b be δb (which may be negative, of course). We want a volume restoring motion $\vec{R}_v$

$$\vec{R}_v = \sum_B c_B \vec{g}_{Bv} \qquad \text{and} \qquad \sum_v \vec{R}_v \cdot \vec{g}_{bv} = -\delta b \qquad \text{for each } b \tag{1}$$

which leads to the linear system for the c_B:

$$\sum_B c_B \sum_v \vec{g}_{Bv} \cdot \vec{g}_{bv} = -\delta b \qquad \text{for each } b. \tag{2}$$

§7.8.2. Motion projection in gradient mode.

The motion in this mode is the scale factor times the force on a vertex. Let $\vec{F}_v$ be the total force at v. We want a projected force $\vec{F}_{vproj}$ such that

$$\vec{F}_{vproj} = \vec{F}_v - \sum_B a_B \vec{g}_{Bv} \qquad \text{and} \qquad \sum_v \vec{F}_{vproj} \cdot \vec{g}_{bv} = 0 \qquad \text{for each } b \tag{3}$$

which leads to the linear system for a_B

$$\sum_B a_B \sum_v \vec{g}_{Bv} \cdot \vec{g}_{bv} = \sum_v \vec{F}_v \cdot \vec{g}_{bv} \qquad \text{for each } b. \tag{4}$$

The coefficients a_B are the pressures in the bodies when the surface is in equilibrium.

§7.8.3. Force projection in mean curvature mode.

The motion in this mode is the scale factor times the force on a vertex divided by the area of the vertex. Let $\vec{F}_v$ be the total force at v and A_v its area. We want a projected force $\vec{F}_{vproj}$ such that

$$\vec{F}_{vproj} = \vec{F}_v - \sum_B a_B \vec{g}_{Bv} \qquad \text{and} \qquad \sum_v \vec{F}_{vproj} \cdot \vec{g}_{bv}/A_v = 0 \qquad \text{for each } b \tag{5}$$

which leads to the linear system for a_b

$$\sum_b a_b \sum_v \vec{g}_{Bv} \cdot \vec{g}_{bv}/A_v = \sum_v \vec{F}_v \cdot \vec{g}_{bv}/A_v \qquad \text{for each } b. \tag{6}$$

The coefficients a_b are the pressures in the bodies even when the surface is not in equilibrium. At equilibrium, the pressures calculated with or without the mean curvature option are equal.

§7.9. Iteration.

This section explains what happens during each iteration (g command). Δt is the current scale factor.

§7.9.1. Fixed scale motion.

1. Do diffusion if called for. For each facet f, let A_f be the area of the facet. Let m_1 and P_1 be the prescribed volume (mass) of a body on one side of f, and m_2 and P_2 those of the body on the other side. Let κ be the diffusion constant. If there is no body on one side, the pressure there is zero or ambient pressure for the ideal gas model. The mass transfers are:

$$dm_1 = -\kappa(P_1 - P_2)A_f\Delta t \qquad \text{and} \qquad dm_2 = -\kappa(P_2 - P_1)A_f\Delta t. \tag{1}$$

2. All the forces on vertices are calculated, as detailed in the **Energies and Forces** section above. If the mean curvature option is active, each force is divided by the vertex's associated area.
3. All forces at `FIXED` vertices are set to zero. Forces on constrained vertices are projected to the constraint tangent spaces. Forces on vertices on boundaries are converted to forces in boundary parameter spaces.
4. The volume restoring motion is calculated, and the forces are projected according to body volume constraints.
5. Jiggle if jiggling is toggled on.
6. Move vertices by volume restoring motion and current scale times force.
7. Enforce constraints on vertices. Do up to 10 projection steps until vertex is within tolerance of constraints.
8. Recalculate volumes, pressures, areas, and energy.

§7.9.2. Optimizing scale motion.

The idea is to find three scale factors that bracket the energy minimum and then use quadratic interpolation to estimate the optimum scale factor. The first four steps are the same as for fixed scale motion.

5. Save current coordinates.
6. Move vertices by volume restoring motion and current scale times force and enforce constraints. Recalculate energy.
7. Restore coordinates, double scale factor, move surface, and recalculate energy. If this energy is higher, keep cutting scale factor in half until energy increases again. If it is lower, keep doubling scale factor until energy increases.
8. Eventually get three scale factors s_1, s_2, s_3 with energies e_1, e_2, e_3 bracketing a minimum. The scale factors are successive doublings: $s_2 = 2s_1$, $s_3 = 2s_2$. Do quadratic interpolation to find approximate optimum:
$$s_{opt} = 0.75s_2(4e_1 - 5e_2 + e_3)/(2e_1 - 3e_2 + e_3). \tag{2}$$
9. Jiggle if jiggling is on.
10. Move vertices by volume restoring motion and optimum scale times force.
11. Project to constraints.
12. Recalculate volumes, pressures, areas, and energy.

§7.9.3. Conjugate gradient mode.

The `U` command toggles conjugate gradient mode. The conjugate gradient method does not follow the gradient downhill, but makes an adjustment using the past history of the minimization. It usually results in much faster convergence. At iteration step i, let S_i be the surface, E_i its energy, $\vec{F}_i(v)$ the force at vertex v, and $\vec{h}_i(v)$ the "history vector" of v. Then

$$\vec{h}_i(v) = \vec{F}_i(v) + \gamma \vec{h}_{i-1} \tag{3}$$

where

$$\gamma = \frac{\sum_v \vec{F}_i(v) \cdot \vec{F}_i(v)}{\sum_v \vec{F}_{i-1}(v) \cdot \vec{F}_{i-1}(v)}. \tag{4}$$

Then a one-dimensional minimization is performed in the direction of $\vec{h}_i$, as described in steps 6,7,8 above. It is important that all volumes and constraints be enforced during the one-dimensional minimization, or else the method can go crazy. The history vector is reset after every surface modification, such as refinement or equiangulation.

The above formula is the Fletcher-Reeves version of conjugate gradient. The `ribiere` command toggles the Polak-Ribiere version, which differs only in having

$$\gamma = \frac{\sum_v (\vec{F}_i(v) - \vec{F}_{i-1}(v)) \cdot \vec{F}_i(v)}{\sum_v \vec{F}_{i-1}(v) \cdot \vec{F}_{i-1}(v)}. \tag{5}$$

Polak-Ribiere seems to recover much better from stalling. If you have to stop and restart conjugate gradient often, try "ribiere".

Conjugate gradient blowups: Sometimes conjugate gradient wants to move so far and fast that it loses contact with volume constraints. Before, Evolver did only one or two Newton method projections back to volume constraints each iteration; now it will do up to 10. Ordinary iteration does only one projection still, but you can get the extra projections with the "post_project" toggle. If convergence fails after 10 iterations, you will get a warning message, repeated iterations will stop, and the variable "iteration_counter" will be negative.

§7.10. Hessian iteration.

The "`hessian`" command constructs a quadratic approximation of the energy and solves for the minimum (or whatever the critical point happens to be). See the Hessian section of the Model chapter for remarks on its use. The independent variables used are the displacements of vertex coordinates. For vertices on level set constraints, the coordinates are replaced by set of variables equal in number to the degrees of freedom. Fixed vertices are not represented. Let X denote the vector of independent variables. Let B denote the energy gradient, and let H be the Hessian matrix of second partial derivatives. Hence the energy change is

$$E = \frac{1}{2} X^T H X + B^T X. \tag{1}$$

Global constraints like volumes and fixed named quantities are actually scalar functions of X with fixed target values. Indexed these constraints by i, and let C_i be the gradient and Q_i the Hessian of constraint i. Let F_i be the current value and F_{i0} be the target value of constraint i. Then we have the constraint conditions on X

$$\frac{1}{2} X^T Q_i X + C_i^T X = F_{i0} - F_i. \tag{2}$$

Let Γ_i be the Lagrange multiplier for constraint i. The Lagrange multiplier is shown in the "pressure" column of the 'v' command. At a critical point we have

$$X^T H + B^T = \sum_i \Gamma_i (X^T Q_i + C_i^T).$$

So we want to solve the system

$$\begin{aligned}(H - \sum_i \Gamma_i Q_i)X - \sum_i \Gamma_i C_i &= -B \\ \frac{1}{2}X^T Q_i X + C_i^T X &= F_{i0} - F_i.\end{aligned} \tag{3}$$

We do this by Newton's method. This means solve the system

$$\begin{pmatrix} H - \sum_i \Gamma_i Q_i & C \\ C^T & 0 \end{pmatrix} \begin{pmatrix} X \\ d\Gamma \end{pmatrix} = \begin{pmatrix} C\Gamma - B \\ F_0 - F \end{pmatrix} \tag{4}$$

where C is the matrix with columns C_i, Γ is the vector of Γ_i, $d\Gamma$ is the change in Γ, and F_0, F are the vectors of constraint values. For convenience, denote $A = H - \sum_i \Gamma_i Q_i$. The solution of this is

$$\begin{aligned} d\Gamma &= (C^T A^{-1} C)^{-1}(C^T A^{-1}(C\Gamma - B) - (F_0 - F)) \\ X &= A^{-1}(C\Gamma - B) - A^{-1} C d\Gamma. \end{aligned} \tag{5}$$

I choose to solve for A^{-1} first for two reasons: (1) A is sparse, while C is not, and (2) finding A^{-1} and $C^T A^{-1} C$ can tell us about the stability of the critical point. Actually, A^{-1} is never found as such. Instead, a Cholesky factorization $A = U^T D U$ is found and used to solve $AY = C$ for $Y = A^{-1}C$ and so forth. Here U is an upper triangular matrix, and D is a diagonal matrix. The factoring is done with routines from the Yale Sparse Matrix Package, modified a bit since the matrix A may not be positive definite. Negative entries in D are allowed, and the total number of them is the *index* of A. Zero entries are also allowed, since many surfaces have degenerate minimums of energy (due to translational invariance, for example). When a zero diagonal entry appears, a warning message is printed for the user. If the zero does represent a true degeneracy, then the whole row and column of that zero should also be zero at that stage of the factoring. The warning message prints the maximum size of other entries in the row to assure the user that all is fine. The factoring routine then puts a 1 on the diagonal to insure an invertible D. This has no effect on any of the solutions. The cutoff value for considering a diagonal element to be zero is given by the variable "`hessian_epsilon`" which may be set by the user with an ordinary assignment command. Its default value is 1e-8.

The index of the Hessian constrained to the constraints is given by the relation

$$index(H_{constrained}) = index(A) - index(C^T A^{-1} C). \tag{6}$$

If this index is positive, then a warning message is printed. Once the Hessian method has converged, this provides a test for being a local minimum. At a saddle point, the constrained index is positive and it is possible to find a downhill direction. However, this feature has not yet been implemented.

Some notes for people rash enough to write hessian routines for their own named quantity methods: Hessians can only be written for methods that are evaluated independently on elements. Two vertices are allocated a Hessian entry only if they are joined by an edge. See q_edge_tension_hessian() in hessian.c for an example. For debugging, the command "`hessian_menu`" brings up a little menu. You can turn debugging on, in which case you get a whole lot of information dumped to the screen as the algorithm proceeds. Don't do that with more that 3 or 4 unfixed vertices. The sequence of menu options for one iteration is 1,2,3,4 (stepsize 1). For checking Hessian matrix values, there is a "`hessian_diff`" command at the main prompt which will toggle on the calculation of the Hessian matrix by finite differences.

§7.11. Equiangulation.

Triangulations work best when the facets are close to equilateral (that is, equiangular). Given a set of vertices, how do you make them into a triangulation that has triangles as nearly as possible equilateral? In the plane, the answer is the Delauney triangulation, in which the circumcircle of each triangle contains no other vertex. See [S]. It is almost always unique. It can be constructed by local operations beginning with

any triangulation. Consider any edge as the diagonal of the quadrilateral formed by its adjacent triangles. If the angles of the two vertices off of the edge add to more than π, then the circumcircle criterion is violated, and the diagonal should be switched to form a replacement pair of facets.

Suppose now we have a triangulation of a curved surface in space. For any edge with two adjacent facets, we switch the edge to the other diagonal of the skew quadrilateral if the sum of the angles at the off vertices is more than π. Let a be the length of the common edge, b and c the lengths of the other sides of one triangle, and d and e the lengths of the other sides of the other triangle. Let θ_1 and θ_2 be the off angles. Then by the law of cosines

$$a^2 = b^2 + c^2 - 2bc\cos\theta_1, \qquad a^2 = d^2 + e^2 - 2de\cos\theta_2. \tag{1}$$

The condition $\theta_1 + \theta_2 > \pi$ is equivalent to $\cos\theta_1 + \cos\theta_2 < 0$. So we switch if

$$\frac{b^2 + c^2 - a^2}{bc} + \frac{d^2 + e^2 - a^2}{de} < 0. \tag{2}$$

This is guaranteed to terminate since a switch reduces the radii of the circumcircles and there are a finite number of triangulations on a finite number of vertices. When using the `u` command to equiangulate, you should use it several times until no changes happen. If you do get a genuine infinite loop, report it as a bug.

§7.12. Dihedral angle.

The dihedral angle attribute of an edge is defined in the soap film model for any edge with two adjacent facets. (Other edges return a dihedral angle of 0.) Letting the common edge be $\vec{a}$, and letting $\vec{b}$ and $\vec{c}$ be the other edge vectors from the base of $\vec{a}$, we use the inner product of 2-vectors:

$$\cos\theta = \frac{<\vec{a}\wedge\vec{b}, \vec{c}\wedge\vec{a}>}{||\vec{a}\wedge\vec{b}||||\vec{c}\wedge\vec{a}||} = \frac{\begin{vmatrix} \vec{a}\cdot\vec{c} & \vec{a}\cdot\vec{a} \\ \vec{b}\cdot\vec{c} & \vec{b}\cdot\vec{a} \end{vmatrix}}{\begin{vmatrix} \vec{a}\cdot\vec{a} & \vec{a}\cdot\vec{b} \\ \vec{b}\cdot\vec{a} & \vec{b}\cdot\vec{b} \end{vmatrix}^{1/2} \begin{vmatrix} \vec{c}\cdot\vec{c} & \vec{c}\cdot\vec{a} \\ \vec{a}\cdot\vec{c} & \vec{a}\cdot\vec{a} \end{vmatrix}^{1/2}}.$$

If the denominator is 0 or $\cos\theta > 1$, then $\theta = 0$. If $\cos\theta < -1$, then $\theta = \pi$. Note that this definition works in any ambient dimension.

§7.13. Area normalization.

By default, the gradients of quantities like energy and volume are calculated simply as the gradient of the quantity as a function of vertex position. This gives the force on a vertex, for example. But sometimes it is desirable to have force per area instead, for example in directly estimating mean curvature. The mean curvature vectorfield $\vec{h}$ of a surface is defined to be the gradient of the area of the surface in the sense that if the surface is deformed with an instantaneous velocity $\vec{u}$ then the rate of change of surface area is

$$\frac{dA}{dt} = \int\int_{surface} \vec{u}\cdot\vec{h}\, dA. \tag{1}$$

According to the triangulation formulation, with $\vec{F}_v$ being the force on vertex v, the rate of change is

$$\frac{dA}{dt} = \sum_v u(v)\cdot -\vec{F}_v. \tag{2}$$

Hence as approximation to $\vec{h}$, we take

$$\vec{h} = -\vec{F}_v/dA_v \tag{3}$$

and take the area dA_v associated with a vertex to be one-third of the total areas of the facets surrounding the vertex. Since each facet has three vertices, this allocates all area. Command "`a`" can be used to toggle area normalization.

§7.14. Hidden surfaces.

This section describes the algorithm used by the painter graphics interface to hide hidden surfaces.

1. Each facet has the viewing transformation applied to it.

2. Each facet has its maximum and minimum in each dimension recorded (bounding box).

3. Facets are sorted on their maximum depth (rear of bounding box).

4. List is traversed in depth order, back to front. If a facet's bounding box does not overlap any others', it is drawn. If it does overlap, a linear program tries to find some point where one facet is directly in front of the other. If there is such a point and the order there is backward, the facets are switched on the list. The traversal then restarts there. If it makes over 10 switches without drawing a facet, it gives up and draws the current facet anyway.

§7.15. Extrapolation.

The final energy value at refinement step n is saved as E_n. Assuming the difference from minimum energy follows a power law of unknown power, three successive values are used to extrapolate to the minimum energy E_0:

$$\begin{aligned} E_n &= E_0 + ac^b, \\ E_{n-1} &= E_0 + a(2c)^b, \\ E_{n-2} &= E_0 + a(4c)^b. \end{aligned} \tag{1}$$

Hence

$$E_0 = E_n - \frac{(E_n - E_{n-1})^2}{E_n - 2E_{n-1} + E_{n-2}}. \tag{2}$$

§7.16. Curvature test.

This only applies to the quadratic model.

§7.17. Annealing (jiggling).

This happens at each command `j`, or at each iteration if the jiggling option (command `J`)is activated. Each coordinate of each non-`FIXED` vertex is moved by

$$\delta x = gTL \tag{1}$$

where g is a random value from the standard Gaussian distribution (calculated from the sum of five random values from the uniform distribution on [0,1]), T is the current temperature, and L is a characteristic length that starts as the diameter of the surface and is cut in half at each refinement.

§7.18. Long wavelength perturbations (long jiggling).

This is command `longj`. An amplitude $\vec{A}$ and a wavelength $\vec{L}$ are chosen at random from a unit sphere by picking random vectors in a cube of side 2 centered at the origin and rejecting attempts that are outside the unit sphere. $\vec{A}$ and $\vec{L}$ are then multiplied by the size of the surface to give them the proper scale. The wavelength is inverted to a wavevector $\vec{w}$. The amplitude is multiplied by the temperature. A random phase ψ is picked. Then each vertex $\vec{v}$ is moved by $\vec{A}\sin(\vec{v}\cdot\vec{w}+\psi)$.

§7.19. Homothety.

This scales the total volume of all bodies to 1 by multiplying each coordinate by

$$\left(\sum_{bodies} V_{body}\right)^{-1/3}. \tag{1}$$

In the string model, the factor is

$$\left(\sum_{bodies} V_{body} \right)^{-1/2} . \tag{2}$$

§7.20. Popping non-minimal edges.

All facets are assumed to have equal tension. This looks for edges with more that three facets that are not fixed or on boundaries or constraints. When found, such an edge is split with a new facet in between. The two closest old facets are attached to the new edge. This is repeated until only three facets are on the original edge. Each split is propagated along the multiple junction line as far as possible. If it is impossible to propagate beyond either endpoint, the edge is subdivided to provide a vertex which can be split.

§7.21. Popping non-minimal vertex cones.

String model.

Any vertex with four or more edges is tested. The edges into the vertex are separated into two contiguous groups. The endpoints of one group are transfered to a new vertex, and a short edge is introduced between the new and old vertex. All groupings are tested to see which one pulls apart the most. This method works when the edges have non-equal tensions.

Soapfilm model.

All facets are assumed to have equal tension. This assumes that all edges have at most three facets adjoining, so edge popping should be done first. Here the facet and edge structure around each vertex is analyzed to find which have the wrong topology. The analysis is done by looking at the network formed by the intersection of the facets and edges containing the vertex with the surface of a small sphere around the vertex. The numbers of sides of the cells of the network are counted. A simple plane vertex has two cells of one side each. A triple edge vertex has three cells of two sides each. A tetrahedral point has four cells with three sides each. Any other configuration is popped.

The popping itself is done by replacing the vertex with a hollow formed by truncating each cell-cone except the cell with the largest solid angle. In case the network is disconnected, the solid angles of all the cells will add up to over 4π. Then the vertex is duplicated and the different components are assigned to different vertices. This lets necks shrink to zero thickness and pull apart.

§7.22. Refining.

First, all edges are subdivided by inserting a midpoint. Hence all facet temporarily have six sides. For edges on constraints, the midpoints get the same set of constraints, and are projected to them. For edges on boundaries, the parameters of the midpoint are calculated by projecting the vector from the edge tail to the midpoint back into the parameter space and adding that to the tail parameters. This avoids averaging parameters of endpoints, which gives bad results when done with boundaries that wrap around themselves, such as circles. The new edges and the midpoint inherits their attributes from the edge.

Second, each facet is subdivided into four facets by connecting the new midpoints into a central facet. The new edges inherit their attributes from the facet.

§7.23. Refining in the simplex model.

The goal is to divide an n-dimensional simplex into 2^n equal volume simplices, although these cannot be congruent for $n > 2$. First, each 1-dimensional edge is subdivided by inserting a new vertex. This vertex inherits the intersection of the attributes of the edge endpoints (i.e. fixity and constraints). Second, the $n+1$ tips of the old simplex are lopped off, leaving a "core". This core is recursively subdivided. An edge midpoint is picked as a base point. Faces of the core not adjacent to the base point are either simplices (where tips got lopped off) or cores of one lower dimension. The core is given a conical subdivision from the

base point to simplicial subdivisions of the nonadjacent faces. The base point is always picked to have the lowest id number, in order that refinements of adjacent simplices are consistent.

§7.24. Removing tiny edges.

The edge list is scanned, looking for edges shorter than the cutoff length. It is NOT removed if any of the following are true:

1. Both endpoints are `FIXED`.
2. The edge is `FIXED`.
3. The boundary and constraint attributes of the endpoints and the edge are not identical. For an edge that passes these tests, one endpoint is eliminated. If one endpoint is `FIXED`, that is the one kept. All the facets around the edge are eliminated (collapsing their other two edges to one), and the edge itself is eliminated.

§7.25. Weeding small triangles.

This is meant to help eliminate narrow triangles that tiny edge removal can't because they don't have short edges. This procedure finds the shortest edge of a triangle and eliminates it by the same process as the regular tiny edge removal. If that fails, it tries the other edges.

§7.26. Vertex averaging.

For each vertex, this computes a new position as the area-weighted average of the centroids of the facets adjoining the vertex. `FIXED` vertices or vertices on boundaries are not moved, nor are vertices on triple or higher edges. If vertex v is connected by edges to vertices $v_1, \ldots, v_n$, then the new position is calculated as

$$\vec{v}_{avg} = \frac{\sum_{facets} area \cdot \vec{x}_{centroid}}{\sum_{facets} area}. \tag{1}$$

The volume one one side of all the facets around the vertex calculated as a cone from the vertex is

$$V = \sum_{facets\ f} \vec{v} \cdot \vec{N}_f \tag{2}$$

where $\vec{N}_f$ is the facet normal representing its area. The total normal $\vec{N}$ is

$$\vec{N} = \sum_{facets\ f} \vec{N}_f. \tag{3}$$

To preserve volume, we subtract a multiple λ of the total normal to the average position:

$$(\vec{v}_{avg} - \lambda\vec{N}) \cdot \vec{N} = \vec{v} \cdot \vec{N}, \tag{4}$$

so

$$\lambda = \frac{\vec{v}_{avg} \cdot \vec{N} - \vec{v} \cdot \vec{N}}{\vec{N} \cdot \vec{N}}. \tag{5}$$

Then the new vertex position is

$$\vec{v}_{new} = (\vec{v}_{avg} - \lambda\vec{N}). \tag{6}$$

Constrained vertices are then projected to their constraints.

The "`rawv`" command will do vertex averaging as just described, but without conserving volumes. The "`rawestv`" command will also ignore all restrictions about like constraints and triple edges, but it will not move fixed points or points on boundaries. Points on constraints will be projected back to them.

§7.27. Zooming in on vertex.

First, all vertices beyond the cutoff distance from the given vertex are deleted. Then all edges and facets containing any deleted vertices are deleted. Any remaining edge that had a facet deleted from it is made `FIXED`.

§7.28. Mobility and approximate curvature.

This section derives the resistance and mobility matrices used in approximate curvature. The derivation is done in the full generality of vertex constraints, boundaries, volume and quantity constraints, and effective area.

First, we must define the inner product or metric on global vectors, which is the resistance matrix. Let $\vec{W}$ be a global vectorfield, that is, $\vec{W}$ has a component vector $\vec{W}_v$ at each vertex v. At each vertex v, let $\vec{U}_{v,i}$ be a basis for the degrees of freedom of motion of vertex v due to level set constraints or boundaries. Consider one edge e in the string model. Let P be the projection operator onto the normal of e if effective area is in effect, and let P be the identity map if not. Then the inner product of two vector fields is

$$\begin{aligned} <\vec{W},\vec{V}> &= L\int_0^1 P((1-t)\vec{W}_a + t\vec{W}_b)\cdot P((1-t)\vec{V}_a + t\vec{V}_b)dt \\ &= L(\frac{1}{3}P\vec{W}_a\cdot P\vec{V}_a + \frac{1}{6}P\vec{W}_a\cdot P\vec{V}_b + \frac{1}{6}P\vec{W}_b\cdot P\vec{V}_a + \frac{1}{3}P\vec{W}_b\cdot P\vec{V}_b). \end{aligned} \tag{1}$$

If the vectors are expressed in terms of the bases U_v with coefficient column matrices W_v and V_v, then

$$\begin{aligned} <\vec{W},\vec{V}> = L(&\frac{1}{3}\sum_{i,j} W_{ai}\vec{U}_{a,i}\cdot P\vec{U}_{a,j}V_{aj} + \frac{1}{6}\sum_{i,j} W_{ai}\vec{U}_{a,i}\cdot P\vec{U}_{b,j}V_{bj} \\ &+\frac{1}{6}\sum_{i,j} W_{bi}\vec{U}_{b,i}\cdot P\vec{U}_{a,j}V_{aj} + \frac{1}{3}\sum_{i,j} W_{bi}\vec{U}_{b,i}\cdot P\vec{U}_{b,j}V_{bj}). \end{aligned} \tag{2}$$

So the components of the resistance matrix S are

$$\begin{aligned} S_{ai,aj} &= \frac{L}{3}\vec{U}_{a,i}\cdot P\vec{U}_{a,j}, \\ S_{ai,bj} &= \frac{L}{6}\vec{U}_{a,i}\cdot P\vec{U}_{b,j}. \end{aligned} \tag{3}$$

In the soapfilm model, for a facet of area A,

$$\begin{aligned} S_{ai,aj} &= \frac{A}{6}\vec{U}_{a,i}\cdot P\vec{U}_{a,j}, \\ S_{ai,bj} &= \frac{A}{12}\vec{U}_{a,i}\cdot P\vec{U}_{b,j}. \end{aligned} \tag{4}$$

The total matrix S is formed by adding the contributions from all edges. Note that S has a block on its diagonal for each vertex and a block for each pair of edges joined by an edge. Hence it is reasonably sparse. S is a symmetric positive semidefinite matrix, positive definite if effective area is not in effect.

Now suppose we have a form H to convert to a vector. H is represented as a covector H_v at each vertex v. The mobility matrix $M = (M_{bj,ai})$ is the inverse of S. The first step is to find the coefficients in the dual basis of U by contracting:

$$h_{a,i} = <\vec{U}_{a,i}, H_v> . \tag{5}$$

The U basis components of the vector dual to H are then

$$c_{b,j} = M_{bj,ai}h_{a,i}. \tag{6}$$

Actually, the components are found by solving the sparse system

$$S_{ai,bj}c_{a,i} = h_{a,i}. \tag{7}$$

The foregoing ignores volume and quantity constraints. Suppose B_k are gradient forms for the volume and quantity constraints. We need to project the motion in such a way as to guarantee that when the velocity is zero, the energy gradient is a linear combination of constraint gradients.

$$proj(H) = H - \lambda_k B_k. \tag{8}$$

The projected velocity is

$$V = M(H - \lambda_k B_k). \tag{9}$$

The condition for motion tangent to the constraints is

$$B_m M(H - \lambda_k B_k) = 0 \qquad \text{for each } m. \tag{10}$$

Therefore

$$B_m M B_k \lambda_k = B_m M H, \tag{11}$$

and so

$$\lambda_k = (B_m M B_k)^{-1} B_m M H. \tag{12}$$

Chapter 8. Helpful hints and notes.

When writing a new datafile, use the `d` command to check that it is being read as you think it should be.

Run at low resolution before refining. Having many triangles not only takes a long time to calculate, but motion can propagate only one triangle per iteration. Also run the linear model first, and use the quadratic model for final polishing (if at all).

Conjugate gradient should be used only when regular motion has settled down. Conjugate gradient assumes a quadratic energy function, and may get confused when it's not. Conjugate gradient may need to be toggled off and on to make it forget its history.

Judging convergence is tough. If iterations run at a more or less constant scale factor and energy isn't changing much, and running in conjugate gradient mode for a long time doesn't change much, then you're probably in good shape. The `hessian` command may help.

Watch out for edges shrinking to zero length and triangles to zero area; they can stall progress. If the optimal scale factor heads toward 0, try equianglation (`u`), vertex averaging (`V`), small triangle weeding (`w`), or the tiny edge removing (`t`). Always precede and follow `w` with `t`.

Facets entirely on constraints tend not to move, and moving free boundaries tend to overrun such facets, leading to problems. Use constraint integrals rather than facets on constraints where possible.

If your edges on curved constraints try to shortcut the curve, try declaring the constraint `CONVEX` to add a penalty for shortcutting. Another approach is to add an energy integrand term to the constraint that is zero on the constraint and positive off it. Integrands are evaluted at several points in the interior of an edge, not the endpoints, so this gives an energy penalty for going away from the edge. Hopefully, it will not change the nature of your solution.

Use constraints for two-dimensional free boundaries, and use parametric boundaries for wire frames.

Use the `d` command to save your surface at critical points.

Run checks (`C`) after modifying a surface just to make sure everything worked right.

Chapter 9. Bugs.

There are no known outright bugs at present. but they undoubtably exist. When you run across one, I would like to hear about it. Bug reports should be submitted by email to `brakke@geom.umn.edu`. Please include the Evolver version number, a description of the problem, the initial data file, and the sequence of commands necessary to reproduce the problem.

There are a few shortcomings, however:

Not all features are implemented in all models.

Vertex and edge popping is not elegant or complete.

Zero length edges and zero area triangles stall things.

Surfaces can intersect each other without knowing it.

Convergence to a minimum energy can be difficult to judge.

Chapter 10. Version history.

Version 1.0 August 4, 1989

First public version.

Version 1.01 August 22, 1989

Various bug fixes.

Constraint integral specification changed to have just components, not density.

Facet-edge specification made obsolete (but still legal).

Vertex motion adjustment for quadratic model.

Zoom factor changed from 2 to 1.2.

Initial datafile reading revamped to use lex and yacc. Has simple macros. Comments must be delimited. Expressions now in algebraic form, not RPN.

Version 1.10 October 18, 1989

More bug fixes.

Graphics driver for HP98731 contributed by Eric Haines.

Datafile reading:

Equations permitted as constraints.

Backslash line splicing.

Constant folding in expressions.

Version 1.11 May 18, 1990

More bug fixes.

x,y,z accepted as synonyms for x1,x2,x3

Version 1.12 May 25, 1990

Datafile coordinates may be given as expressions.

Constraints revamped. Number of constraints per element raised to sizeof(int). One-sided constraints may be applied selectively. `GLOBAL` constraints automatically apply to all vertices (they count in number limit).

Version 1.2 June 17, 1990

Comments removed from input stream before lex analyzer. So comments in macros safe now.

Scale factor upper bound adjustable when toggling with `m` command.

Adjustable constants implemented. Syntax in data file: `PARAMETER` name = constant-expression These are treated as constants in expressions, but can be changed with the `A` command. Useful for dynamically changing contact angles and other stuff in constraint expressions.

Symmetric content evaluation added for linear model. Volumes evaluated as surface integral of $(x\vec{i}+y\vec{j}+z\vec{k})/3$ rather than of $z\vec{k}$. Use keyword `SYMMETRIC CONTENT` in datafile. Permits more accurate evaluation of lunes.

Return value of sprintf not used, as this varies among systems.

Arbitrary surface energy integrands added. Vector field integrated over designated facets. Syntax

surface energy *n*
e1: *expression*
e2: *expression*
e3: *expression*

Designate facet by following facet definition with "energy *n*", in same manner as giving constraints. Linear model only. This useful for changing direction of gravity, by putting in Divergence Theorem equivlent surface integrand for gravitational potential energy and putting adjustable constant in for direction.

The 'q' or 'x' exit command gives you a chance to load another datafile, continue with the current configuration, or exit.

You can change the initial upper limit on the 'scale' factor by putting a line in the data file:

SCALE LIMIT *value*

value must be a number (no expression).

The 'V' command (for Vertex averaging) will replace each unconstrained vertex by the average of its neighboring vertices (connected by edges). Good for uncramping skinny triangles sometimes.

TENSION allowed as synonym for DENSITY in setting facet surface tension.

Binary save/reload disabled, since it is out of date and a binary file turns out twice as large as the ascii dump file.

Version 1.21 June 30, 1990

Shared memory interface added for MinneView (which is a public domain 3D graphics viewer for Irises written by the Geometry Project at the Minnesota Supercomputer Institute.)

Histogram added for ridge notcher (option 'n').

Ported to NeXT (no screen graphics, but PostScript output files can be displayed).

Automatic energy recalculation added after all options that change energy.

Version 1.3 July 30, 1990

Reptition counts before letters in graphics commands.

Clockwise (c) and counterclockwise (C) rotations added to graphics.

Printout during quadratic search for optimum scale suppressed.

'i' command added for information. 'v' reports just volumes.

Extrapolation command 'e' fixed.

Constant expressions permitted wherever real value needed.

'F' command to log commands to file.

-ffilename command line option to read commands from file. Take commands from stdin afterwards.

Dump file real values printed to 15 decimal places so accuracy not lost.

Adjustable accuracy on edge integrals via `INTEGRAL_ORDER` keyword in datafile for setting order of Gaussian quadrature.

Datafile now allows specification of constraint tolerance with `CONSTRAINT_TOLERANCE`.

All two-word keywords made into single words by connecting the words with '_'.

Parsing of datafile continues after errors.

'b' command permits editing body volumes.

'v' command prints 'none' for prescribed volume of those bodies with no prescribed volume.

Manual in TEXformat with PostScript figures.

`CONVEX` gap energies and forces fixed up. $k = 1$ best approximation to area.

Vertex popping fixed to handle disjoint components of tangent cones. Also not to screw up its data structures after a modification.

Version 1.31

Added long-wavelength random jiggle (command `jj`).

Fixed simultaneous Minneview to handle torus display options.

Simultaneous MinneView can be stopped and restarted.

Fixed bug in Gaussian quadrature of content integrals.

Fixed equiangulation to work on arbitrarily small triangles.

Histograms adjusted to current length and area order of magnitude.

Zero area triangle test area cutoff adjusted to scale of surface.

Vertex averaging improved to preserve volumes.

Small edge removal bug fixed. In collapsing a facet, will preferentially keep an edge on a constraint.

`VOLCONST` adjustment to body volumes added to datafile.

"Quantities" added. A quantity is a sum of vector integrals over facets and edges. Can be simply tallied for informational purposes, or can be used as mathematical constraints with fixed values. Good for center of mass, moment of inertia, magnetic flux, etc.

Conjugate gradient energy minimization added. Use the `U` command to toggle between gradient descent and this.

Version 1.4 posted August 20, 1990

Version 1.41 September 22, 1990

Bug fixes on vertex popping and element list management.

Long jiggle command jj lets user put in own numbers, use random numbers, or use previous numbers.

Version 1.42

Bug fixes:

segment violation on error message at end of data file.

STRING model not graphing third dimension

On SOAPFILM model, edges without facets are displayed. Useful for showing wire boundaries beyond surface. Such edges will generate warnings when datafile is read, however.

Version 1.5 May 15, 1991

dimensional surfaces can live in N-dimensional space. See `SPACE_DIMENSION`.

Simplex model added to represent k-dimensional surfaces in N-dimensional space.

Embryonic query language added. Does `list` and `show`. Also set and unset attributes.

Background metric on space added for string model only.

Commands can be read from a file with `read "`*filename*`"`

Version 1.6 June 20, 1991

Riemannian metric extended to all dimensional surfaces.

Refine, delete added to query language. List query has same format output as datafile dump.

Quotient spaces added.

Piping output added to commands and queries.

Version 1.63 July 21, 1991

SET FACET COLOR query added. Colors include CLEAR. Also SET FACET TRANSPARENCY for Iris and like.

Squared mean curvature added as possible energy.

Queries can refer to elements by original number of parent in datafile.

Adjustable constants can take values from a file according to ID number of element applied to.

Version 1.64 August 2, 1991

Revised notch command (n) to subdivide adjacent facets instead of edge itself. Supposed to be followed with equiangulation.

Put in K command to subdivide longest edges of skinny triangles (as judged by their smallest angle).

Added VALENCE attribute for edges for queries. Is the number of facets on an edge.

Version 1.65 August 20, 1991

Added minimization by using Newton's method on Hessian matrix of energy. Only for no-constraint area minimization with no other energies. Command "`hessian`".

NeXT version given graphical interface.

User-defined functions of coordinates added. See `userfunc.c`.

Version 1.76 March 20, 1992

Autopopping and autochopping in string model for automatic evolution.

Phase-dependent grain boundary energies.

Approximate polyhedral curvature.

Stability test for approximate curvature.

Squared Gaussian curvature as part of energy only, not force.

"system" command to execute shell commands.

"check_increase" to guard against blowup during interation.

"effective_area" to count only resistance to motion normal to surface.

Runge-Kutta iteration.

Version 1.80 July 25, 1992

Command and query language much extended.

`geomview` interface added.

Fixed area added as a constraint.

Multiple viewing transforms can be specified in the datafile so one fundamental region of a symmetric surface can be displayed as the whole surface.

Commands can be included at the end of the datafile, introduced by the keyword READ.

Version 1.83 September 9, 1992

Some alternate definitions of squared curvature added. Invoked by "`effective_area ON | OFF`" or "`normal_curvature ON | OFF`".

Version 1.84 September 10, 1992

Shaded colors added to xgraph and cheygraph.

Version 1.85 September 29, 1992

Restriction of motion to surface normal added. Toggle "tt normal_motion".

Squared mean curvature, Gaussian curvature, and squared Gaussian curvature extended to surfaces with boundary.

Datafile element attribute "`bare`" added for vertices and edges in soapfilm model so they won't generate erroneous warnings.

Force calculation added for squared Gaussian curvature, so it can be used in the energy.

All prompts that require real value responses now accept arbitrary expressions.

Version 1.86 October 19, 1992

User-defined mobility added, both scalar and tensor forms.

Default squared curvature works for 2-surfaces in R^n.

Version 1.87 October 27, 1992

"`close_show`" command added to close show window (the native graphics window, not geomview).

Graphics command checks string for illegal characters before doing any transformations.

Dihedral angles now work for 2-surfaces in any dimension.

Permanent variable assignments may be made with "`::=`" instead of "`:=`". Such assignments will not be forgotten when a new surface is begun.

Conditional expressions of C form added: expr ? expr : expr. Useful for patching constraints together.

Version 1.88 December 16, 1992

"SET BACKGROUND color" command added for native graphics.

View transformation generators and expressions added.

Exact bounding box calculated for PostScript files.

Version 1.88a January 6, 1993

Default constraint_tolerance lowered from 1e-5 to 1e-12.

Fixed bug in volume constraint calculation introduced in 1.88.

Version 1.89 February 18, 1993

Postscript draws fixed and boundary edges in interior of surface. All internal graphics should be consistent in the special edges they draw (bare edges, triple edges, etc.).

Viewing matrix can be read from datafile and will be dumped. Keyword VIEW_MATRIX

Mod operator '%' added, and functions floor(), ceil().

'rebody' command added to recalculate connected bodies after neck pinching and any other body disruption.

If squared mean curvature part of energy, then squared mean curvature at a vertex is available as a query attribute as "sqcurve".

These quantities can now be used in command expressions: vertex_count, edge_count, facet_count, body_count, total_energy, total_area, total_length, scale.

Dump file records defined procedures in 'read' section at end.

Knot energies added, both conducting and insulating wire.

'dissolve' command added to erase elements and leave gaps in surface, unlike delete command, which closes gaps. Can only dissolve elements not neede by higher dimensional elements.

Command repeat numbers have been restricted to just three types of commands: 1. single letter commands that don't have optional arguments (l,t,j,m,n,w have optional arguments) 2. command list in braces 3. user-defined procedure names This is to prevent disasters like list vertex 1293 which before would produce 1293 full lists of all vertices.

"dump" without argument will dump to default file name, which is datafile name with .dmp extension.

SIGTERM is caught and causes dump to default dump file and exit. Useful for interrupting scripts running in the background with kill -TERM. Likewise for SIGHUP.

Version 1.90 April 2, 1993

Conjugate gradient ON/OFF state saved in dump file. Note that conjugate gradient history vector is not saved.

Notching and "dihedral" attribute apply to vertices in the string model.

FOREACH iterator added. Syntax: FOREACH element [name] [WHERE expr] DO command

LOAD command added. Syntax: LOAD "filename". Useful for starting new surfaces, especially in scripts.

PRINTF command added for formatted printing. Syntax: PRINTF "format string",expr,expr,... expr is floating point, so use %f or %g formats.

String variables have been added. Can be used where quoted strings needed. Can be assigned to. SPRINTF is version of PRINTF giving string output.

A view transformation matrix in the datafile may be preceded by "color n" to give that transform a color (overrides any facet color).

In queries, element attribute "oid" added, which returns a signed version of id.

Many knot energies added. Also a "hooke energy" that keeps edges near a uniform length.

PostScript output optionally includes color.

Version 1.91 May 31, 1993

Two sides of facets can have different colors. '`COLOR`' applies to both sides, '`FRONTCOLOR`' and '`BACKCOLOR`' to different sides.

Attributes of individual named elements can be set inside loops, i.e. foreach facet ff do set ff color red

Every time a command changed a global variable, the surface was being recalculated. This slowed down scripts immensely. So now the only variables that cause recalculation are 1) adjustable parameters defined in the datafile 2) quantity moduli and parameters

History commands now echoed.

Surface area can be minimized by minimizing Dirichlet integral, according to scheme of Polthier and Pinkall. Command '`dirichlet`'.

To reduce need for explicit line-splicing on long commands, the parser now keeps track of depth of brace and parenthesis nesting, and will call for more input if a line ends inside nest. So if you want to type a multiline command, start with '' and end with '' many lines later. Also does auto line-splicing if certain tokens are last token in line (such as '+').

'`facet_knot_energy_fix`' method added.

Command assignment fixed to assign only one command. so "`ggg := g; g`" will be the same as "`{ggg := g} ; g`" and not "`ggg := {g;g}` ".

Queries can run through edges and facets adjacent to a vertex, and facets of a body, as in "`list vertices vv where max(vv.facet,color==red) > 0`"

Improved NeXT terminal interface. `-u` option for no graphics, `-t` for terminal and graphics.

view_4d command to toggle sending full 4D coordinates to geomview. Default is OFF.

Version 1.92 July 31, 1993

SGI parallelism enabled for named quantity calculations.

method-instance scheme introduced.

Torus periods can be specified with expressions using adjustable parameters.

Verbs (list,refine,delete,dissolve) may apply to single elements: foreach edge ee do refine ee

FIX and UNFIX may be used as verbs:

```
fix vertices where on_constraint 1
```

Toggle command names may now be used as boolean values in expressions in commands. Also new boolean read-only variables: torus, torus_filled, symmetry_group, simplex_representation. New numeric read-only variables: space_dimension, surface_dimension, integration_order.

Mac version repeated commands interruptable with control-'.'.

Macintosh and Dos versions pipe to a file instead of a command:

```
Enter command:  list vertices | "filename"
```

For a torus domain, the torus periods may be specified using expressions with parameters, so the fundamental cell may be changed interactively. Do a `recalc` after changing such a parameter to update the torus periods.

`gv_binary` toggle for binary/ascii data to geomview. Default ON for binary, which is faster. Ascii mode useful for debugging.

Version 1.93 December 13, 1993

"history" command added to print command history. Single-letter commands now included in history for convenience. But history does not record responses to prompts commands may issue.

command repeat counts can now be expressions

More internal variables for counters on command events: equi_count, delete_count, notch_count, dissolve_count, pop_count, where_count.

Quantities for scalar and vector integrands over edges and facets added.

Quantity names may now be used as element attributes. Value of total quantity must be referred to as "total quantityname".

DOS version has improved graphics. Recognizes higher resolution and more colors.

Can apply named quantities to elements with SET command.

Undocumented user_attr.

Version 1.94 January 24, 1994

New named quantity methods: vertex_scalar_integrand, facet_2form_integral.

Hessians for named quantity methods: edge_length, facet_area, vertex_scalar_integral, edge_scalar_integral, edge_vector_integral, facet_scalar_integral, facet_vector_integral, facet_2form_integral, gravity_method.

Added edge wrap as readable attribute.

Added coordinate attributes for edges and facets. Interpreted as edge vector components and facet normal components.

Commands are added to history list after being successfully parsed, rather than after successful execution.

Unfound files are treated as errors rather than prompting for new name, except for datafiles.

New arithmetic operators: mod (synonym for %), imod, idiv. New arithmetic function: atan2(y,x).

Show conditions for edges and facets are saved in read section of datafile.

Total energy is in a comment at the top of a dump file.

PostScript output in case of string model in 3D has option for doing bordered crossings.

'`w`' is synonym for coordinate `x4`.

Version 1.95 June 24, 1994

Named quantity methods for squared curvature: sq_mean_curvature, eff_area_sq_mean_curvature, normal_sq_mean_curvature. All work with h_zero.

New quantities edge_general_integral, facet_volume, facet_torus_volume, facet_general, stress_integral, edge_area, edge_torus_area. Also quadratic model versions of basic quantities. Also hessian.

Quadratic midpt for edges included in dump. Optional in datafile.

'midv' attribute for edges in quadratic model.

'iteration_counter' variable for printing current repetition number.

New math functions: tanh, asinh, acosh, atanh.

Extra attributes, indexable. Can have non-dumping extra attributes.

'quietgo' toggle to suppress output of just the 'g' command.

'ribiere' toggle for conjugate gradient. Does not initiate CG. Also extra projections to constraints in conjugate gradient or post-project mode, with iteration_counter set to -1 if nonconvergence in 10 projections.

'assume_oriented' toggle for square mean curvature.

Label option added to PostScript output.

Short-circuit evaluation of AND and OR.

Delete facet more aggressive; tries to eliminate all edges of facet in increasing length order until it succeeds.

Chapter 11. Bibliography.

[A] F. Almgren, "Minimal surface forms," *The Mathematical Intelligencer*, vol.4, no. 4 (1982), 164–172.

[AT] F. Almgren and J. Taylor, "The geometry of soap films and soap bubbles," *Scientific American*, July 1976, 82–93.

[B1] K. Brakke, *The motion of a surface by its mean curvature*, Princeton University Press, Princeton, NJ (1977).

[B2] K. Brakke, "The surface evolver," *Experimental Mathematics*, vol. 1, no. 2 (1992), 141–165.

[B3] K. A. Brakke, "Minimal surfaces, corners, and wires," *Journal of Geometric Analysis* **2** (1992) 11-36.

[B4] K. A. Brakke, "The opaque cube problem video," *Computing Optimal Geometries*, J. E. Taylor, ed., American Mathematical Society, Providence RI, 1991.

[B5] K. A. Brakke, "Grain growth with the Surface Evolver," *Video Proceedings of the Workshop on Computational Crystal Growing*, J. E. Taylor, ed., American Mathematical Society, Providence RI, 1992.

[C] M. Callahan, P. Concus and R. Finn, "Energy minimizing capillary surfaces for exotic containers," *Computing Optimal Geometries*, American Mathematical Society, Providence RI, 1991.

[DL] D. Dobkin and M. Laszlo, "Primitives for the manipulation of three-dimensional subdivisions," technical report CS-TR-089-87, Department of Computer Science, Princeton University, Princeton, New Jersey. (April 1987).

[FHW] M. Freedman, X. He, and Z. Wang, "On the energy of knots and unknots," *Annals of Mathematics* **139** no. 1 (1994) 1–50.

[HKS] L. Hsu, R. Kusner, and J. Sullivan, "Minimizing the squared mean curvature integral for surfaces in space forms," *Experimental Mathematics* **1** (1991) 191–208.

[MH] H. Mittelmann, "Symmetric capillary surfaces in a cube", *Math. Comp. Simulation* **35** (1993) 139-152.

[MF1] F. Morgan, "Harnack-type mass bounds and Bernstein theorems for area-minimizing flat chains modulo ν," *Comm. Part. Diff. Eq.* **11** (1986) 1257–1283.

[MT] F. Morgan and J. E. Taylor, "Destabilization of the tetrahedral point junction by positive triple junction line energy," *Scripta Metall. Mater.* **25** (1991) 1907-1910.

[P] W. Press, B. Flannery, S. Teukolsky, and W. Vetterling, *Numerical Recipes in C*, Cambridge University Press, New York, 1988.

[RSB] L. M. Racz, J. Szekely, and K. A. Brakke, "A General Statement of the Problem and Description of a Proposed Method of Calculation for Some Meniscus Problems in Materials Processing", ISIJ International, Vol. 33, No. 2, (February 1993).

[S] R. Sibson, "Locally equiangular triangulations", *Comput. J.* **21** (1978) 243-245.

[T1] J. E. Taylor, "The structure of singularities in soap-bubble-like and soap-film-like minimal surfaces," *Ann. Math.* **103** (1976), 489-539.

[T2] J. E. Taylor, "Constructing crystalline minimal surfaces," *Seminar on Minimal Submanifolds*, E. Bombieri, ed., *Annals of Math. Studies* **105** (1983), 271–288.

[T3] J. E. Taylor, "Constructions and conjectures in crystalline nondifferentiable geometry," *Proceedings of the Conference in Differential Geometry*, Rio de Janiero, 1988, Pittman Publishing Ltd.

Chapter 11. Bibliography.

[Te] J. Tegart, "Three-dimensional fluid interfaces in cylindrical containers," AIAA paper AIAA-91-2174, 27th Joint Propulsion Conference, Sacramento, CA, June 1991.

[TW] W. Thompson (Lord Kelvin), "On the division of space with minimum possible error," *Acta Math.* **11**(1887), 121–134.

[U] A. Underwood, "Constructing barriers to minimal surfaces from polyhedral data," Ph.D. thesis, Princeton, 1993.

[WP] D. Weaire and R. Phelan, "A counter-example to Kelvin's conjecture on minimal surfaces", *Phil. Mag. Letters* Feb. 1994.

Chapter 12. Index.

+ graphics command 84
- graphics command 84
0 command 70
? graphics command 84
acquisition 2
adjustable constants 9,23,28,45,50
aggregate expressions 74
ambient pressure 38,41,46,53,70
annealing 53,111
approximate curvature 44,80
APPROXIMATE_CURVATURE 53
APPROX_CURV 80
area normalization 42,44,67,69,110
AREAWEED 78
AREA_FIXED 80
AREA_FIXED 58
AREA_NORMALIZATION 80
AREA_NORMALIZATION 53
area 72
assignment 76
ASSUME_ORIENTED 80
attributes 8,75
AUTOCHOP 80
autochop 59
autochop command 80
AUTOPOP 80
autopopping 60
autopop command 80
AUTORECALC 81
average_crossings 99
AVG 74
A command 9,11,24,29,46,67
a command 67
BACKCOLOR 62,72
background 76
blowup 71,111
BODIES 7,62
bodies 6,34
body surface 34
body_count 73
boundaries 11,33,34,35,36,37,45,58,84
BOUNDARY_CURVATURE 81
BOUNDARY 61,62
boundary 33
bounding box 84
bugs 1,117
B graphics command 84
b command 46,68
b graphics command 84
case 7,47
catenoid 11
CHECK_INCREASE 81
check_increase 81
clear 75
CLIPPED 81
clipped cell 13,36,84
CLOSE_SHOW 78
color map 4
COLORMAP 81
colors 49,70
COLOR 62,72
color 33,34,75
command line options 64
command line 64
command repitition 65
commands, graphics 83
commands 6,65,72
comments 7,47
compiling 4
compressibility 38
compressible 53
conformal metric 59
CONF_EDGE_SQCURV 81
conjugate gradient 42,71,82,108
CONJ_GRAD 81
CONNECTED 81
connected bodies 13,36,84
conserved quantities 34
consistency checks 68
constant expressions 49
constraint energy integral 92
constraint energy integrand 38
constraint energy 9,36
constraint volume integral 103
constraint volume integrand 22,27,37,41
CONSTRAINTS 61
constraints 33,34,35,36,37,42,45,57,84
CONSTRAINT_TOLERANCE 42,58
constraint_tolerance 73
CONSTRAINT 57,61,62
constraint 105
contact angle 9,21,26,38
CONTENT 57
content 41
CONVEX 22,27,36,38,57,58,93
coordinates 33
crystalline integrands 37
crystalline integrand 31,52,92
cube 6
curvature test 72,111
C command 68
C graphics command 84
c command 68
c graphics command 84
datafile 6,47,64

DEBUG 81
DEFINE 78
delete_count 73
DELETE 75
DENSITY 37,63
density 34,72
DETURCK 81
DIFFUSION 81
DIFFUSION 42,53
diffusion 42,46,68
dihedral angle 72,110
dimension 4,34,35
DIRICHLET 78
displayable 34,45,62
display 68,71
dissolve_count 73
DISSOLVE 75
DOS 2
DO 66
DUMP 78
dump 68
D command 68
d command 68
d graphics command 8,83
edge popping 70,112
edge wraparound 35
EDGES 7,61
edges 6,33,61
EDGEWEED 79
edge_area. 97
edge_count 73
edge_general_integral 97
edge_length 96
edge_scalar_integral 96
edge_tension 96
edge_vector_integral 96
effective area 44
EFFECTIVE_AREA 81
EFFECTIVE_AREA 53
eff_area_sq_mean_curvature 99
ENERGY 57,62
energy 6,37,42,91
environment 3
equiangulation 71,109
equi_count 73
errors 64
ESTIMATE 81
EVOLVERPATH 3,64
exit 9,71,84
expressions 49,72
extra attributes 33,61,75,78
extra attribute 73
extrapolation 68,111
e command 68
FACES 7,62
faces 62
facet-edges 91
facet-edge 6
facets 6,33
facet_2form_integral 97
facet_area_u 96
facet_area 96
FACET_COLORS 81
facet_count 73
facet_general_integral 97
facet_scalar_integral 97
facet_tension 96
facet_vector_integral 97
facet_volume. 97
file formats 87
files 3
FIXED 33,37,45,56,57,59,61,62,76
force 91
FOREACH 75
FRONTCOLOR 62,72
ftp 2
F command 68
f command 68
gap constant 69
gap energy 36,46,93
gaps 36,38,42,46,53,69,93
GAP_CONSTANT 53
Gaussian curvature 39,83
Gaussian quadrature 37,58
Gauss_curvature_integral 99
GENERIC 4
geomview 2,8,70,82,88
GLOBAL 36,52,56,57
graphics commands 8,83
graphics interfaces 3,4
GRAVITY 82
GRAVITY_CONSTANT 53
gravity_method 98
gravity 9,21,26,35,37,38,46,53,68,92
GV_BINARY 82
G command 11,46,68
g command 8,68,107
head 33
help 68,84
hessian_epsilon 73
Hessian 42,108
hidden surfaces 4,84,111
HISTOGRAM 78
history list 65
HISTORY 79
homogeneous coordinates 5

HOMOTHETY 82
homothety 60,71,111
Hooke energy 98
HP 98731 4
H command 68
h command 68
h graphics command 84
ideal gas model 46,53,63,70,94
ideal gas 38,41
identifiers 47
identifier 47
id 34,72
IF 66
inequality constraint 57
information 68
initiallization 64
installation 2
INTEGRAL_ORDER 37,59
integration_order 73
INTERP_NORMALS 82
interrupts 87
interrupt 68
Iris 3
iteration_counter 73
iteration 6,8,42,68,107
i command 68
JIGGLE 53
jiggling 31,42,46,53,69,111
J command 46,69,111
j command 46,69,111
Kelvin tetrakaidecahedron 13
Kelvin 59
keywords 7,48
Klein hyperbolic metric 59
KLEIN_METRIC 35
knot energy 53,100
KUSNER 82
K command 69
k command 46,69
labels 88
length 72
lex 3
line splicing 47
LINEAR 79
lines 7
LIST 75,77
LOAD 79
Local Hooke energy 99
logging 68
LOGHISTOGRAM 78
long edges 69
LONGJ 79
longj 111
l command 69
l graphics command 8,83
Macintosh 2
macros 47
macro 9
mail 2
makefile 4
MAXCOORD 35
MAX 74
mean curvature integral 39,52
mean curvature 38,41,44,106
mean_curvature_integral 99
memory 68
MERIT_FACTOR 59
method instances 54
methods 96
METRIC 59
metric 35,59
midv 33,62,73
MIN 74
MOBILITY 59
mobility 43,80
motion 42
M command 34,69
m command 31,42,69
named elements 74
named quantities 96
named quantity 73
NeXT 2
NODISPLAY 62
NONNEGATIVE 57
NONPOSITVE 57
normal interpolation 70
NORMAL_CURVATURE 82
NORMAL_MOTION 82
normal_sq_mean_curvature 99
notching 70
notch_count 73
NOTCH 79
nulgraph 4
numbers 47
N command 69
n command 70
octahedron 31
OLD_AREA 82
omitted faces 41
omitting faces 9
optimizing scale factor 69
orientation 6,8,57,58,62,63,91
original 34,72
o command 13,70
painter algorithm 4,111
PC 2

periodic surfaces 35
PERIODS 51
perturbations 79,111
PHASEFILE 52
phases 52
PHASE 62
pipe 66
Pixar 70,87
pop_count 73
PostScript 70,88
POST_PROJECT 82
post_project 108
Power User 21,26
prescribed mean curvature 38,41
prescribed pressure 94
PRESSURE 41,53,63,94
pressure 34,38,41,42,46,68,71
PRINT 77
P command 70,87
p command 46,70
quadratic representation 34,35,69
QUADRATIC 51,79
quantities 34,35,39,40,56,57,58,70,96,104
QUANTITY 56,57
quantity 61,73
queries 72
QUIET 82
QUIETGO 82
QUIT 79
quit 9,70,71,84
quotient spaces 36
quotient space 51
Q command 41
q command 9,70
q graphics command 8,84
RAWESTV 79
RAWV 79
RAW_CELLS 82
READ 79,80
REBODY 79
RECALC 80
redirecting input 64
REFINE 75
refining 45,62,70,112
reset 84
RIBIERE 82
ribiere 108
Riemannian metric 35
rotate 83
Runge-Kutta 60
RUNGE_KUTTA 82
R graphics command 8,84
r command 9,70
r graphics command 8,83
save 68
scale factor 6,42,59,69
scale optimization 59
scale optimizing 68,107
SCALE_LIMIT 59
scale_scale 42,68
SCALE 59
scale 73
SET 76
SHADING 83
SHELL 80
SHOWQ 84
SHOW_EXPR 85
SHOW_INNER 83
SHOW_OUTER 83
SHOW_TRANS 85
SHOW 84
show 71
shrink 84
signals 87
Silicon Graphics 3
simplex model 34
simplex refining 112
SIMPLEX_REPRESENTATION 51
simplex_representation 73
skinny triangles 69
small facets 71
small triangles 113
soapfilm model 34,50
SoftImage 70,89
space_dimension 73
sphere example 26
sphere 6
SQGAUSS 83
squared Gaussian curvature 52,95
squared mean curvature 38,52,94
sq_mean_curvature 99
STABILITY_TEST 80
stability_test 80
stability 44
string model 34,46,50,58,62,63
SUM 74
surface energy integral 52,93
surface energy 21,27,34,37,38
surface tension 34,37,45,52,92
SURFACE_DIMENSION 51
surface_dimension 73
SURFACE_ENERGY 52
surface 6
SYMMETRIC_CONTENT 42,102
SYMMETRY_GROUP 51
symmetry_group 73

symmetry 36
s command 8,71
s graphics command 84
TAG 62
tag 34,72
tail 33
tank example 21
TEMPERATURE 53
temperature 42,46,69
TENSION 37,62
tetrakaidecahedron 13
THICKEN 83
thickening 70
time 60
tiny edges 71,113
toggles 80
topology 6,42,45,70,91
torus duplication 71
torus wrapping 33,35,45,62
TORUS_FILLED 35,51
torus_filled 73
TORUS_PERIODS 35
TORUS 35,51
torus 13,34,35,70,73,103
total_area 73
total_energy 73
total_length 73
TRANSFORMS 85
TRANSFORM_EXPR 85
translation 84
transparent 75
triangulation 45
triple junction 6
t command 13,24,29,71
t graphics command 13,84
unit cell 51
units 6
UNSET 76
user-defined functions 49
U command 71,108
U graphics command 13
u command 12,24,29,71,110
u graphics command 8,83
valence 72
valleys 84
vertex averaging 113
vertex popping 11,70,112
vertex_count 73
vertex_scalar_integral 96
VERTEX 61
VERTICES 7
vertices 6,33,61
view transform generators 61
view transforms 60
viewing matrix 60
VIEW_4D 85
VOLCONST 28,63
volume constraints 42
volume constraint 9,21,26,41,63,106
volumes 102
VOLUME 8,63
volume 34,41,46,68,69,71,72
v command 9,41,71
v graphics command 84
where_count 73
WHILE 66
whitespace 47
wrap 73
Wulff shape 31
Wulff vectors 4,31,37
WULFF 52
W command 71
w command 24,29,71
w graphics command 84
X-geomview 2
X-Windows 3
Xwindows 2,4
x command 71
x graphics command 84
yacc 3
y 71
ZOOM 80
zoom 72,84,114
Z command 72
z command 72
z graphics command 84